4" SQUARE (4S) **SHALLOW BOX**

DRAWN

1-1/4" DEEP 18.0 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW

▶ For Fixture/Luminaire Support of 50 lbs or less

Cat.	Knockouts		Std.
No.	Sides	Bottom	Pkg.
D4SSB-50	10 - 1/2"	4 - 1/2"	50



D4SSB-50

4" SQUARE (4S) BOXES **DRAWN**

1-1/2" DEEP

21.0 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW

BOXES WITH PIGTAIL FEATURES

▶ 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw

▶ For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Bracket & Setback	Knockouts		Std.
		Sides	Bottom	Pkg.
D4SB-50	-	12 - 1/2"	4 - 1/2"	50
D4SB-50-PT	-	12 - 1/2"	4 - 1/2"	50
D4SB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	50
*D4SB-50-FB	FB, Flush	9 - 1/2"	4 - 1/2"	24
*D4SB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24





D4SB-CKO



D4SB-50-PT



*D4SB-50-FB



D4SB-50/75







D4SB-75



4" SQUARE (4S) DEEP BOXES **DRAWN**

2-1/8" DEEP

30.3 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW

▶ For Fixture/Luminaire Support of 50 lbs or less

- ▶ 600V MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- Visit www.ul.com or QCIT Guide on page W1 for more information

Cat.	Bracket &	Knockouts		Std.
No.	Setback	Sides	Bottom	Pkg.
D4SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24













