

4" SQUARE (4S) DEEP BOXES

WELDED

2-1/8" DEEP

30.3 Cu. In.

**WITH RAISED GROUND EMBOSS
(EXCEPT FOR BRACKETED BOXES)**

METAL STUD BRACKET FEATURES


- ▶ U.S. Patent No.: 8,262,043 Metal Stud (MS) Bracket engages on either side of metal stud
- **Model Revised Feb. 2008

BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail pre-assembled with Ground Emboss and 10-32 Ground Screw
- ▶ 10" Pigtail for BSA Series, PT-10 and 4SDB-BP

BSA FEATURES

- ▶ Back Support Arm installed on this box provides support for studs up to 6" deep
- ▶ An excellent choice for pre-fab applications



Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SDB-50	-	12 - 1/2"	4 - 1/2"	24
4SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
*4SDB-75	-	8 - 3/4"	2 - 1/2", 2 - MKO	24
4SDB-75/100	-	4 - 3/4", 4 - 1"	2 - 1/2", 2 - 3/4"	24
4SDB-100	-	8 - 1"	2 - 1/2", 2 - 3/4"	24
*4SDB-MKO	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-MKO-PT	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-MKO-PT-10	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-50-FB	FB, Flush	9 - 1/2"	5 - 1/2"	24
4SDB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	3 - 1/2", 2 - 3/4"	24
4SDB-75-FB	FB, Flush	6 - 3/4"	1 - 1/2", 4 - 3/4"	24
4SDB-100-FB	FB, Flush	6 - 1"	3 - 1/2", 2 - 3/4"	24
*4SDB-MKO-FB	FB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-MS**	MS, Self-Gripping + Box Support Clip	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-WB	WB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-PT-BSA	Back Support Arm	8 - 1/2", 4 - MKO	1 - 1/2", 2 - MKO	24
4SDB-BP	Back Mounting Plate, see pg. P21 for more info.	8 - 1/2", 4 - MKO	-	24
4SDB-MKO-S NEW	-	8 - 1/2", 4 - MKO	1 - 1/2", 2 - MKO	24
4SDB-MKO-EXT	-	8 - 1/2", 4 - MKO	-	24

4SDB-MKO-S FEATURES

- ▶ Back-center K.O. replaced with through hole eliminating need for washer or punching back-center K.O. when mounting boxes in suspended application.

NOTE

- ▶ *Available in Durable Red Powder Coat Finish (pg. A24)
- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SDB-MKO-MS)

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit www.ul.com or QCIT Guide on page W1 for more information



See pg. P7-8 for full line of Ready-To-Install assembled product

