



**ZINC DIE CAST
METAL CLAD (MC)
CONNECTORS SADDLE-TYPE**

PRODUCT FEATURES

- ▶ Combo Head Set-Screw
- ▶ With Insulated Throat
- ▶ Suitable for Dry Location Only
- ▶ For AC, MCI-A, NM Cable, FMC/RWFMC

NOTE

- ▶ Insulated color may vary



Cat. No.	Description	KO Size	Std. Pkg.	Master Ctn.
OF6231	Steel AC: 14/2 (0.457") - 12/4 (0.539") Aluminum AC: 14/2 (0.464") - 10/4 (0.622") Steel MCI-A: 14/2 (0.453") - 10/4 (0.614") Aluminum MCI-A: 14/2 (0.433") - 10/3 (0.630") NM Cable: 12/3, 14/2 & 8/2 with ground. 12/2 without ground Steel/AL FMC/RWFMC: 3/8"	1/2"	100	500
OF6232	Steel Interlocking: 0.661 - 0.711 Dia. AL Interlocking: 0.775 - 0.825 Dia. Steel/AL AC: 0.650 - 0.810 Dia. Steel FMC: 1/2"	3/4"	50	250

**ZINC DIE CAST
METAL CLAD (MC) & AC (BX)
CONNECTOR SET-SCREW TYPE**

PRODUCT FEATURES

- ▶ For AC, MCI-A, FMC/RWFMC



Cat. No.	Description	KO Size	Std. Pkg.	Master Ctn.
OF653	Steel AC: 14/2 (0.453") - 10/4 (0.622") Aluminum AC: 14/2 (0.464") - 14/4 (0.535") Steel MCI-A: 14/2 (0.453") - 10/2 (0.581") Aluminum MCI-A: 14/2 (0.437") - 10/2 (0.535") Steel/AL FMC/RWFMC: 3/8"	1/2"	100	500

**ZINC DIE CAST
METAL CLAD (MC) & AC (BX)
CONNECTOR**

PRODUCT FEATURES

- ▶ For AC, MCI-A, NM Cable, FMC/RWFMC



Cat. No.	Description	KO Size	Std. Pkg.	Master Ctn.
OF6620	Steel AC: 14/2 (0.457") - 12/4 (0.539") Aluminum AC: 14/2 (0.464") - 14/4 (0.534") Steel MCI-A: 14/2 (0.453") - 10/2 (0.531") Aluminum MCI-A: 14/2 (0.433") - 14/4 (0.539") NM Cable: 12/3, 14/2 with ground & 12/2 without ground Steel/AL FMC/RWFMC: 3/8"	1/2"	100	500

**ZINC DIE CAST
METAL CLAD (MC)
CONNECTORS
CLAMP TYPE**

PRODUCT FEATURES

- ▶ With Insulated Throat
- ▶ Suitable for Dry Location Only

NOTE

- ▶ Insulated color may vary



Cat. No.	Cable Size Dia.	Trade Size	Std. Pkg.	Master Ctn.
*MC-CL-300	2.30" - 2.68"	3"	-	5
*MC-CL-350	2.85" - 3.42"	3-1/2"	-	5

**ZINC DIE CAST
COMBINATION AC (BX) &
NON-METALLIC (NM)
CONNECTOR**

PRODUCT FEATURES

- ▶ Suitable for Dry Location Only
- ▶ For AC, NM Cable, FMC/RWFMC, Cord



Cat. No.	Description	KO Size	Std. Pkg.	Master Ctn.
OF623	Steel/AL AC: 14/2 Steel/AL FMC/RWFMC: 3/8" NM Cable: 14/2 Cord: 0.340" - 0.380" Dia Cord 14/3 SJO, 16/3 SJO, 16/2 SO	1/2"	25	250

Electrical Fittings