

## LSL12 SERIES

### PRODUCT FEATURES

- ▶ Suitable for Outdoor Location
- ▶ Aluminum Alloy Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Tempered Glass with High Grade Weatherproof Gasket
- ▶ Pre-wired with 18" SJTW Cord
- ▶ Trunnion Mount & Spike Included
- ▶ Min Operating Temp: -20°C/-4°F
- ▶ 50,000 Life Hours
- ▶ 1 Year Limited Warranty

### CERTIFICATES



Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
<b>LSL12-6W-WW</b>	12V AC/DC	6W	3000K	350 lm	20W MH
<b>LSL12-6W-CW</b>		6W	5000K	350 lm	20W MH

## LFL13 SERIES

### PRODUCT FEATURES

- ▶ IP65 Rated for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ Ambient Operating Temp: -20°C / -4°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 3 Year Limited Warranty

### CERTIFICATES



Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
<b>LFL13-12WW-T-12V</b>	12V AC/DC	12W	3000K	1,270 lm	50W MH

## LFL12-12V SERIES

### PRODUCT FEATURES

- ▶ IP65 Rated for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 6H x 6V NEMA Type
- ▶ Ground Spike Included
- ▶ Ambient Operating Temp: -20°C / -4°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 3 Year Limited Warranty

### CERTIFICATES



Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
<b>LFL20-6WW-KN-12V</b>	12V AC/DC	6W	3000K	510 lm	35W MH
<b>LFL20-6CW-KN-12V</b>		6W	5000K	560 lm	35W MH

See Section I For More Low Voltage Lighting