

LFL20 SERIES

PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 6H x 6V NEMA Type
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES



LFL20-15W-KN



LFL20-28W-KN



LFL20-42W-KN

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LFL20-15W-WW-KN	120~277V	15W	3000K	1,770 lm	50W MH
LFL20-15W-CW-KN		15W	5000K	1,800 lm	50W MH
LFL20-28W-WW-KN		28W	3000K	3,304 lm	100W MH
LFL20-28W-CW-KN		28W	5000K	3,360 lm	100W MH
LFL20-42W-WW-KN		42W	3000K	5,250 lm	150W MH
LFL20-42W-CW-KN		42W	5000K	5,376 lm	150W MH

NEW LAL1 SERIES

PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ TYPE VS Distribution
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage Model (50W)
- ▶ Twist-Lock Photocell Included
- ▶ 0-10V Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES



90° Extension Arm Included

Wall Mount



Adjustable Wattage (50W model)

Adjustable Wattage DIP Switch with Cover
Weatherproof with cover on

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LAL1-50W-P-CW	120~277V	20W/ 30W/ 40W/ 50W	5000K	2,760 lm/ 4,140 lm/ 5,520 lm/ 6,435 lm	70W/ 100W/ 150W/ 175W MH
LAL1-80W-P-CW		80W		11,227 lm	250W MH

DIMMABLE

