

D14 | FLEX/AC/MC Fittings



ZINC DIE CAST 90° ANGLE AC (BX) MC/FLEX CONNECTORS SQUEEZE TYPE

PRODUCT FEATURES

- ▶ Suitable for dry location only
- ▶ For AC, MCI-A, FMC/RWFMC

Cat. No.	Flex/Cable Range	KO Size	Std. Pkg.	Master Ctn.
OF643	Steel AC: 14/2 (0.453") - 8/2 (0.647")	1/2"	25	250
	AL AC: 14/2 (0.453") - 10/4 (0.622")			
	Steel MCI-A: 14/2 (0.453") - 8/2 (0.669")			
OF644	Steel AC: 10/4 (0.648") - 8/3 (0.826")	1/2"	25	250
	AL AC: 10/4 (0.622") - 6/4 (0.905")			
	Steel MCI-A: 10/4 (0.622") - 6/3 (0.866")			
OF645	Steel AC: 6/4 (0.945") - 3/4 (1.185")	3/4"	25	250
	AL AC: 6/4 (0.925") - 2/4 (1.133")			
	Steel MCI-A: 8/4 (0.827") - 3/4 (1.185")			



Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
OF6463	1"	5	25
OF6464	1-1/4"	-	5
OF6465	1-1/2"	-	5
OF6466	2"	-	5
OF6467	2-1/2"	-	5
OF6468	3"	-	5
OF6469	3-1/2"	-	1
OF6470	4"	-	1



1" to 2"



2-1/2" to 4"

ZINC DIE CAST 90° ANGLE FLEX CONNECTORS SQUEEZE TYPE

STEEL EMT TO FLEX COUPLINGS SET-SCREW/DOUBLE-BITE SADDLE CLAMP TYPE

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Set-Screw type for EMT conduit
- ▶ Dual-gripping Saddle Clamp
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, MCI-A, HCF, RWFMC
- ▶ Suitable for dry location only

Cat. No.	Flex/Cable Range	EMT Size	Std. Pkg.	Master Ctn.
SEFSD-38	Steel AC: 14/2 (0.450") - 10/2 (0.660")	1/2"	25	100
	AL AC: 14/2(0.450") - 10/2 (0.660")			
	Steel MCI: 14/2 (0.450") - 10/2 (0.660")			
	AL MCI: 14/2 (0.450") - 10/2 (0.660")			
	AL MCI-A: 14/2 (0.400") - 10/3 (0.590")			
SEFSD-50	Steel AC: 12/4 (0.550") - 6/3 (0.920")	1/2"	25	100
	AL AC: 12/4 (0.550") - 6/3 (0.920")			
	Steel MCI: 10/4 (0.640") - 8/3 (0.920")			
	AL MCI: 10/4 (0.640") - 8/3 (0.920")			
	AL MCI-A: 12/4 (0.520") - 8/4 (0.770")			
SEFSD-75	Steel AC: 6/4 (0.930") - 4/3 (1.075")	3/4"	25	100
	AL AC: 8/3(0.680") - 4/3 (1.075")			
	Steel MCI: 8/3 (0.730") - 4/3 (1.075")			
	AL MCI: 6/4 (0.930") - 4/3 (1.075")			
	AL MCI-A: 8/4 (0.770") - 6/4 (1.110")			

