

STEEL EMT COUPLINGS COMPRESSION TYPE & RAIN-TIGHT

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Concrete-Tight

NOTE

- ▶ Sizes 2-1/2" to 4" are also listed for RIGID and IMC Conduits
- ▶ Compression Cap color may vary



Cat. No. Compression	Cat. No. Rain-Tight	Trade Size	Std. Pkg.	Master Ctn.
OF7611	OF7611-W	1/2"	25	250
OF7612	OF7612-W	3/4"	25	250
OF7613	OF7613-W	1"	10	100
OF7614	OF7614-W	1-1/4"	10	100
OF7615	OF7615-W	1-1/2"	10	50
OF7616	OF7616-W	2"	5	50
OF7617	OF7617-W	2-1/2"	-	12
OF7618	OF7618-W	3"	-	12
OF7619	OF7619-W	3-1/2"	-	6
OF7620	OF7620-W	4"	-	6



Compression Type



Rain-Tight

STEEL EMT TO LIQUID TIGHT COMBINATION COUPLINGS COMPRESSION TYPE

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Concrete-Tight
- ▶ Rain-Tight



Cat. No.	EMT Size	LT Size	Std. Pkg.	Master Ctn.
SELTC-50	1/2"	1/2"	25	250
SELTC-75	3/4"	3/4"	10	100
SELTC-100	1"	1"	10	100



3/4"



1"

STEEL RIGID TO EMT COMBINATION COUPLINGS THREADED/COMPRESSION TYPE

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Internally threaded for Rigid/IMC conduit
- ▶ Compression type for EMT conduit
- ▶ Rain-Tight
- ▶ Concrete-Tight



Cat. No.	RIGID Size	EMT Size	Std. Pkg.	Master Ctn.
SREC-50	1/2"	1/2"	25	100
SREC-75	3/4"	3/4"	25	100
SREC-100	1"	1"	10	40



1/2"

