

SPRING STEEL CONDUIT TO FLANGE CLIPS BOTTOM MOUNT, PUSH IN

PRODUCT FEATURES

- ▶ Supports conduit/pipe or cable from beam flanges
- ▶ Push-in Clip can pivot through 360°
- ▶ Requires only a hammer to install

Cat. No.	Flange Thickness	EMT Size	Rigid Size	Static Load (lbs.)	Std. Pkg.
F8P24	1/8" to 1/4"	1/2"	-	25	100
F8P58	5/16" to 1/2"	1/2"	-	25	100
F8P912	9/16" to 3/4"	1/2"	-	25	50
F12P24	1/8" to 1/4"	3/4"	1/2"	25	100
F12P58	5/16" to 1/2"	3/4"	1/2"	25	100
F12P912	9/16" to 3/4"	3/4"	1/2"	25	100
F16P24	1/8" to 1/4"	1"	3/4"	25	100
F16P58	5/16" to 1/2"	1"	3/4"	25	50
F16P912	9/16" to 3/4"	1"	3/4"	25	50



SPRING STEEL CONDUIT TO FLANGE CLIPS SIDE MOUNT, PUSH IN

PRODUCT FEATURES

- ▶ Supports conduit/pipe or cable from beam flanges
- ▶ Push-in Clip can pivot through 360°
- ▶ Requires only a hammer to install

Cat. No.	Flange Thickness	EMT Size	Rigid Size	Static Load (lbs.)	Std. Pkg.
F8P24SM	1/8" to 1/4"	1/2"	-	15	100
F8P58SM	5/16" to 1/2"	1/2"	-	15	100
F8P912SM	9/16" to 3/4"	1/2"	-	15	100
F12P24SM	1/8" to 1/4"	3/4"	1/2"	15	100
F12P58SM	5/16" to 1/2"	3/4"	1/2"	15	100
F12P912SM	9/16" to 3/4"	3/4"	1/2"	15	50
F16P24SM	1/8" to 1/4"	1"	3/4"	15	100
F16P58SM	5/16" to 1/2"	1"	3/4"	15	100
F16P912SM	9/16" to 3/4"	1"	3/4"	15	50



SPRING STEEL CABLE/CONDUIT TO ROD/WIRE CLIPS, SNAP CLOSE

PRODUCT FEATURES

- ▶ Provides attachment of conduit and boxes
- ▶ Snap-close Clip can pivot through 360°
- ▶ Easy Installation

Cat. No.	EMT/Rigid Size	FMC Size	MC/AC Size	Flange Thickness	Rod Size	Wire Size	Std. Pkg.
F4Z346M	-	3/8"	14/2 to 12/3	1/8" to 3/8"	1/4"	#12	100
F4Z34812M	1/2", 3/4"	-	-	1/8" to 3/8"	1/4"	#12	100
F6Z34812M	1/2", 3/4"	-	-	3/8" to 7/16"	3/8"	-	100
F4Z3416M	1"	-	-	1/8" to 3/8"	1/4"	#12	100
F6Z3416M	1"	-	-	3/8" to 7/16"	3/8"	-	100

