

G15 | Occupancy Sensors



OCCUPANCY SENSORS

PRODUCT FEATURES

- ▶ Turn lights ON/OFF automatically
- ▶ With manual ON/OFF pushbutton
- ▶ Adjustable time delay from 15 seconds to 30 minutes
- ▶ Adjustable sensitivity settings
- ▶ 2 year warranty
- ▶ Standard decorative wall plate included
- ▶ For **MAGNETIC BALLAST** only

NOTE

- ▶ Neutral wire required

TITLE 24
COMPLIANT 

Cat. No.	Description	Color (Cat. No. - Color Code)			Std. Pkg.
		White	Ivory	Almond	
*OS-P	Passive Infrared Occupancy Sensor, 150°, 450 Sq. Ft. Coverage RATING: Incandescent: 500W @120VAC Fluorescent: 500VA @120VAC Motor: 1/8HP@ 120VAC	OS-P-W	OS-P-I	-	10



OCCUPANCY SENSORS

PRODUCT FEATURES

- ▶ Turn lights ON/OFF automatically
- ▶ Use as regular switch with manual ON/OFF setting
- ▶ Adjustable time delay from 15 seconds to 30 minutes
- ▶ Adjustable sensitivity settings
- ▶ 2 year warranty
- ▶ Standard decorative wall plate included
- ▶ For **MAGNETIC BALLAST** only

NOTE

- ▶ Neutral wire required

Cat. No.	Description	Color (Cat. No. - Color Code)			Std. Pkg.
		White	Ivory	Almond	
*OS-S	Passive Infrared Occupancy Sensor, 150°, 450 Sq. Ft. Coverage RATING: Incandescent: 500W @120VAC Fluorescent: 500VA @120VAC Motor: 1/8HP@ 120VAC	OS-S-W	OS-S-I	-	10



NOTE: Occupancy Sensors should be initially left ON for 4-5 minutes for first time to function properly.