

# H5 | LED Wall Packs

## \*AWC-LWP4 SERIES

### PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Prismatic Borosilicate molded Lens with weatherproof gasket
- ▶ TYPE IV Distribution
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage & CCT
- ▶ Pre-installed Photozell With Cover
- ▶ 0-10V Dimmable
- ▶ 5 Year Limited Warranty

### CERTIFICATES



Photozell Included



CCT and Wattage Adjustment Knobs Inside

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
AWC-LWP4-30W-P	120~277V	15W/ 20W/ 25W/ 30W	3000K/ 4000K/ 5000K/ 5700K	1,935 lm/ 2,580 lm/ 3,225 lm/ 3,824 lm	70W/ 100W/ 150W MH
AWC-LWP4-60W-P		20W/ 30W/ 50W/ 60W		2,600 lm/ 3,900 lm/ 6,500 lm/ 7,200 lm	70W/ 150W/ 175W MH
AWC-LWP4-80W-P		20W/ 40W/ 60W/ 80W		2,700 lm/ 5,400 lm/ 8,100 lm/ 10,502 lm	70W/ 150W/ 250W MH
AWC-LWP4-120W-P		50W/ 80W/ 100W/ 120W		6,200 lm/ 9,920 lm/ 12,400 lm/ 15,057 lm	175W/ 250W/ 400W MH

## \*LWP4 SERIES

### PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Prismatic Borosilicate molded Lens with weatherproof gasket
- ▶ TYPE IV Distribution
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

### CERTIFICATES



Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LWP4-30W-CW	120~277V	30W	5000K	4,145 lm	150W MH
LWP4-50W-CW		50W		6,750 lm	175W MH
LWP4-80W-CW		80W		11,360 lm	250W MH
LWP4-120W-CW		120W		15,840 lm	400W MH

## ACCESSORIES Sold Separately



LWP2-S: Fits 50W and 80W models  
LWP2-120W-S: Fits 120W model

Cut-off Shrouds



PC-1F  
PC-1F-277

PC-1S

PC-1SH

Photocells

SCAN FOR MORE INFO

