

ZINC DIE CAST DUPLEX AC (BX) FLEX/MC CONNECTOR

PRODUCT FEATURES

- Suitable for Dry Location Only
- For AC, MCI-A, NM Cable, FMC/RWFMC



Cat. No.	Description	KO Size	Std. Pkg.	Master Ctn.
MC-DX-50	Steel AC: 14/2 (0.457") - 12/4 (0.539")	1/2"	25	250
	Aluminum AC: 14/2 (0.464") - 10/4 (0.622")			
	Steel MCI-A: 14/2 (0.453") - 10/4 (0.614")			
	Aluminum MCI-A: 14/2 (0.433") - 10/3 (0.630")			
	NM Cable: 12/3, 14/2 with ground 12/2 without ground Steel/AL FMC/RWFMC: 3/8"			

STAMPED STEEL 1-HOLE MC(BX) CABLE STRAP

PRODUCT FEATURES

- Electroplated Zinc
- Corrosion-resistant



Cat. No.	Description	Std. Pkg.	Master Ctn.
S1-38	12-2, 12-3, 10-2, 10-3 MC (BX) 1-Hole Strap	100	1000

STAMPED STEEL SADDLE TYPE STRUT CLAMPS

PRODUCT FEATURES

- Electroplated Zinc
- Tri-Combo Hex Screw Head
- Wide Saddle Design



Cat. No.	EMT/Rigid/FMC Conduit Size	Cable O.D. Range	Std. Pkg.
STS-50	5/16" - 1/2"	0.260" - 0.890"	100
STS-75	3/4"	0.670" - 1.090"	100
STS-100	1"	0.890" - 1.450"	100
STS-125	1-1/4"	1.150" - 1.700"	50
STS-150	1-1/2"	1.350" - 2.000"	50
STS-200	2"	1.875" - 2.570"	50
STS-250	2-1/2"	2.500" - 3.060"	25
STS-300	3"	3.000" - 3.600"	25
STS-350	3-1/2"	3.600" - 4.100"	25
STS-400	4"	4.100" - 4.700"	25

STAMPED STEEL NAIL STRAPS

PRODUCT FEATURES

- Electroplated Zinc

NOTES

- Varies according to sizes



Cat. No.	EMT Size	Flex/Rigid Size	Std. Pkg.	Master Ctn.
NS-50	1/2"	3/8"	100	1000
NS-50/75	3/4"	1/2"	100	1000
NS-100	1"	3/4"	100	1000

ANTI-SHORT BUSHINGS THERMOPLASTIC

PRODUCT FEATURES

- High-Temperature Plastic
- Fits BX (AC) and Flex Conduits



Cat. No.	For Use With	Trade Size	Std. Pkg.	Master Ctn.
ASB-516	14/2, 14/3, 12/2	5/16"	35	3500
ASB-38	14/4, 12/3, 6/1, 4/1	3/8"	35	2100
ASB-716	12/4, 10/2, 10/3, 2/1	7/16"	35	700
ASB-50	10/4, 8/2, 8/3, 1/1	1/2"	20	400
ASB-75	8/4, 6/2, 4/2, 4/3, 6/4	3/4"	16	320

