

MALLEABLE IRON 45° ANGLE LIQUID TIGHT CONNECTORS

PRODUCT FEATURES

- ▶ Electroplated Zinc



| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|-----------|------------|-----------|-------------|
| MLT45-38 | 3/8" | 25 | 150 |
| MLT45-50 | 1/2" | 25 | 150 |
| MLT45-75 | 3/4" | 10 | 100 |
| MLT45-100 | 1" | 5 | 50 |
| MLT45-125 | 1-1/4" | 5 | 40 |
| MLT45-150 | 1-1/2" | 4 | 20 |
| MLT45-200 | 2" | 1 | 15 |
| MLT45-250 | 2-1/2" | - | 1 |
| MLT45-300 | 3" | - | 1 |
| MLT45-350 | 3-1/2" | - | 1 |
| MLT45-400 | 4" | - | 1 |



MALLEABLE IRON INSULATED 45° ANGLE LIQUID TIGHT CONNECTORS

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ With Insulated Throat

NOTE

- ▶ Insulated color may vary



| Cat. No. | Trade Size | Std. Pkg. | Master Ctn. |
|------------|------------|-----------|-------------|
| MLTI45-38 | 3/8" | 25 | 150 |
| MLTI45-50 | 1/2" | 25 | 150 |
| MLTI45-75 | 3/4" | 10 | 100 |
| MLTI45-100 | 1" | 5 | 50 |
| MLTI45-125 | 1-1/4" | 5 | 40 |
| MLTI45-150 | 1-1/2" | 4 | 20 |
| MLTI45-200 | 2" | 1 | 15 |
| MLTI45-250 | 2-1/2" | - | 1 |
| MLTI45-300 | 3" | - | 1 |
| MLTI45-350 | 3-1/2" | - | 1 |
| MLTI45-400 | 4" | - | 1 |



MALLEABLE IRON INSULATED 45° ANGLE LIQUID TIGHT CONNECTORS WITH ALUMINUM LAY-IN LUG

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ 105°C rated insulated throat
- ▶ Sealing washer included
- ▶ Aluminum lay-in lug provides easy installation of a ground wire

NOTE

- ▶ Insulated color may vary



| Cat. No. | Trade Size | Lug Range | Std. Pkg. | Master Ctn. |
|--------------|------------|--------------|-----------|-------------|
| MLTI45LL-38 | 3/8" | #14 - #4 | 10 | 100 |
| MLTI45LL-50 | 1/2" | #14 - #4 | 10 | 100 |
| MLTI45LL-75 | 3/4" | #14 - #4 | 10 | 100 |
| MLTI45LL-100 | 1" | #14 - #4 | 5 | 50 |
| MLTI45LL-125 | 1-1/4" | #14 - #4 | - | 5 |
| MLTI45LL-150 | 1-1/2" | #14 - #4 | - | 5 |
| MLTI45LL-200 | 2" | #14 - #4 | - | 5 |
| MLTI45LL-250 | 2-1/2" | #14 - #1/0 | - | 1 |
| MLTI45LL-300 | 3" | #14 - #1/0 | - | 1 |
| MLTI45LL-350 | 3-1/2" | #6 - #250MCM | - | 1 |
| MLTI45LL-400 | 4" | #6 - #250MCM | - | 1 |



3/4"

1-1/4"

