

# D48 | Combination Fittings



## STEEL EMT TO FLEX COUPLINGS SET-SCREW/DOUBLE-BITE SADDLE CLAMP TYPE

### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Set-Screw type for EMT conduit
- ▶ Dual-gripping Saddle Clamp
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, MCI-A, HCF, RWFMC
- ▶ Suitable for dry location only

Cat. No.	Flex/Cable Range	EMT Size	Std. Pkg.	Master Ctn.
<b>SEFSD-38</b>	Steel AC: 14/2 (0.450") - 10/2 (0.660")	Steel HCF AC: 14/2 (0.450") - 10/2 (0.660")	1/2"	25 100
	AL AC: 14/2(0.450") - 10/2 (0.660")	AL HCF AC: 14/2 (0.450") - 10/2 (0.660")		
	Steel MCI: 14/2 (0.450") - 10/2 (0.660")	HCF MCI-A: 14/2 (0.400") - 10/3 (0.590")		
	AL MCI: 14/2 (0.450") - 10/2 (0.660")	Steel/AL FMC/RWFMC/XRWFMC: 3/8"		
	AL MCI-A: 14/2 (0.400") - 10/3 (0.590")			
<b>SEFSD-50</b>	Steel AC: 12/4 (0.550") - 6/3 (0.920")	Steel HCF AC: 12/4 (0.550") - 6/3 (0.920")	1/2"	25 100
	AL AC: 12/4 (0.550") - 6/3 (0.920")	AL HCF AC: 12/4 (0.550") - 6/3 (0.920")		
	Steel MCI: 10/4 (0.640") - 8/3 (0.920")	HCF MCI-A: 12/4 (0.520") - 8/4 (0.770")		
	AL MCI: 10/4 (0.640") - 8/3 (0.920")	Steel/AL FMC/RWFMC/XRWFMC: 1/2"		
	AL MCI-A: 12/4 (0.520") - 8/4 (0.770")			
<b>SEFSD-75</b>	Steel AC: 6/4 (0.930") - 4/3 (1.075")	Steel HCF AC: 6/4 (0.930") - 4/3 (1.075")	3/4"	25 100
	AL AC: 8/3(0.680") - 4/3 (1.075")	AL HCF AC: 8/3 (0.680") - 4/3 (1.075")		
	Steel MCI: 8/3 (0.730") - 4/3 (1.075")	HCF MCI-A: 8/4 (0.770") - 6/4 (1.110")		
	AL MCI: 6/4 (0.930") - 4/3 (1.075")	Steel/AL FMC/RWFMC/XRWFMC: 3/4"		
	AL MCI-A: 8/4 (0.770") - 6/4 (1.110")			



## STEEL EMT TO FLEX COUPLINGS COMPRESSION/DOUBLE-BITE SADDLE CLAMP TYPE

### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Compression type for EMT conduit
- ▶ Dual-gripping Saddle Clamp
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, MCI-A, HCF, RWFMC
- ▶ Suitable for dry location only

Cat. No.	Flex/Cable Range	EMT Size	Std. Pkg.	Master Ctn.
<b>SEFCD-50</b>	Steel AC: 12/4 (0.550") - 6/3 (0.920")	Steel HCF AC: 12/4 (0.550") - 6/3 (0.920")	1/2"	25 100
	AL AC: 12/4 (0.550") - 6/3 (0.920")	AL HCF AC: 12/4 (0.550") - 6/3 (0.920")		
	Steel MCI: 10/4 (0.640") - 8/3 (0.920")	HCF MCI-A: 12/4 (0.520") - 8/4 (0.770")		
	AL MCI: 10/4 (0.640") - 8/3 (0.920")	Steel/AL FMC/RWFMC/XRWFMC: 1/2"		
	AL MCI-A: 12/4 (0.520") - 8/4 (0.770")			
<b>SEFCD-75</b>	Steel AC: 6/4 (0.930") - 4/3 (1.075")	Steel HCF AC: 6/4 (0.930") - 4/3 (1.075")	3/4"	25 100
	AL AC: 8/3(0.680") - 4/3 (1.075")	AL HCF AC: 8/3 (0.680") - 4/3 (1.075")		
	Steel MCI: 8/3 (0.730") - 4/3 (1.075")	HCF MCI-A: 8/4 (0.770") - 6/4 (1.110")		
	AL MCI: 6/4 (0.930") - 4/3 (1.075")	Steel/AL FMC/RWFMC/XRWFMC: 3/4"		
	AL MCI-A: 8/4 (0.770") - 6/4 (1.110")			



## STEEL RIGID TO EMT COMBINATION COUPLINGS SET-SCREW TYPE

### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Concrete-Tight when taped

Cat. No.	Rigid Size	EMT Size	Std. Pkg.	Master Ctn.
<b>SRECS-50</b>	1/2"	1/2"	25	250
<b>SRECS-75</b>	3/4"	3/4"	10	100
<b>SRECS-100</b>	1"	1"	10	100



1/2" to 3/4"

1"