

# G17 | Single Receptacles

## COMMERCIAL GRADE

### SINGLE RECEPTACLES

#### PRODUCT FEATURES

- ▶ 125 VAC or 250 VAC
- ▶ Impact-Resistant Thermoplastic Body
- ▶ **With integral ground contacts locked into back, body, & face to prevent strap separation**
- ▶ Up to #10AWG Side Wire
- ▶ With Combination Head Screws
- ▶ Meets NEC Article 406.12 for tamper-resistant receptacles (for more information see Section W)

For use with:

Wallplates	
LEXAN	Stainless Steel
OP7	OS7

For complete wallplate section, see pg. G25 to G31

Industrial Covers	
4S Box	5S Box
4403	5503

For complete industrial cover section, see pg. A13 & A20

Cat. No.	Description	Color (Cat. No. - Color Code)		Std. Pkg.	Master Carton
		White	Ivory		
SR15	15A, 125V Single Receptacle	SR15-W	*SR15-I	10	200
SR15-TR	15A, 125V Single Receptacle, <b>Tamper Resistant</b>	*SR15-TR-W	*SR15-TR-I	10	200
SR20	20A, 125V Single Receptacle	SR20-W	SR20-I	10	200
SR20-TR	20A, 125V Single Receptacle, <b>Tamper Resistant</b>	SR20-TR-W	*SR20-TR-I	10	200
SR15-250	15A, 250V Single Receptacle	SR15-250-W	*SR15-250-I	10	200
SR20-250	20A, 250V Single Receptacle	SR20-250-W	SR20-250-I	10	200



## INDUSTRIAL GRADE

### SINGLE RECEPTACLES

#### PRODUCT FEATURES

- ▶ 125~250 VAC
- ▶ Impact-Resistant Thermoplastic Body
- ▶ #10 to #4 AWG Back Terminals

For use with:

Wallplate	
Stainless Steel	
OS703	

For complete wallplate section, see pg. G25 to G31

Industrial Covers	
4S Box	5S Box
4407	5507

For complete industrial cover section, see pg. A13 & A20

Cat. No.	Description	Color (Cat. No. - Color Code)		Dia.	Std. Pkg.	Master Carton
		Black	White			
R50-3	50A, 3-Pole, <b>3-Wire Range Receptacle</b> , NEMA 10-50R	R50-3	-	2.11"	10	40
R30-3	30A, 3-Pole, <b>3-Wire Dryer Receptacle</b> , NEMA 10-30R	R30-3	-	2.11"	10	40
R50-4	50A, 3-Pole, <b>4-Wire Range Receptacle</b> , NEMA 14-50R	R50-4	R50-4-W	2.11"	10	40
R30-4	30A, 3-Pole, <b>4-Wire Dryer Receptacle</b> , NEMA 14-30R	R30-4	R30-4-W	2.11"	10	40

