



ESI


SELF-ILLUMINATING LOW-LEVEL EXIT SIGN

PRODUCT FEATURES

- ▶ Non-Electrical, Non-Nuclear
- ▶ Non-Radioactive
- ▶ UL Listed
- ▶ Minimum 5 Foot-Candles (54 Lux) external unfiltered Fluorescent
- ▶ 90 minutes of illumination upon failure of utility power
- ▶ Rated viewing distance of 50 feet
- ▶ Aluminum Body
- ▶ Photoluminescent Surface
- ▶ Built-in wall mount
- ▶ Field Applied Chevrons Included
- ▶ Single face only
- ▶ Indoor use only



(From Top) ESI-G/ESI-R



Mounting Bracket Included



Illuminated



Cat. No.	Letter Color
ESI	R (Red) G (Green)

ESN


SELF-ILLUMINATING TRITIUM (NUCLEAR) EXIT SIGN

PRODUCT FEATURES

- ▶ Tritium-Powered Self-Illuminating
- ▶ Non-Electrical, Nuclear
- ▶ UL Listed for Wet Location
- ▶ Non-Radioactive and Non-Explosive
- ▶ 10 Foot candles ambient lighting
- ▶ 90 minutes of illumination upon failure of utility power
- ▶ Rated viewing distance of 100 feet
- ▶ Surface Mount Bracket
- ▶ Letter-shaped light tubes for best lighting
- ▶ Field applied chevrons included



ESN-B-G-1



Cat. No.	Housing Color	Faceplate	No. of Faces	Life in Years
ESN	W (White) B (Black)	R (Red) G (Green)	1 2	10 20