


A16 | 5S Boxes

**4-11/16" SQUARE (5S)
SHALLOW BOX &
EXTENSION RING**
WELDED
1-1/2" DEEP


29.5 Cu. In.

**WITH RAISED GROUND EMBOSS
(EXCEPT FOR EXTENSION RING)**

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SSB-MKO	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
5SSB-MKO-EXT	8 - 1/2", 4 - MKO	-	24



5SSB-MKO



5SSB-MKO-EXT

**4-11/16" SQUARE (5S)
BOXES**
DRAWN
2-1/8" DEEP

42.0 Cu. In.

**WITH RAISED GROUND EMBOSS
& 10-32 GROUND SCREW**


PRODUCT FEATURES

- ▶ Back-center KO on D5SDB-CKO-S is replaced with a 0.27" diameter hole for use of 1/4" making for fast and efficient installation


BOXES WITH PIGTAIL FEATURES

- ▶ 10" Pigtail for D5SDB-CKO-PT-10


Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D5SDB-50/75	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO	2 - 1/2", 10 - CKO	2 - 1/2", 2 - 3/4"	24
*D5SDB-CKO-PT-10	2 - 1/2", 10 - CKO	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO-S	2 - 1/2", 10 - CKO	3 - 3/4"	24




D5SDB-50/75




D5SDB-CKO



*D5SDB-CKO-PT-10



D5SDB-CKO-S



Secure D5SDB-CKO-S to ceiling with just a 1/4" rod and locknut



- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit www.ul.com or QCIT Guide on page W1 for more information