

## ZINC DIE CAST COMBINATION AC (BX) & NON-METALLIC (NM) CONNECTORS

### PRODUCT FEATURES

- ▶ Suitable for dry location only
- ▶ For AC, NM Cable, FMC/RWFMC, Cord

## ZINC DIE CAST NON-METALLIC CABLE CONNECTORS

### NOTE

- ▶ Sizes 1" to 2" are also suitable for service entrance

Cat. No.	FLEX/Cable Range	KO Size	Std. Pkg.	Master Ctn.
OF623	Steel/AL AC: 14/2 Steel/AL FMC/RWFMC: 3/8" NM Cable: 14/2 Cord: 0.340" - 0.380" Dia Cord 14/3 SJO, 16/3 SJO, 16/2 SO	1/2"	25	250



Cat. No.	For Use With	Trade Size	Std. Pkg.	Master Ctn.
RX-50	(1) 14/2 to 10/2 NM, (2) 14/2 or (2) 12/2 NM, 0.340" to 0.380" Dia. Flex Cord (Dry Location) 14/3, 16/2, and 16/3 SJO	1/2"	100	1000
RX-75	(2) 14-2 NM, AWG, 0.340" to 0.515" Dia. Flex Cord (Dry Location) 14/3, 14/2 SJO	3/4"	25	250

### For Service Entrance

RX-100	(4) 14/2, (1) 8/3, 8/2, 6/2, 6/3, 4/2, 4/3 NM (1) 2 SE Cable	1"	10	100
RX-125	4/3 or 2/3 NM	1-1/4"	5	50
RX-150	3-2/0 or 3-4/0 NM	1-1/2"	5	50
RX-200	3-2/0 or 3-4/0 NM	2"	5	50



## ZINC DIE CAST WATERTIGHT SERVICE ENTRANCE CABLE CONNECTORS

### PRODUCT FEATURES

- ▶ Watertight



Cat. No.	Trade Size	Wire Size	Grommet Opening	Std. Pkg.	Master Ctn.
WECC-100-8	1"	#8	0.40" - 0.68"	10	100
WECC-100-6	1"	#6	0.44" - 0.70"	10	100
WECC-100-4	1"	#4	0.52" - 0.84"	10	100
WECC-125-3	1-1/4"	#3	0.56" - 0.92"	10	50
WECC-125-2	1-1/4"	#2	0.60" - 1.00"	10	50
WECC-125-1	1-1/4"	#1	0.65" - 1.09"	10	50
WECC-150-10	1-1/2"	#1/0	0.72" - 1.24"	5	50
WECC-150-20	1-1/2"	#2/0	0.86" - 1.34"	5	50
WECC-150-30	1-1/2"	#3/0	0.87" - 1.37"	5	50
WECC-200-10	2"	#1/0	0.72" - 1.24"	5	25
WECC-200-20	2"	#2/0	0.86" - 1.34"	5	25
WECC-200-30	2"	#3/0	0.87" - 1.34"	5	25
WECC-200-40	2"	#4/0	0.90" - 1.50"	5	25
WECC-200-40N	2"	#4/0	1.11" - 1.73"	5	25

