



**SPRING STEEL**  
CONDUIT TO FLANGE CLIPS  
BOTTOM MOUNT, SNAP CLOSE

**PRODUCT FEATURES**

- ▶ Supports conduit/pipe or cable from beam flanges
- ▶ Snap-close Clip can pivot through 360°
- ▶ Requires only a hammer to install

Cat. No.	Flange Thickness	EMT/Rigid Size	FMC Size	MC/AC Size	Static Load (lbs.)	Std. Pkg.
F6M24	1/8" to 1/4"	-	3/8"	14/2 to 12/3	75	100
F6M58	5/16" to 1/2"	-	3/8"	14/2 to 12/3	75	100
F6M912	9/16" to 3/4"	-	3/8"	14/2 to 12/3	75	100
F812M24	1/8" to 1/4"	1/2", 3/4"	-	-	75	100
F812M58	5/16" to 1/2"	1/2", 3/4"	-	-	75	100
F812M912	9/16" to 3/4"	1/2", 3/4"	-	-	75	100
F16M24	1/8" to 1/4"	1"	-	-	75	100
F16M912	9/16" to 3/4"	1"	-	-	75	50



**SPRING STEEL**  
CONDUIT TO FLANGE CLIPS  
SIDE MOUNT, SNAP CLOSE

**PRODUCT FEATURES**

- ▶ Supports conduit/pipe or cable from beam flanges
- ▶ Snap-close Clip can pivot through 360°
- ▶ Requires only a hammer to install

Cat. No.	Flange Thickness	EMT/Rigid Size	FMC Size	MC/AC Size	Static Load (lbs.)	Std. Pkg.
F6M24SM	1/8" to 1/4"	-	3/8"	14/2 to 12/3	25	100
F6M58SM	5/16" to 1/2"	-	3/8"	14/2 to 12/3	25	100
F6M912SM	9/16" to 3/4"	-	3/8"	14/2 to 12/3	25	100
F812M24SM	1/8" to 1/4"	1/2", 3/4"	-	-	25	100
F812M58SM	5/16" to 1/2"	1/2", 3/4"	-	-	25	100
F812M912SM	9/16" to 3/4"	1/2", 3/4"	-	-	25	100
F16M24SM	1/8" to 1/4"	1"	-	-	25	100
F16M58SM	5/16" to 1/2"	1"	-	-	25	100
F16M912SM	9/16" to 3/4"	1"	-	-	25	100
F20M24SM	1/8" to 1/4"	1-1/4"	-	-	25	100
F20M58SM	5/16" to 1/2"	1-1/4"	-	-	25	100
F20M912SM	9/16" to 3/4"	1-1/4"	-	-	25	100
F24M24SM	1/8" to 1/4"	1-1/2"	-	-	25	50
F24M58SM	5/16" to 1/2"	1-1/2"	-	-	25	50
F24M912SM	9/16" to 3/4"	1-1/2"	-	-	25	50
F32M24SM	1/8" to 1/4"	2"	-	-	25	50
F32M58SM	5/16" to 1/2"	2"	-	-	25	50
F32M912SM	9/16" to 3/4"	2"	-	-	25	50



**SPRING STEEL**  
CONDUIT TO ANGLE PURLIN CLIP

**PRODUCT FEATURES**

- ▶ Provides attachment for conduit/pipe or cable to angle purlins
- ▶ Snap-close Clip can pivot through 360°
- ▶ Requires only a hammer to install

Cat. No.	EMT/Rigid Size	Flange Thickness	Static Load (lbs.)	Std. Pkg.
F123812M	1/2", 3/4"	3/32" MAX	100	100

