



Bracket Specification


BRACKET TYPE	AB	B (for S)	FB (for S)	FB (for FSB)	FB (for R)	FB (for H)	LB	MS	OB	WB
Length	5-7/8"	3"	7-3/8"	5-1/2"	7-1/4"	7"	2 - 3/8"	2-1/2"	6-3/4"	7-1/2"
Width	7/8"	2"	1-9/16"	2-1/8"	3/4"	1"	2 - 23/32"	1-3/8"	1-3/16"	1-9/16"
Offset	0" (Flush)	0" (Flush)	0" (Flush)	9/16"	1/2"	9/16"	1/4"	0" (Flush)	1-5/16"	0" (Flush)




"AB" 90° BRACKET
Positions box against face and side of stud.




"B" BRACKET for Square Box
Face mounts on front edge of wood stud.




"FB" BRACKET for Square Box
Mounts on flat side of stud.




"FB" BRACKET for FSB
Flush-Mounts on flat side of stud or joist.




"FB" BRACKET for Round Box
Offset Mounts on flat side of stud or joist.




"FB" BRACKET for Handy Box
Mounts on flat side of stud.




"LB" BRACKET
With spurs, slotted holes for toe-nailing.



"MS" BRACKET
Self-Gripping Metal Stud Bracket with Box Support Clip.
***Model Revised Feb. 2008**




"OB" BRACKET
Positions box away from side of stud for door frame trim clearance.




"WB" BRACKET
With positioning spurs to mount box on side of stud.


Clamp Specification




"BX/MC" Clamp
Accommodates Metal Clad Cables from size #14-2 to #10-4
****All MC series boxes are suitable for use with MCI-A Type**



"NM" Clamp
Accommodates #14-2 to #10-3 Non-Metallic Cables with ground



"NM" Clamp for Pancake Box
Accommodates #14-2 Non-Metallic Sheathed Cables with ground



"NM" Clamp for Beveled Switch Box
Accommodates #14-2 to #10-3 Non-Metallic Sheathed Cables with ground. 45° & 90° Screw Mounting.

Knockout & Pryout Specification

