

D16 | FLEX/AC/MC Fittings



ZINC DIE CAST RIGID TO FLEX COUPLING CLAMP TYPE

PRODUCT FEATURES

- ▶ For Steel FLEX Only

Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
OF697	1/2"	25	250



ZINC DIE CAST RIGID TO FLEX COUPLINGS SET-SCREW TYPE

PRODUCT FEATURES

- ▶ For Steel FLEX Only

Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
OF694	1/2"	25	250
OF695	3/4"	25	250



ZINC DIE CAST INSULATED DOUBLE-SNAP CABLE CONNECTOR

PRODUCT FEATURES

- ▶ 105°C rated throat insulator
- ▶ Fast and Tool-free installation
- ▶ Removable and Reusable
- ▶ For AC, MCI, MCI-A, HCF, RWFMC
- ▶ Dry location

Cat. No.	Description	KO Size	Std. Pkg.
DSC-38	DOUBLE-SNAP CABLE CONNECTOR WITH INSULATOR Steel/AL AC: 14/2 (0.40") - 10/3 (0.618") Steel MCI: 0.395" - 0.638" AL MCI: 0.40" - 0.618" Steel/AL MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL HCF MCI-A: 14/2 (0.395") - 10/3 (0.638") AL RWFMC: 3/8"	1/2"	50



ZINC DIE CAST INSULATED CUT-IN DOUBLE-SNAP CABLE CONNECTOR

PRODUCT FEATURES

- ▶ 105°C rated throat insulator
- ▶ Fast and Tool-free installation
- ▶ Removable and Reusable
- ▶ For FMC, AC, MCI, MCI-A, HCF
- ▶ Dry location

Cat. No.	Description	KO Size	Std. Pkg.
DSC-38C	CUT-IN DOUBLE-SNAP CABLE CONNECTOR WITH INSULATOR, FOR OLD WORK Steel/AL AC: 14/2 (0.40") - 10/3 (0.618") Steel/AL MCI: 14/2 (0.395") - 10/3 (0.638") Steel/AL MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL HCF MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL FMC: 3/8"	1/2"	50

