

STEEL "FASTLOCK" CONNECTOR

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Saddle-Base Connector
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, HCF AC, MCI-A, HCF MCI-A, FMC/RWFMC

NOTE

- ▶ Insulated color may vary

Cat. No.	Description	K.O. Size	Std. Pkg.	Master Ctn.
FLC-50	Steel AC 14/2 (0.475") - 10/3 (0.565") AL AC 14/2 (0.464") - 10/3 (0.610") Steel MCI: 14/2 (0.455") - 10/3 (0.565") AL MCI: 14/2 (0.455") - 10/3 (0.600") Steel HCF AC: 14/2 (0.475") - 10/3 (0.565") AL HCF AC: 14/2 (0.464") - 10/3 (0.610") AL MCI-A: 14/2 (0.385") - 10/3 (0.510") HCF MCI-A: 14/2 (0.385") - 10/3 (0.510") Steel/AL FMC/RWFMC: 3/8"	1/2"	50	500



STEEL "FASTLOCK" WIDE-THROAT CONNECTORS

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Saddle-Base Connector
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, HCF AC, MCI-A, HCF MCI-A, FMC/RWFMC

NOTE

- ▶ Insulated color may vary

Cat. No.	Description	K.O. Size	Std. Pkg.	Master Ctn.
FLC-50L	Steel AC 10/4 (0.605") - 6/3 (0.853") AL AC 10/3 (0.610") - 6/3 (0.823") Steel MCI: 10/3 (0.580") - 8/3 (0.690") AL MCI: 10/3 (0.520") - 8/3 (0.690") Steel HCF AC: 10/4 (0.605") - 6/3 (0.853") AL HCF AC: 10/3 (0.610") - 6/3 (0.823") AL MCI-A: 8/3 (0.675") HCF MCI-A: 8/3 (0.675") Steel/AL FMC/RWFMC: 1/2"	1/2"	50	500
FLC-75L	Steel AC 10/3 (0.545") - 6/3 (0.850") AL AC 10/3 (0.600") - 6/3 (0.835") Steel MCI: 10/3 (0.550") - 6/3 (0.850") AL MCI: 10/3 (0.580") - 6/3 (0.850") Steel HCF AC: 10/3 (0.545") - 6/3 (0.850") AL HCF AC: 10/3 (0.600") - 6/3 (0.835") AL MCI-A: 8/3 (0.675") - 6/3 (0.785") HCF MCI-A: 8/3 (0.675") - 6/3 (0.785") Steel/AL FMC/RWFMC: 1/2"	3/4"	25	250



STEEL "FASTLOCK" DUPLEX CONNECTOR

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Combo Head Set-Screw
- ▶ For AC, MCI, HCF AC, MCI-A, HCF MCI-A, FMC/RWFMC

NOTE

- ▶ Insulated color may vary

Cat. No.	Description	K.O. Size	Std. Pkg.	Master Ctn.
FLD-50	Steel AC 14/2 (0.475") - 10/3 (0.565") AL AC 14/2 (0.464") - 12/4 (0.600") Steel MCI: 14/2 (0.455") - 12/4 (0.545") AL MCI: 14/2 (0.455") - 12/4 (0.550") Steel HCF AC: 14/2 (0.475") - 10/3 (0.565") AL HCF AC: 14/2 (0.464") - 12/4 (0.600") AL MCI-A: 14/2 (0.385") - 10/3 (0.520") HCF MCI-A: 14/2 (0.385") - 10/3 (0.520") Steel/AL FMC/RWFMC: 3/8"	1/2"	25	250

