

## 4S Boxes


Steel Products

### 4" SQUARE (4S) SHALLOW BOX

**DRAWN**  
1-1/4" DEEP

- 18.0 Cu. In.  
• With Raised Ground Emboss & 10-32 Ground Screw

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D4SSB-50	10 - 1/2"	4 - 1/2"	50



### 4" SQUARE (4S) BOXES


**DRAWN**  
1-1/2" DEEP

- 21.0 Cu. In.  
• With Raised Ground Emboss & 10-32 Ground Screw


#### Boxes with Pigtail:

- Raised Ground Emboss and Pre-Assembled 3-Way, 10-32 Ground Screw and 7" Long Solid #12AWG Pigtail


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
D4SB-50	-	12 - 1/2"	4 - 1/2"	50
D4SB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-50/75-PT	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-75-PT	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	50
D4SB-50-FB	FB, Flush	9 - 1/2"	4 - 1/2"	24
D4SB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24




D4SB-50




D4SB-50/75



D4SB-50/75-PT




D4SB-75




D4SB-75-PT




D4SB-CKO



D4SB-50-FB



D4SB-50/75-FB




D4SB-CKO-FB

### 4" SQUARE (4S) DEEP BOXES


**DRAWN**  
2-1/8" DEEP

- 30.3 Cu. In.  
• With Raised Ground Emboss & 10-32 Ground Screw


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
D4SDB-50	-	12 - 1/2"	2 - 1/2", 2 - 3/4"	24
D4SDB-50-FB	FB, Flush	9 - 1/2"	2 - 1/2", 2 - 3/4"	24
D4SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-75-FB	FB, Flush	6 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24




D4SDB-50




D4SDB-50-FB




D4SDB-50/75




D4SDB-75



D4SDB-75-FB



D4SDB-CKO



D4SDB-CKO-FB

#### Certification:

- File E227970
- Acceptable for use in 2-hour Fire Rated Walls, Visit [www.ul.com](http://www.ul.com)