



LED FLOOD LIGHT



NEW

LFL6 Series

Available Wattages
ranging from
15W up to 300W

Orbit's LFL6 Series Flood Lights are ideal for exterior building lighting, sign lighting, loading docks, warehouses, and other outdoor applications. The slim design of these Ultra-Bright LED Flood Lights makes them a very attractive upgrade to traditional flood lighting.



LED FLOOD LIGHT



LFL6-50W-T



LFL6-30W-T



LFL6-15W-T



Built-In Heatsinks
Shown Installed



LFL6-50W-KN



LFL6-30W-KN



LFL6-15W-KN



The LFL6 Series is ideal for exterior building lighting, sign lighting, loading docks, warehouses, and other outdoor applications.

- 120~277V
- Die Cast Aluminum Housing
- UV Resistant Bronze Powder Coat Finish
- Polycarbonate Lens with Weatherproof Gasket
- Min Operating Temp: -20°C/-4°F
- 50,000 Life Hours
- 5 Year Limited Warranty
- UL Listed For Wet Location

Mounting Options

- T** Trunnion
- KN** Adjustable 1/2" Knuckle

Cat. No.	System Wattage	Efficacy	Color Temperature	Emission Color	Lumens	CRI	Wattage Equivalent
LFL6-15W-WW-KN	15W	101 lm/W	3000K	Warm White	1511	80+	50W MH
LFL6-15W-WW-T	15W	101 lm/W	3000K	Warm White	1511	80+	50W MH
LFL6-15W-CW-KN	15W	101 lm/W	5000K	Cool White	1511	80+	50W MH
LFL6-15W-CW-T	15W	101 lm/W	5000K	Cool White	1511	80+	50W MH
LFL6-30W-WW-KN	30W	99 lm/W	3000K	Warm White	2985	80+	100W MH
LFL6-30W-WW-T	30W	99 lm/W	3000K	Warm White	2985	80+	100W MH
LFL6-30W-CW-KN	30W	99 lm/W	5000K	Cool White	2985	80+	100W MH
LFL6-30W-CW-T	30W	99 lm/W	5000K	Cool White	2985	80+	100W MH
LFL6-50W-CW-KN	50W	101 lm/W	5000K	Cool White	5053	80+	175W MH
LFL6-50W-CW-T	50W	101 lm/W	5000K	Cool White	5053	80+	175W MH

LED FLOOD LIGHT



NEW LFL6-80W/100W/150W-SF



NEW LFL6-220W/300W-SF

**PHOTOCELL &
MOTION SENSOR
*READY***



NEW LFL6-80W/100W/150W-T



NEW LFL6-220W/300W-T



The LFL6 Series is ideal for exterior building lighting, parking areas, loading docks or warehouses.

- 120~277V
- Dimmable to 10%
- Die Cast Aluminum Housing
- UV Resistant Bronze Powder Coat Finish
- Polycarbonate Lens with Weatherproof Gasket

- Min Operating Temp: -20°C/-4°F
- 50,000 Life Hours
- 5 Year Limited Warranty
- UL Listed For Wet Location

Mounting Options

- T** Trunnion
- SF** Adjustable 2" Slip-Fitter

Cat. No.	System Wattage	Efficacy	Color Temperature	Emission Color	Lumens	CRI	Wattage Equivalent
LFL6-80W-T	80W	113 lm/W	5000K	Cool White	9064	80+	250W MH
LFL6-80W-SF	80W	113 lm/W	5000K	Cool White	9064	80+	250W MH
LFL6-100W-T	100W	110 lm/W	5000K	Cool White	11021	80+	250W MH
LFL6-100W-SF	100W	110 lm/W	5000K	Cool White	11021	80+	250W MH
LFL6-150W-T	150W	109 lm/W	5000K	Cool White	16423	80+	400W MH
LFL6-150W-SF	150W	109 lm/W	5000K	Cool White	16423	80+	400W MH
LFL6-220W-T	220W	117 lm/W	5000K	Cool White	25684	80+	750W PSMH
LFL6-220W-SF	220W	117 lm/W	5000K	Cool White	25684	80+	750W PSMH
LFL6-300W-T	300W	113 lm/W	5000K	Cool White	34017	80+	1000W MH
LFL6-300W-SF	300W	113 lm/W	5000K	Cool White	34017	80+	1000W MH