




As a leading manufacturer of electrical products, Orbit offers one of the largest selections of electrical boxes and rings in the industry. Our state-of-the-art manufacturing facilities and industry trained engineers ensure the production and development of quality electrical products. With the contractor as our main priority, all of our boxes are cleaned, deburred and offered with a variety of brackets and knockouts to suit various applications.



### BRACKET OPTIONS



Up to 7 different types

### FLUSH KNOCKOUTS



Variety of options

### CLEAN BOXES AND NO SHARP EDGES



Clean and deburred boxes

### EMBOSS AND PIGTAIL



Reduce waste and time  
10" length pigtail on select boxes

### CLAMPS



Accommodates metal and non-metallic cables


### PRE-INSTALLED RAISED SCREWS




Easy installation out of box

## Bracket Specification


BRACKET TYPE	AB	B (for S)	FB (for S)	FB (for FSB)	FB (for R)	FB (for H)	LB	MS	OB	WB
Length	5-7/8"	3"	7-3/8"	5-1/2"	7-1/4"	7"	2 - 3/8"	2-1/2"	6-3/4"	7-1/2"
Width	7/8"	2"	1-9/16"	2-1/8"	3/4"	1"	2 - 23/32"	1-3/8"	1-3/16"	1-9/16"
Offset	0" (Flush)	0" (Flush)	0" (Flush)	9/16"	1/2"	9/16"	1/4"	0" (Flush)	1-5/16"	0" (Flush)




**"AB" 90° BRACKET**  
Positions box against face and side of stud.




**"B" BRACKET for Square Box**  
Face mounts on front edge of wood stud.




**"FB" BRACKET for Square Box**  
Mounts on flat side of stud.




**"FB" BRACKET for FSB**  
Flush-Mounts on flat side of stud or joist.




**"FB" BRACKET for Round Box**  
Offset Mounts on flat side of stud or joist.




**"FB" BRACKET for Handy Box**  
Mounts on flat side of stud.




**"LB" BRACKET**  
With spurs, slotted holes for toe-nailing.



**"MS" BRACKET**  
Self-Gripping Metal Stud Bracket with Box Support Clip.  
**\*Model Revised Feb. 2008**




**"OB" BRACKET**  
Positions box away from side of stud for door frame trim clearance.




**"WB" BRACKET**  
With positioning spurs to mount box on side of stud.


## Clamp Specification




**"BX/MC" Clamp**  
Accommodates Metal Clad Cables from size #14-2 to #10-4  
**\*\*All MC series boxes are suitable for use with MCI-A Type**



**"NM" Clamp**  
Accommodates #14-2 to #10-3 Non-Metallic Cables with ground




**"NM" Clamp for Pancake Box**  
Accommodates #14-2 Non-Metallic Sheathed Cables with ground



**"NM" Clamp for Beveled Switch Box**  
Accommodates #14-2 to #10-3 Non-Metallic Sheathed Cables with ground. 45° & 90° Screw Mounting.

## Knockout & Pryout Specification





## Octagonal Concrete Ceiling Fan Box | Pg. A30



4CB-F




Orbit's line of Concrete Boxes and Covers continues to grow with the addition of a Fan-Rated Concrete Box, 4CB-F, 4" deep fan-rated concrete box approved to support fixtures up to 90 lbs. and fans up to 70 lbs.

## 4" Box with Angled MC Cable Clamps | Pg. A10, P25, F22



4SDB-AMC-PT



15° angle



Unique ground screw location allows fastening of box to any Adj. Box Bracket

CUT-AWAY SIDE VIEW

The 4SDB-AMC-PT features cable clamp screws set at a 15° angle. Installers can now secure MC cable with the mud ring attached. This box can mount onto Adjustable Bar Hangers, thanks to its unique grounding screw location. Compatible with Orbit's UMA-LVBS, BARB, and SSB Families. An ideal MC box for prefabrication. Also available Ready-To-Install with mounting adapter and cable support.

## Easy Access Lighting Box w/ Sliding Swivel | Pg. P22, I46, J21


Only box UL-Listed for up to 90 lbs. of fixture load!

**50% LABOR SAVINGS**

**PATENTED**



**EALBS**



**TRADITIONAL METHOD**

Requires two installers




**WITH ORBIT'S EALBS**

One installer completes wiring while fixture hangs

Orbit's Easy Access Lighting Box with Sliding Swivel Cover can double productivity when hanging light fixtures. Two installers are needed when mounting traditional swivel covers: one person to hold, and another to complete the wiring. But with EALBS, just ONE installer does it all...and with both hands free for wiring! This 2014 NECA Showstopper features detachable sides and a 20° angle sliding swivel cover that fits 3/4" to 1/2" conduit (with supplied bushing). UL Rated up to 90lbs.

## Easy Hang Boxes | Pg. A9, A16, P21 - 22



**4SDB-BP**




**4SDB-MKO-S** NEW



**D5SDB-CKO-S**



Mount to ceilings, walls, corrugated surfaces, or underneath counters




Secure to ceiling with just a rod and locknut  
**4SDB-MKO-S 3/8" ROD**  
**D5SDB-CKO-S 1/4" ROD**

Easy Hang Boxes have been developed through feedback from the field and installers looking to save time or simplify unique installations. The 4SDB-BP can be wired ahead of shipment to jobsite and installed without having to access the inside of the junction box. D5SDB-CKO-S have the back-center K.O. replaced with through hole eliminating need for washer or punching back-center K.O. when mounting boxes in suspended application.



## Universal Mounting Adjustable Boxes | Pg. A4, A11, A24, P1, P5 - 8, F21 - 23



Adjustable 1/2" to 1-1/2"

TRI-COMBO HEX SCREW




FA-UMIAB-35 **NEW**



UMIAB-35 **NEW**

**INTERNAL ADJUSTMENT**



Adjustable 0" to 1-1/2"



FA-UMAB



UMAB



FA-UMAB-4R



UMAB-4R

**EXTERNAL ADJUSTMENT**

**DIRECT-TO, BETWEEN STUDS & OVERHEAD APPLICATIONS**



**DIRECT TO STUD**



**BETWEEN STUDS**



**DROP CEILING (T-BAR)**

6-way Adjustability

6-way Adjustability

UMAB's & UMIAB-35's can be mounted directly to studs or snapped onto SSB-T5 for between stud or overhead/hard lid applications and SSB-TBAR for drop ceiling applications

## The Largest Selection of Gangable Switch Boxes With Pre-Installed Pigtail | Pg. A35 - 36




With the largest selection of switch boxes with pre-installed pigtails in the market, installing switch boxes has never been easier! Installers will no longer need to reach inside the narrow switch boxes to mount grounding pigtails again!

## EXTRA Wide Switch Boxes | Pg. A34 - 35, P29




TGW



TGMW



WMB-PT



TGW SHOWN WITH GFCI INSTALLED

More Space For An Easier Fit!

Up to 1/4" Wider and/or Deeper than traditional 2" x 3" cut-in boxes to simplify the installation of oversized USB or GFCI devices. All models 2-1/4" wide. WMB-PT and TGMW are 2-3/4" deep; TGW is 2-1/2" deep. WMB-PT features 1/2" to 3/4" MKOs and 7" grounding pigtail.



## Adjustable Depth Plaster Rings | Pg. A14 - 15, A20 - 21, A27, P23 - 24

*Ensure a flush finish every time with the industry's largest offering of Adjustable Plaster Rings.*

**IDEAL FOR WALL DEPTHS UP TO 1-1/2"**



**1-Gang, 4" or 4-11/16" sq.**  
Adj. range: 5/8" - 1-1/2"



**2-Gang, 4" or 4-11/16" sq.**  
Adj. range: 5/8" - 1-1/2"



**30, 4" sq.**  
Adj. range: 3/4" - 1-1/2"



**3-Gang**  
Adj. range: 3/4" - 1-1/2"

The 4AR, 5AR, 4ARR & 3GAR Series of UL-Listed adjustable rings are ideal for use in applications where wall depths are up to 1-1/2".

**IDEAL FOR INFINITE WALL DEPTHS**



**1-Gang, 4" or 4-11/16" sq.**  
Adj. range: 5/8"+  
with use of 1GX75



**2-Gang, 4" or 4-11/16" sq.**  
Adj. range: 5/8"+  
with use of 2GX75



**1GX75**  
1-Gang,  
3/4" Extension



**2GX75**  
2-Gang,  
3/4" Extension



**Exploded View of 5SAR2G & 2GX75 Installed**

The SAR & WBAR Series of adjustable rings are perfect for applications where wall depths are 1-1/2" or greater. These rings are compatible with the 1GX75 or 2GX75, allowing installer to achieve infinite depths effortlessly.



## Dual Direction Fixture Rings | Pg. A5, A12, A19



CONCRETE



40 to 30



4" Sq. to 30



ONE-DIRECTION  
Industry Standard



4-11/16" Sq. to 30



4" & 4-11/16" Sq. to 40




DUAL-DIRECTION  
Orbit's New Standard

All Orbit Fixture Rings with Round Openings are now Dual-Direction Mounting. With four mounting tabs (vs. the two-tab standard), installers can now mount 30 and 40-compatible fixtures in any orientation. Installers can also mount rings on boxes with less planning – and less potential re-work!

## Universal 4" & 4-11/16" Sq. to 40 Fixture Rings | Pg. A19, P25

NEW



540X Series

#8-32 Threads



4" BOX



4-11/16" BOX

Universal Square-to-Octagon Fixture Rings transition any 4" or 4-11/16" square box into a 4" octagon (3-1/2" O.C.) opening. 540X Series features four (4) dual-direction mounting tabs, so 40 compatible fixtures can be installed in any orientation, saving installation time.



## 4" Square Ring Adapter for 3-Gang Box | Pg. A27



4M3-4S



4M3-4S Shown Installed on BHA-16, SB-3 & 4AR1G-58

4" Square Ring Adapter for 3-Gang Junction Box transitions a multigang box into a 4" square opening. Ideal in markets where 2-1/2" stud depths are common. Increase box fill volume by 55% (65 Cu. In.) versus deep 4-11/16" Sq., 2-1/8" deep junction boxes (42 Cu. In.). Increased volume allows for more conductors and fittings within tight wall spaces.

## Universal Cut-In Box Adapter | Pg. A24, A33, P30



UCIA-4S



FA-UCIA-4S



FIRE ALARM

Small footprint easily concealed by life safety devices



PREFABRICATION

Prepare 4" boxes with UCIA-4S in the shop

Enable any 4" square junction box to be used in old work applications. Installers can quickly mount 4" sq. boxes of any depth into existing walls. Includes two (2) old work clips that firmly secure boxes to finished drywall or plaster, without risk of pull-out. Small footprint is easily covered by large appliances and devices. FA-UCIA-4S is powder coated red for quick identification of FA devices.

**PROFAB**  
ENGINEERED ELECTRICAL SYSTEMS

# LOOKING TO INSTALL RIGHT OUT OF THE BOX?

Contact our PROFAB Service Division to discuss solutions for your next big job!

Request a PROFAB consultation today!

1.833.3.PROFAB (776322) | info@orbitprofab.com | www.orbitprofab.com

## 4" CEILING FAN & LIGHT FIXTURE SUPPORT PRODUCTS

WITH NON-METALLIC (NM) SHEATHED CABLE CONNECTOR

### PRODUCT FEATURES

- ▶ NM Clamp installed in 1-1/2" & 2-1/8" Boxes
- ▶ Easy-to-follow Instruction Sheet
- ▶ Complies with NEC 314.27 (A)(C)(D) for up to 70 lbs. of ceiling fan load or 70 lbs. of fixture load (for more information see pg. W18)

### NOTE

- ▶ Hardware Pack include variety of fasteners for all installation types
- ▶ Replaceable MC Clamp supplied in Hardware Pack


### BAR HANGER FEATURES

- ▶ **NBH:** New Construction Bar Hanger slides apart to fit joist spacing from 16" to 24"
- ▶ **OBH:** Old Work Bar Hanger for joist spacing from 16" to 24", No tools necessary for expansion of the bar

### BX/MC CLAMP FEATURES


- ▶ All MC series boxes are suitable for use with MCI-A Type

Cat. No.	Depth	Clamp Type	Bracket, Setback or Expansion	Knockouts	Cu. In.	Std. Pkg.
FSB	1-1/2"	BX/MC, NM	-	3 - 1/2", 2 - Loom	15.5	20
FSDB	2-1/8"	BX/MC, NM	-	3 - 1/2", 2 - Loom	21.5	20
FSDB-FB	2-1/8"	BX/MC, NM	FB, 1/2"	2 - 1/2", 2 - Loom	21.5	20
FSB-NBH	1-1/2"	BX/MC, NM	NBH, 16" to 24"	3 - 1/2", 2 - Loom	15.5	10
FSDB-NBH	2-1/8"	BX/MC, NM	NBH, 16" to 24"	3 - 1/2", 2 - Loom	21.5	10
FSB-OBH	1-1/2"	BX/MC, NM	OBH, 16" to 24"	3 - 1/2", 2 - Loom	15.5	10
FSDB-OBH	2-1/8"	BX/MC, NM	OBH, 16" to 24"	3 - 1/2", 2 - Loom	21.5	10
FS4PB	1/2"	-	-	2 - 1/2"	6.0	20
FS4PB-NBH	1/2"	-	NBH, 16" to 24"	2 - 1/2"	6.0	10



## FAN SUPPORT BAR HANGERS

Cat. No.	Description	Std. Pkg.
FS-NBH	16" to 24" Adjustable New Construction Bar Hanger for use with Fan Support Boxes	10
FS-OBH	16" to 24" Adjustable Old Work Bar Hanger for use with Fan Support Boxes	10



# A2 | Pancakes, 30 Boxes & Covers




Boxes & Covers

## 3-3/8" & 4" ROUND PANCAKE BOXES

### NOTE

- ▶ Not for use as Ceiling Fan Support Boxes (See pg. A1)
- ▶ For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Depth	Clamp Type	Knockouts	Box Diameter	Cu. In.	Std. Pkg.
3PB-NM	1/2"	NM	1 - 1/2", 4 - Circ. Pryouts	3 - 3/8"	3.9	50
3PDB-NM	3/4"	NM	1 - 1/2", 4 - Circ. Pryouts	3 - 3/8"	5.0	50
4PB	1/2"	-	5 - 1/2"	4"	6.0	50
4PB-NM	1/2"	NM	3 - 1/2", 4 - Circ. Pryouts	4"	6.0	50



## 3-1/2" OCTAGON (30) BOXES & EXTENSION RING


**DRAWN**  
1-1/2" DEEP

9.0 Cu. In.

### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
3RB-50	-	4 - 1/2"	1 - 1/2"	50
3RB-50-FB	FB, 1/2"	3 - 1/2"	1 - 1/2"	50
3RB-50-EXT	-	4 - 1/2"	-	50



## 3-1/2" OCTAGON (30) BOXES

**DRAWN**  
1-1/2" DEEP


9.0 Cu. In.

WITH NON-METALLIC (NM)  
SHEATHED CABLE CLAMPS

### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 3RB-NM-E)

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
3RB-NM	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
3RB-NM-E	Ears	2 - 1/2", 4 - Loom	1 - 1/2"	50
3RB-NM-FB	FB, 1/2"	1 - 1/2", 4 - Loom	1 - 1/2"	50



## 3-1/2" ROUND COVERS

Cat. No.	Description	Std. Pkg.
3RBC	Flat, Blank	50
3RBCK	Flat, 1/2" KO	50



## 4" OCTAGON (40) BOXES

**DRAWN**  
1-1/2" DEEP

15.5 Cu. In.

**NOTE**

- ▶ For Fixture/Luminaire Support of 50 lbs or less

## 4" OCTAGON (40) BOXES & EXTENSION RINGS

**WELDED**  
1-1/2" DEEP

15.5 Cu. In.


**BAR HANGER FEATURES**

- ▶ **BHA:** Adjustable Bar Hanger allows installation of box anywhere along length of stud
- ▶ 4RB-50-BHA includes 3/8" - 18 NPS trade sized stud to accommodate fixture stem


**NOTE**

- ▶ For Fixture/Luminaire Support of 50 lbs or less
- ▶ \*For Fixture/Luminaire Support of 50 lbs or less at 16 in. Span


Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D4RB-50	4 - 1/2"	5 - 1/2"	50
D4RB-50/75	2 - 1/2", 2 - 3/4"	3 - 1/2", 2 - 3/4"	50
D4RB-75	4 - 3/4"	3 - 1/2", 2 - 3/4"	50



D4RB-50




D4RB-50/75




D4RB-75


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RB-50	-	4 - 1/2"	5 - 1/2"	50
4RB-MKO	-	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	50
4RB-50-FB	FB, 1/2"	3 - 1/2"	5 - 1/2"	50
4RB-MKO-FB	FB, 1/2"	1 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	50
4RB-50-LB	LB, Flush	4 - 1/2"	5 - 1/2"	50
*4RB-50-BHA	BHA-1, Adj. 16" to 24"	4 - 1/2"	4 - 1/2"	25
4RB-50-EXT	-	4 - 1/2"	-	50
4RB-MKO-EXT	-	2 - 1/2", 2 - MKO	-	50




4RB-50




4RB-MKO




4RB-50-FB




4RB-MKO-FB




4RB-50-LB



\*4RB-50-BHA



4RB-50-EXT



4RB-MKO-EXT

## 4" OCTAGON (40) BOXES

**WELDED**  
1-1/2" DEEP


15.5 Cu. In.

**WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS**


**NOTE**

- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4RB-NM-E and 4RB-NM-SG)
- ▶ \*For Fixture/Luminaire Support of 50 lbs or less at 16 in. Span


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RB-NM	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-E	Ears	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-FB	FB, 1/2"	1 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-LB	LB, Flush	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-NM-SG	Swing Bracket - Old Work	4 - Loom	1 - 1/2"	50
*4RB-NM-BHA	BHA-1, Adj. 16" to 24"	2 - 1/2", 4 - Loom	-	25




4RB-NM




4RB-NM-E




4RB-NM-FB



4RB-NM-LB



4RB-NM-SG



\*4RB-NM-BHA

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information



## 4" OCTAGON (40) BOXES

**WELDED**

**1-1/2" DEEP**

15.5 Cu. In.


WITH METAL CLAD (BX/MC)

CABLE CLAMPS

**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less (Except 4RB-MC-E)
- \*For Fixture/Luminaire Support of 50 lbs or less at 16 in. Span

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RB-MC	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-MC-E	Ears	2 - 1/2", 4 - Loom	1 - 1/2"	50
4RB-MC-FB	FB, 1/2"	1 - 1/2", 4 - Loom	1 - 1/2"	50
*4RB-MC-BHAC <b>NEW</b>	BHA-1C, Adj. 16" to 24"	2 - 1/2", 4 - Loom	-	25



## 4" OCTAGON (40) DEEP BOXES

**WELDED**


**2-1/8" DEEP**

21.5 Cu. In.

**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less (except UMAB-4R's)
- UMAB-4R's mount direct-to-stud or used with the SSB-T5 or SSB-TBAR for between stud or ceiling installation (see pg. P1 for more info.)
- UMAB-4R's depth adjusted via screws on the outside of the box

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RDB-MKO	-	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	50
4RDB-MKO-FB	FB, 1/2"	1 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	25
UMAB-4R	Adjustable from 0" to 1-1/2"	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	20
FA-UMAB-4R	Adjustable from 0" to 1-1/2"	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	20



## 4" OCTAGON (40) DEEP BOXES

**WELDED**

**2-1/8" DEEP**


21.5 Cu. In.

WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS

**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RDB-NM	-	2 - MKO, 4 - Loom	1 - 1/2"	50
4RDB-NM-FB	FB, 1/2"	1 - MKO, 4 - Loom	1 - 1/2"	25
4RDB-NM-LB	LB, 1/2"	2 - MKO, 4 - Loom	1 - 1/2"	25



## 4" OCTAGON (40) DEEP BOXES

**WELDED**

**2-1/8" DEEP**


21.5 Cu. In.

WITH METAL CLAD (BX/MC) CABLE CLAMPS

**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less
- 600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4RDB-MC	-	2 - MKO, 4 - Loom	1 - 1/2"	50
4RDB-MC-FB	FB, 1/2"	1 - MKO, 4 - Loom	1 - 1/2"	25
*4RDB-MC-LB	LB, 1/2"	2 - MKO, 4 - Loom	1 - 1/2"	25



## 4" ROUND COVERS FLAT OR DRAWN

### PRODUCT FEATURES


- ▶ For X covers, four dual-direction mounting tabs -install devices in any orientation

### NOTE

- ▶ \*Available in Durable Red Powder Coat Finish, see page A24



4R000S features holes for multi-directional mounting, resulting in a faster installation



Cat. No.	Description	Cu. Inch	Std. Pkg.
<i>For use with 4O boxes (page A3~4)</i>			
*4RBC	Flat, Blank (Octagonal)	-	50
4RBC-R	Flat, Blank (Round)	-	50
4RBCK	Flat, 1/2" KO (Octagonal)	-	50
4RBC-MKO	Flat, MKO (Octagonal)	-	50
4RC-TS	Flat, Toggle Switch (Octagonal)	-	50
4RC-DR	Flat, Duplex Receptacle (Octagonal)	-	50
4RC-SR	Flat, 1.4" Dia. Single Receptacle (Octagonal)	-	50
*4RC-PO	Flat, 1.6" Dia. Power Outlet (Octagonal)	-	50

*For use with 4" concrete boxes (page A30)*

4R000S	Flat, Open, Dual Dir. Ears 2-3/4" O.C. Universal Mounting	-	25
--------	---	---	----

*For use with both 4O boxes (page A3~4) and 4" concrete boxes (page A30)*


4R000X <b>NEW</b>	Flat, Open, Dual Dir. Ears 2-3/4" O.C.	-	50
4R050X <b>NEW</b>	Raised 1/2", Open, Dual Dir. Ears 2-3/4" O.C.	3.0	50
4R058X <b>NEW</b>	Raised 5/8", Open, Dual Dir. Ears 2-3/4" O.C.	4.0	50
4R075X <b>NEW</b>	Raised 3/4", Open, Dual Dir. Ears 2-3/4" O.C.	5.0	50
4R100X <b>NEW</b>	Raised 1", Open, Dual Dir. Ears 2-3/4" O.C.	6.8	25
4R125X <b>NEW</b>	Raised 1-1/4", Open, Dual Dir. Ears 2-3/4" O.C.	8.5	25
4R150X <b>NEW</b>	Raised 1-1/2", Open, Dual Dir. Ears 2-3/4" O.C.	9.7	25
4R200X <b>NEW</b>	Raised 2", Open, Dual Dir. Ears 2-3/4" O.C.	12.9	25
4R1000	Flat, 1-Gang Device Ring	-	50
4R1058	Raised 5/8", 1-Gang Device Ring	3.5	50

## 4" SWIVEL-TYPE COVER PLATES

### PRODUCT FEATURES

- ▶ 20° Swivel Angle
- ▶ Complies with NEC 314.27 (A)(D) for up to 90 lbs. of fixture load (for more information see Section W)

Cat. No.	Description	Swivel Thread Size	Std. Pkg.
SCR-75	4" Round Swivel-Type Cover	3/4", 1/2" Reducing Bushing Included	25
SCS-75	4" Square Swivel-Type Cover	3/4", 1/2" Reducing Bushing Included	25




**Install Swivel Covers Faster & Safer with Orbit's Easy Access Lighting Box (EALBS) on pg. P22**

## 5" ROUND CLOSURE PLATES WITH UNIVERSAL-MOUNT STRAP

### PRODUCT FEATURES

- ▶ For covering up to 4" Round and Octagonal Boxes

Cat. No.	Description	Color	Std. Pkg.
CP-5	Hard Aluminum 5" dia. Blank Cover Plate	White	50
CP-5NM	Non-metallic 5-3/8" dia. Blank Cover Plate	White	50



# A6 | 4S Boxes

## 4" SQUARE (4S) SHALLOW BOX

**DRAWN**

1-1/4" DEEP


18.0 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW

**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D4SSB-50	10 - 1/2"	4 - 1/2"	50



D4SSB-50

## 4" SQUARE (4S) BOXES

**DRAWN**

1-1/2" DEEP

21.0 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW


**BOXES WITH PIGTAIL FEATURES**

- 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw


**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
D4SB-50	-	12 - 1/2"	4 - 1/2"	50
D4SB-50-PT	-	12 - 1/2"	4 - 1/2"	50
D4SB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	50
D4SB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	50
*D4SB-50-FB	FB, Flush	9 - 1/2"	4 - 1/2"	24
*D4SB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24




D4SB-50



D4SB-50-PT




D4SB-50/75




D4SB-75




D4SB-CKO



\*D4SB-50-FB



\*D4SB-50/75-FB



D4SB-CKO-FB

## 4" SQUARE (4S) DEEP BOXES

**DRAWN**

2-1/8" DEEP


30.3 Cu. In.

WITH RAISED GROUND EMBOSS & 10-32 GROUND SCREW


**NOTE**

- For Fixture/Luminaire Support of 50 lbs or less


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
D4SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-75	-	8 - 3/4"	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO	-	8 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	24
D4SDB-CKO-FB	FB, Flush	6 - 1/2", 3 - CKO	2 - 1/2", 2 - 3/4"	24




D4SDB-50/75



D4SDB-75



D4SDB-CKO



D4SDB-CKO-FB

- 600V MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- Acceptable for use in 2-hour rated walls
- Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4" SQUARE (4S) BOXES & EXTENSION RINGS

### WELDED

### 1-1/2" DEEP

21.0 Cu. In.

WITH RAISED GROUND EMBOSS (EXCEPT FOR BRACKETED AND EXTENSION BOXES)

#### METAL STUD BRACKET FEATURES

- ▶ U.S. Patent No.: 8,262,043
- ▶ Metal Stud (MS) Bracket engages on either side of metal stud
- \*\*\*Model Revised Feb. 2008


#### BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw

#### NOTE

- ▶ \*Available in Durable Red Powder Coat Finish (pg. A24)
- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SB-MKO-MS and 4SB-MKO-OB)
- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SB-50	-	12 - 1/2"	4 - 1/2"	50
4SB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
4SB-50/75-PT	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	50
4SB-75	-	8 - 3/4"	2 - 1/2", 2 - MKO	50
*4SB-MKO	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	50
4SB-MKO-PT	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	50
4SB-50-FB	FB, Flush	9 - 1/2"	5 - 1/2"	24
4SB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	3 - 1/2", 2 - 3/4"	24
4SB-75-FB	FB, Flush	6 - 3/4"	1 - 1/2", 4 - 3/4"	24
4SB-MKO-FB	FB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-MKO-MS**	MS, Self-Gripping + Box Support Clip	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-MKO-OB	OB, 1-5/16"	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-MKO-B	B, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-MKO-AB	AB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-MKO-WB	WB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SB-50-EXT	-	12 - 1/2"	-	50
4SB-50/75-EXT	-	8 - 1/2", 4 - 3/4"	-	50
*4SB-MKO-EXT	-	8 - 1/2", 4 - MKO	-	50
4SB-MKO-EHB	Extension Ring to Handy Box	8 - 1/2", 4 - MKO	-	50



\*While Supplies Last

## 4" SQUARE (4S) BOXES

**WELDED**

**1-1/2" DEEP**

21.0 Cu. In.

**WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS**


### METAL STUD BRACKET FEATURES

- ▶ U.S. Patent No.: 8,262,043  
Metal Stud (MS) Bracket engages on either side of metal stud
- \*\*Model Revised Feb. 2008

### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SB-NM-MS)

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SB-NM	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	50
4SB-NM-FB	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
*4SB-NM-MS**	MS, Self-Gripping + Box Support Clip	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SB-NM-WB	WB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24



## 4" SQUARE (4S) BOXES

**WELDED**

**1-1/2" DEEP**

21.0 Cu. In.

**WITH METAL CLAD (BX/MC) CABLE CLAMPS**

### BX/MC CLAMP FEATURES

- ▶ All MC series boxes are suitable for use with MCI-A Type


### BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw

### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SB-MC-MS)

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SB-MC	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	50
4SB-MC-PT	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	50
4SB-MC-FB	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SB-MC-FB-PT	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SB-MC-B	B, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SB-MC-WB	WB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SB-MC-MS**	MS + Box Support Clip	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24



- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4" SQUARE (4S) DEEP BOXES

**WELDED**

**2-1/8" DEEP**

30.3 Cu. In.

**WITH RAISED GROUND EMBOSS  
(EXCEPT FOR BRACKETED BOXES)**

### METAL STUD BRACKET FEATURES


- ▶ U.S. Patent No.: 8,262,043 Metal Stud (MS) Bracket engages on either side of metal stud
- \*\*\*Model Revised Feb. 2008

### BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail pre-assembled with Ground Emboss and 10-32 Ground Screw
- ▶ 10" Pigtail for BSA Series, PT-10 and 4SDB-BP

### BSA FEATURES

- ▶ Back Support Arm installed on this box provides support for studs up to 6" deep
- ▶ An excellent choice for pre-fab applications



### 4SDB-MKO-S FEATURES

- ▶ Back-center K.O. replaced with through hole eliminating need for washer or punching back-center K.O. when mounting boxes in suspended application.

### NOTE


- ▶ \*Available in Durable Red Powder Coat Finish (pg. A24)
- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SDB-MKO-MS)

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information



See pg. P7-8 for full line of Ready-To-Install assembled product

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SDB-50	-	12 - 1/2"	4 - 1/2"	24
4SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
*4SDB-75	-	8 - 3/4"	2 - 1/2", 2 - MKO	24
4SDB-75/100	-	4 - 3/4", 4 - 1"	2 - 1/2", 2 - 3/4"	24
4SDB-100	-	8 - 1"	2 - 1/2", 2 - 3/4"	24
*4SDB-MKO	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-MKO-PT	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-MKO-PT-10	-	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
4SDB-50-FB	FB, Flush	9 - 1/2"	5 - 1/2"	24
4SDB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	3 - 1/2", 2 - 3/4"	24
4SDB-75-FB	FB, Flush	6 - 3/4"	1 - 1/2", 4 - 3/4"	24
4SDB-100-FB	FB, Flush	6 - 1"	3 - 1/2", 2 - 3/4"	24
*4SDB-MKO-FB	FB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-MS**	MS, Self-Gripping + Box Support Clip	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-WB	WB, Flush	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
4SDB-MKO-PT-BSA	Back Support Arm	8 - 1/2", 4 - MKO	1 - 1/2", 2 - MKO	24
4SDB-BP	Back Mounting Plate, see pg. P21 for more info.	8 - 1/2", 4 - MKO	-	24
4SDB-MKO-S <b>NEW</b>	-	8 - 1/2", 4 - MKO	1 - 1/2", 2 - MKO	24
4SDB-MKO-EXT	-	8 - 1/2", 4 - MKO	-	24



# A10 | 4S Deep Boxes



## 4" SQUARE (4S) DEEP BOXES

### WELDED

### 2-1/8" DEEP

30.3 Cu. In.

### WITH METAL CLAD (BX/MC) CABLE CLAMPS

#### BX/MC CLAMP FEATURES

- ▶ All MC series boxes are suitable for use with MCI-A Type

#### METAL STUD BRACKET FEATURES

- ▶ U.S. Patent No.: 8,262,043 Metal Stud (MS) Bracket engages on either side of metal stud

**\*\*Model Revised Feb. 2008**


#### BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail pre-assembled with Ground Emboss and 10-32 Ground Screw
- ▶ 10" Pigtail for 4SDB-AMC-PT


#### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less (Except 4SDB-MC-MS)


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SDB-MC	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-AMC-PT	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-MC-FB	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-MC-FB-PT	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-MC-B	B, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-MC-MS**	MS, Self-Gripping	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24




4SDB-MC




4SDB-AMC-PT




4SDB-MC-FB




4SDB-MC-FB-PT



4SDB-MC-B



4SDB-MC-MS\*\*




#### TRADITIONAL

Ground Screw Interference - does not mount directly to Box Brackets

#### 4SDB-AMC-PT

Unique ground screw location allows fastening of box to any Adj. Box Bracket



#### Cut-away side view



#### 4SDB-AMC-PT

MC Clamp screws set at a 15° angle, allowing MC cable to be secured with the mud ring still on!

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4" SQUARE (4S) DEEP BOXES

**WELDED**  
2-1/8" DEEP


30.3 Cu. In.

**WITH NON-METALLIC (NM) SHEATHED CABLE CLAMPS**


### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SDB-NM	-	4 - 1/2", 2 - MKO, 4 - Loom	1 - 1/2"	24
*4SDB-NM-B	B, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
4SDB-NM-FB	FB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24
*4SDB-NM-WB	WB, Flush	2 - 1/2", 1 - MKO, 4 - Loom	1 - 1/2"	24




4SDB-NM



\*4SDB-NM-B



4SDB-NM-FB



\*4SDB-NM-WB

## 4" SQUARE (4S) EXTRA DEEP BOXES

**WELDED**  
3-1/2" DEEP

46.0 Cu. In.


### PRODUCT FEATURES

- ▶ Durable Red Powder Coat Finish for FA Series
- ▶ UMAB & UMIAB's mount direct-to-stud or used with the SSB-T5 or SSB-TBAR for between stud or ceiling installation (see pg. P1 for more info.)
- ▶ UMAB's depth adjusted via screws outside of the box
- ▶ UMIAB's depth adjusted via screws inside the box


### NOTE

- ▶ For Fixture/Luminaire Support of 50 lbs or less (except UMAB's & UMIAB's)


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
4SEDB-CKO	-	12 - CKO	4 - CKO	24
FA-4SEDB-CKO	-	12 - CKO	4 - CKO	24
*4SEDB-CKO-FB	FB, 1/2" thru 1-1/4"	10 - CKO	4 - CKO	10
*FA-4SEDB-CKO-FB	FB, 1/2" thru 1-1/4"	10 - CKO	4 - CKO	10
UMAB	Stud-mount, adjustable 0" to 1-1/2"	12 - CKO	4 - CKO	10
FA-UMAB	Stud-mount, adjustable 0" to 1-1/2"	12 - CKO	4 - CKO	10
UMIAB-35 <b>NEW</b>	Stud-mount, adjustable 1/2" to 1-1/2"	12 - CKO	4 - CKO	10
FA-UMIAB-35 <b>NEW</b>	Stud-mount, adjustable 1/2" to 1-1/2"	12 - CKO	4 - CKO	10



4SEDB-CKO



\*4SEDB-CKO-FB



UMAB



UMIAB-35



FA-4SEDB-CKO



\*FA-4SEDB-CKO-FB



FA-UMAB



FA-UMIAB-35

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information




\*While Supplies Last

# A12 | 4S Covers & Rings

## 4" SQUARE (4S) 1-GANG & 2-GANG DEVICE RINGS FLAT, DRAWN & TILE (T)

Drawn Cat. No.	Tile Cat. No.	Description	Gangs	Cu. In.	Std. Pkg.
41000	-	Flat	1	-	50
41025	-	Raised 1/4"	1	1.8	50
41050	41050T	Raised 1/2"	1	3.8	50
41058	-	Raised 5/8"	1	4.3	50
41075	41075T	Raised 3/4"	1	5.5	50
41100	41100T	Raised 1"	1	7.5	25
41125	41125T	Raised 1-1/4"	1	9.4	25
41150	41150T	Raised 1-1/2"	1	11.2	25
41200	41200T	Raised 2"	1	14.4	25
42000	-	Flat	2	-	50
42025	-	Raised 1/4"	2	3.0	50
42050	42050T	Raised 1/2"	2	5.8	50
42058	-	Raised 5/8"	2	7.5	50
42075	42075T	Raised 3/4"	2	8.8	50
42100	42100T	Raised 1"	2	11.8	25
42125	42125T	Raised 1-1/4"	2	14.5	25
42150	42150T	Raised 1-1/2"	2	15.5	25
42200	42200T	Raised 2"	2	20.7	25



## 4" SQUARE (4S) COVERS FLAT OR DRAWN






### PRODUCT FEATURES

- ▶ For X covers, four dual-direction mounting tabs -install devices in any orientation

### NOTE

- ▶ \*Available in Durable Red Powder Coat Finish (pg. A24)

Cat. No.	Description	Cu. In.	Std. Pkg.
*4BC	Flat, Blank	-	50
4BCK	Flat, 1/2" KO	-	50
4BC-MKO	Flat, MKO	-	50
43000X <b>NEW</b>	Flat, Open, Dual Dir. Ears 2-3/4" O.C.	-	50
43050X <b>NEW</b>	Raised 1/2", Open, Dual Dir. Ears 2-3/4" O.C.	3.0	50
43058X <b>NEW</b>	Raised 5/8", Open, Dual Dir. Ears 2-3/4" O.C.	4.0	50
43075X <b>NEW</b>	Raised 3/4", Open, Dual Dir. Ears 2-3/4" O.C.	5.0	50
43100X <b>NEW</b>	Raised 1", Open, Dual Dir. Ears 2-3/4" O.C.	6.8	25
43125X <b>NEW</b>	Raised 1-1/4", Open, Dual Dir. Ears 2-3/4" O.C.	8.5	25
43150X <b>NEW</b>	Raised 1-1/2", Open, Dual Dir. Ears 2-3/4" O.C.	9.7	25
43200X <b>NEW</b>	Raised 2", Open, Dual Dir. Ears 2-3/4" O.C.	12.9	25



**DUAL-DIRECTION  
FIXTURE RINGS**  
Orbit's New Standard




**4" SQUARE (4S)  
INDUSTRIAL COVERS  
RAISED 1/2"**


7.0 Cu. In.

**WITH CRUSHED CORNERS  
(Except for 4414, 4424, 4444)**


Cat. No.	Description	Std. Pkg.
4400	Blank	50
4401	Toggle Switch	50
4402	Duplex Receptacle	50
4403	Single Receptacle, 15A, 1.406" diameter	50
4404	GFCI or Decorative Switch	50
4405	Power Outlet, 20A, 1.60" diameter	50
4406	Power Outlet, 30A Locking, 1.750" diameter	50
4407	Power Outlet, 40 to 50A, 2.155" diameter	50
4408	Power Outlet, 30 to 60A, 2.625" diameter	50
*4409	Power Outlet, 40 to 50A, 2.155" diameter, off-centered	50
4411	2 Toggle Switches	50
4412	Toggle Switch / Duplex	50
4413	Toggle Switch / Single Receptacle, 1.406" diameter	50
4414C	Toggle Switch / GFCI	50
4414	Toggle Switch / GFCI	50
4422	2 Duplex Receptacles	50
4423	Duplex / Single Receptacle, 1.406" diameter	50
4424C	Duplex / GFCI	50
4424	Duplex / GFCI	50
4433	2 Single Receptacles, 1.406" diameter each	50
4444C	2 GFCIs or 2 Decorative Switches	50
4444	2 GFCIs or 2 Decorative Switches	50




4400




4401




4402




4403




4404




4405




4406




4407




4408




\*4409




4411




4412




4413




4414C




4414




4422




4423




4424C




4424



4433



4444C



4444



\*While Supplies Last

# A14 | 4S Adjustable Rings



Boxes & Covers

## 4" SQUARE (4S) ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ Can be adjusted on the jobsite for a quick installation
- ▶ For use with 4" square 2-1/8" or deeper boxes
- ▶ 1/4" to 1-1/4" adjustability range, deeper with addition of extensions
- ▶ Rings achieve a flush finish every time
- ▶ Compatible with exclusive extensions for infinite wall depths

### U.S. PATENT NO.:

7,468,486



**Video Available On Our Website!**

## STUD MOUNTING ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ Accepts 4" or 4-11/16" square boxes in line voltage applications
- ▶ Mount to any stud, shear wall, 6" X 6" NEMA 1 enclosure, Simple Support Bracket (pg. P1) or Ultimate Support Bracket (pg. P11)
- ▶ Can be used standalone for low voltage communications applications

### U.S. PATENT NO.:

7,468,486

## EXTENSIONS AND ACCESSORIES

### PRODUCT FEATURES

- ▶ Extensions ensure flush finish regardless of wall thickness
- ▶ Attach to SAR & WBAR model adjustable rings for additional 3/4" of depth
- ▶ Mount easily to ring with two 8-32 screws
- ▶ Multiple extensions can be installed on one ring
- ▶ UPC-12MA features domed cover for protecting Toggle & Decora™ -style switches
- ▶ UPC-12MA fits 1 Gang, 2 Gang, Multigang, & Adj. Rings

### U.S. PATENT NO.:

7,468,486

Cat. No.	Description	Standard	With One Extension Installed		Std. Pkg.
			+ 1GX75	+ 2GX75	
4SAR1G	1-Gang Adjustable Ring for 4" Sq. Deep Boxes	1/4" to 1-1/4"	1" to 2"	-	25
4SAR2G	2-Gang Adjustable Ring for 4" Sq. Deep Boxes	1/4" to 1-1/4"	-	1" to 2"	25



4SAR1G




4SAR2G




### ACCESSIBLE ADJUSTABILITY

Corner screws are easily accessible for adjustment before and after the device has been installed

Cat. No.	Description	Standard	With One Extension Installed		Std. Pkg.
			+ 1GX75	+ 2GX75	
WBAR1G	1-Gang Universal Box Bracket	1/4" to 1-1/4"	1" to 2"	-	25
WBAR2G	2-Gang Universal Box Bracket	1/4" to 1-1/4"	-	1" to 2"	25



WBAR1G



WBAR2G



WBAR on the 6" x 6" NEMA Enclosure

Cat. No.	Description	For Use With	Std. Pkg.
1GX75	1-Gang 3/4" Extension	4SAR1G, 5SAR1G, or WBAR1G Only	50
2GX75	2-Gang 3/4" Extension	4SAR2G, 5SAR2G, or WBAR2G Only	50
UPC	Gangable, Steel Universal Protective Cover protects any device during drywall, painting, routing, mudding & plastering		25
UPCTS	Optional Plastic Insert for UPC to protect Toggle Switch		25
UPC-12MA <b>NEW</b>	Gangable, Steel Universal Protective Cover, fits 1G, 2G, Multigang & Adj. Rings		50



1GX75



2GX75



UPC



UPCTS

**NEW**



UPC-12MA



\*SAR2G & 2GX75 Exploded View



Complete UPC Assembly Shown Installed with Toggle Switch



Multiple UPC-12MA shown installed on SSB-MB3 - Domed cover ideal for protecting Toggle Switch and other devices

## UL-APPROVED ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ Can be adjusted on the jobsite achieve a flush finish every time
- ▶ Captive screw ensures fast and convenient adjustment
- ▶ Design provides strong electrical and mechanical connections to meet UL requirements
- ▶ \*For Fixture/Luminaire Support of 50 lbs or less

Cat. No.	Description	Adjustability Range	Std. Pkg.
4AR1G-58	1-Gang Adjustable Ring for 4" Square Boxes	5/8" to 1-1/4"	25
4AR1G-34	1-Gang Adjustable Ring for 4" Square Boxes	3/4" to 1-1/2"	25
4AR2G-58	2-Gang Adjustable Ring for 4" Square Boxes	5/8" to 1-1/2"	25
5AR1G-58	1-Gang Adjustable Ring for 4-11/16" Square Boxes	5/8" to 1-1/4"	25
5AR1G-34 <b>NEW</b>	1-Gang Adjustable Ring for 4-11/16" Square Boxes	3/4" to 1-1/2"	25
5AR2G-58	2-Gang Adjustable Ring for 4-11/16" Square Boxes	5/8" to 1-1/2"	25
*4ARR-34	Round Adjustable Ring for 4" Square Boxes	3/4" to 1-1/2"	25
3GAR-34	3-Gang Adjustable Ring	3/4" to 1-1/2"	25



4AR1G-58  
4AR1G-34



4AR2G-58



5AR1G-58  
5AR1G-34 **NEW**



5AR2G-58



### ACCESSIBLE ADJUSTABILITY

Screws are easily accessible for adjustment before and after the device has been installed



\*4ARR-34



3GAR-34



See SSB-MB Series on pg. P2 for 3-6 Gang Adjustable Boxes

## 4" SQUARE (4S) BOXES LOW-VOLTAGE PARTITIONS

### NOTE

- ▶ Not compatible with Adj. Rings

Cat. No.	Description	For Use with 2-Gang Rings:	Std. Pkg.
4SP-100	For Use With 1-1/2" Deep Boxes	Flat, 1/4", 1/2", 3/4", 1"	25
4SP-200	For Use With 1-1/2" Deep Boxes	5/8", 1-1/4", 1-1/2", 1-3/4", 2"	25
4SDP-100	For Use With 2-1/8" Deep Boxes	Flat, 1/4", 1/2", 3/4", 1"	25
4SDP-200	For Use With 2-1/8" Deep Boxes	5/8", 1-1/4", 1-1/2", 1-3/4", 2"	25



4SP-100



4SP-200



4SDP-100



4SDP-200






**4-11/16" SQUARE (5S)  
SHALLOW BOX &  
EXTENSION RING**  
**WELDED**  
**1-1/2" DEEP**


29.5 Cu. In.

**WITH RAISED GROUND EMBOSS  
(EXCEPT FOR EXTENSION RING)**

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SSB-MKO	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
5SSB-MKO-EXT	8 - 1/2", 4 - MKO	-	24



5SSB-MKO



5SSB-MKO-EXT

**4-11/16" SQUARE (5S)  
BOXES**  
**DRAWN**  
**2-1/8" DEEP**

42.0 Cu. In.

**WITH RAISED GROUND EMBOSS  
& 10-32 GROUND SCREW**


**PRODUCT FEATURES**

- ▶ Back-center KO on D5SDB-CKO-S is replaced with a 0.27" diameter hole for use of 1/4" making for fast and efficient installation


**BOXES WITH PIGTAIL FEATURES**

- ▶ 10" Pigtail for D5SDB-CKO-PT-10


Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
D5SDB-50/75	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO	2 - 1/2", 10 - CKO	2 - 1/2", 2 - 3/4"	24
*D5SDB-CKO-PT-10	2 - 1/2", 10 - CKO	2 - 1/2", 2 - 3/4"	24
D5SDB-CKO-S	2 - 1/2", 10 - CKO	3 - 3/4"	24




D5SDB-50/75




D5SDB-CKO



\*D5SDB-CKO-PT-10



D5SDB-CKO-S



Secure D5SDB-CKO-S to ceiling with just a 1/4" rod and locknut



- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4-11/16" SQUARE (5S) BOXES

### WELDED

### 2-1/8" DEEP

42.0 Cu. In.

**WITH RAISED GROUND EMBOSS (EXCEPT FOR BRACKETED BOXES AND EXTENSION RINGS)**

#### BOXES WITH PIGTAIL FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw
- ▶ 10" Pigtail for BSA Series, PT-10 & A-PT


#### BSA FEATURES

- ▶ See pg. A9


#### NOTE

- ▶ \*Available in Durable Red Powder Coat Finish, see pg. A24
- ▶ 5S boxes with FB bracket are certified for Fixture/Luminaire Support of 50 lbs or less
- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
5SDB-50	-	12 - 1/2"	4 - 1/2"	24
5SDB-50/75	-	8 - 1/2", 4 - 3/4"	2 - 1/2", 2 - 3/4"	24
5SDB-75	-	12 - 3/4"	2 - 1/2", 2 - 3/4"	24
5SDB-75/100	-	4 - 3/4", 4 - 1"	2 - 1/2", 2 - 3/4"	24
5SDB-100	-	8 - 1"	2 - 1/2", 2 - 3/4"	24
5SDB-125	-	6 - 1-1/4"	2 - 1/2", 2 - 3/4"	24
*5SDB-MKO	-	2 - 1/2", 10 - MKO	2 - 1/2", 2 - 3/4"	24
5SDB-MKO-PT	-	2 - 1/2", 10 - MKO	2 - 1/2", 2 - 3/4"	24
5SDB-MKO-PT-10	-	2 - 1/2", 10 - MKO	2 - 1/2", 2 - 3/4"	24
5SDB-MKO-A-PT	-	12 - MKO	1 - 1/2", 3 - MKO	24
5SDB-50/75-FB	FB, Flush	6 - 1/2", 3 - 3/4"	3 - 1/2", 2 - 3/4"	24
5SDB-75/100-FB	FB, Flush	3 - 3/4", 3 - 1"	3 - 1/2", 2 - 3/4"	24
5SDB-100-FB	FB, Flush	6 - 1"	3 - 1/2", 2 - 3/4"	24
5SDB-MKO-FB	FB, Flush	2 - 1/2", 7 - MKO	3 - 1/2", 2 - 3/4"	24
5SDB-50/75-EXT	-	8 - 1/2", 4 - 3/4"	-	24
5SDB-MKO-EXT	-	2 - 1/2", 10 - MKO	-	24
*5SDB-50/75-PT-BSA	Back Support Arm	8 - 1/2", 4 - 3/4"	3 - 3/4"	24
*5SDB-50/75-AB-PT-BSA	AB, Flush, Back Support Arm	6 - 1/2", 3 - 3/4"	3 - 3/4"	24




5SDB-50




5SDB-50/75




5SDB-75




5SDB-75/100




5SDB-100




5SDB-125




\*5SDB-MKO




5SDB-MKO-PT  
5SDB-MKO-PT-10




5SDB-MKO-A-PT




5SDB-50/75-FB




5SDB-75/100-FB




5SDB-100-FB




5SDB-MKO-FB




5SDB-50/75-EXT



5SDB-MKO-EXT



\*5SDB-50/75-PT-BSA



\*5SDB-50/75-AB-PT-BSA



\*While Supplies Last

# A18 | 5S Deep Boxes & Covers

## 4-11/16" SQUARE (5S) BOXES

**WELDED**  
2-1/8" DEEP  
42.0 Cu. In.

### BX/MC CLAMP

- ▶ All MC series boxes are suitable for use with MCI-A Type

### METAL STUD BRACKET

- ▶ U.S. Patent No.: 8,262,043 Metal Stud (MS) Bracket Engages On Either Side Of A Metal Stud
- \*\*Model Revised Feb. 2008

### NOTE

- ▶ 5SDB-MC-FB is certified for Fixture/ Luminaire Support of 50 lbs or less

## 4-11/16" SQUARE (5S) LARGE CAPACITY BOX

**WELDED**  
2-1/2" DEEP  
49.4 Cu. In.

WITH RAISED GROUND EMBOSS & TWO #8-32 x 1/2" MOUNTING SCREWS


### PRODUCT FEATURES

- ▶ Ideal for use with SSB System when 1-1/4" K.O required (see pg. P1 for SSB info.)
- ▶ Suitable for Datacom & Electrical Applications
- ▶ Durable Blue Powder Coat Finish for B-5SLB


## 4-11/16" SQUARE (5S) 1-GANG & 2-GANG

DEVICE RINGS  
**FLAT, DRAWN**


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
5SDB-MC	-	6 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24
5SDB-MC-FB	FB, Flush	3 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24
5SDB-MC-MS**	MS, Self-Gripping + Box Support Clip	3 - MKO, 4 - Loom	3 - 1/2", 2 - 3/4"	24



5SDB-MC




5SDB-MC-FB



5SDB-MC-MS\*\*

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
5SLB-2MKO	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24
B-5SLB	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24




5SLB-2MKO




B-5SLB




Cat. No.	Description	Gangs	Cu. Inch	Std. Pkg.
51000	Flat	1	-	50
51025	Raised 1/4"	1	1.8	50
51050	Raised 1/2"	1	3.8	50
51058	Raised 5/8"	1	4.3	50
51075	Raised 3/4"	1	5.5	50
51100	Raised 1"	1	7.5	25
51125	Raised 1-1/4"	1	9.4	25
51150	Raised 1-1/2"	1	11.2	25
51200	Raised 2"	1	14.4	25
52000	Flat	2	-	50
52025	Raised 1/4"	2	3.0	50
52050	Raised 1/2"	2	5.8	50
52058	Raised 5/8"	2	7.5	50
52075	Raised 3/4"	2	8.8	50
52100	Raised 1"	2	11.8	25
52125	Raised 1-1/4"	2	14.5	25
52150	Raised 1-1/2"	2	15.5	25
52200	Raised 2"	2	20.7	25




51000



51025  
51050  
51058  
51075  
51100  
51125  
51150  
51200



52000



52025  
52050  
52058  
52075  
52100  
52125  
52150  
52200

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4-11/16" SQUARE (5S) COVERS

### FLAT OR DRAWN


#### PRODUCT FEATURES

- For X covers, four dual-direction mounting tabs -install devices in any orientation


#### NOTE

- \*Available in Durable Blue or Red Powder Coat Finish, see pg. A23 or A24


Cat. No.	Description	Cu. Inch	Std. Pkg.
*5BC	Flat, Blank	-	50
5BCK	Flat, 1/2" KO	-	50
5BC-MKO	Flat, MKO	-	50
53000X <b>NEW</b>	Flat, Open, Dual Dir. Ears 2-3/4" O.C.	-	50
53050X <b>NEW</b>	Raised 1/2", Open, Dual Dir. Ears 2-3/4" O.C.	3.0	50
53058X <b>NEW</b>	Raised 5/8", Open, Dual Dir. Ears 2-3/4" O.C.	4.0	50
53075X <b>NEW</b>	Raised 3/4", Open, Dual Dir. Ears 2-3/4" O.C.	5.0	50
53100X <b>NEW</b>	Raised 1", Open, Dual Dir. Ears 2-3/4" O.C.	6.8	25
53125X <b>NEW</b>	Raised 1-1/4", Open, Dual Dir. Ears 2-3/4" O.C.	8.5	25
53150X <b>NEW</b>	Raised 1-1/2", Open, Dual Dir. Ears 2-3/4" O.C.	9.7	25
53200X <b>NEW</b>	Raised 2", Open, Dual Dir. Ears 2-3/4" O.C.	12.9	25




\*5BC




5BCK



5BC-MKO



53000X



53050X  
53058X  
53075X  
53100X  
53125X  
53150X  
53200X



**DUAL-DIRECTION  
FIXTURE RINGS**

Orbit's New Standard

## UNIVERSAL 4" & 4-11/16" SQUARE TO 40 FIXTURE RING DRAWN

#### PRODUCT FEATURES

- Mounts to 4" or 4-11/16" square boxes
- 4" octagon opening (3-1/2" O.C.)
- Four dual-direction mounting tabs with #8-32 threads
- Increase box fill volume by 95% versus deep 40 boxes
- Ideal for light fixtures, sensors, LED drivers, and other 40 devices
- For fixture/luminaire support of 50 lbs. or less
- 16 GA Sheet Steel

Cat. No.	Ring Depth	Cu. Inch	Std. Pkg.
54058X <b>NEW</b>	Raised 5/8"	7.5	50
54075X <b>NEW</b>	Raised 3/4"	8.8	50
54100X <b>NEW</b>	Raised 1"	11.8	50
54125X <b>NEW</b>	Raised 1-1/4"	14.5	50



54058X  
54075X  
54100X  
54125X



540X Series mounted on 4-11/16" Sq. Box between T-bar ceilings with SSB-TBAR



540X Series installed on 4SDB-MKO-FB mounted to ceiling joist



Fits 4" & 4-11/16" Square Boxes

**EC&M**  
Product of the Year  
2023 Category Winner

**PATENTED**

## 4-11/16" SQUARE (5S) BOXES LOW-VOLTAGE PARTITIONS

#### NOTE

- Not compatible with Adj. Rings

Cat. No.	Description	For Use with 2-Gang Rings:	Std. Pkg.
5SDP-100	For use with 2-1/8" Deep Boxes	Flat, 1/4", 1/2", 3/4", 1"	25
5SDP-200	For use with 2-1/8" Deep Boxes	5/8", 1-1/4", 1-1/2", 1-3/4", 2"	25
5SLP-100	For use with 2-1/2" Deep Boxes	Flat, 1/4", 1/2", 3/4", 1"	25
5SLP-200	For use with 2-1/2" Deep Boxes	5/8", 1-1/4", 1-1/2", 1-3/4", 2"	25




5SDP-100



5SDP-200



5SLP-100



5SLP-200




# A20 | 5S Covers & Adjustable Rings



## 4-11/16" SQUARE (5S) INDUSTRIAL COVERS RAISED 1/2" 10 Cu. In.



Cat. No.	Description	Std. Pkg.
5501	Toggle Switch	25
5502	Duplex Receptacle	25
5503	Single Receptacle, 15A, 1.406" diameter	25
5504	GFCI or Decorative Switches	25
5505	Power Outlet, 20A, 1.60" diameter	25
5506	Power Outlet, 30A Locking, 1.750" diameter	25
5507	Power Outlet, 30 to 50A, 2.156" diameter	25
5508	Power Outlet, 30 to 60A, 2.625" diameter	25
5511	2 Toggle Switches	25
5512	Toggle Switch / Duplex Receptacle	25
5514	Toggle Switch / GFCI or Decorative Switches	25
5522	2 Duplex Receptacles	25
5524	Duplex Receptacle / GFCI or Decorative Switches	25
5544	2 GFCIs or 2 Decorative Switches	25



## UL-APPROVED 4-11/16" SQUARE (5S) ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ Can be adjusted on the jobsite for a quick installation
- ▶ Adjusts to achieve a flush finish every time
- ▶ Patented design provides strong electrical and mechanical connections to meet UL requirements

Cat. No.	Description	Adjustability Range	Std. Pkg.
5AR1G-58	1-Gang Adjustable Ring for 4-11/16" Square Boxes	5/8" to 1-1/4"	25
5AR1G-34 <b>NEW</b>	1-Gang Adjustable Ring for 4-11/16" Square Boxes	3/4" to 1-1/2"	25
5AR2G-58	2-Gang Adjustable Ring for 4-11/16" Square Boxes	5/8" to 1-1/2"	25



5AR1G-58  
5AR1G-34 **NEW**



5AR2G-58



### ACCESSIBLE ADJUSTABILITY

Screws are easily accessible for adjustment before and after the device has been installed

## 4-11/16" SQUARE (5S) ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ For use with 4-11/16" Square (5S) 2-1/8" or deeper boxes
- ▶ 1/4" to 1-1/4" adjustability range
- ▶ Rings achieve a flush finish every time
- ▶ Compatible with exclusive extensions for infinite wall depths

### U.S. PATENT NO.:

7,468,486



**Video Available  
On Our Website!**

Cat. No.	Description	Standard	With One Extension Installed		Std. Pkg.
			+ 1GX75	+ 2GX75	
5SAR1G	1-Gang Adjustable Ring for 4-11/16" Sq. Deep Boxes	1/4" to 1-1/4"	1" to 2"	-	25
5SAR2G	2-Gang Adjustable Ring for 4-11/16" Sq. Deep Boxes	1/4" to 1-1/4"	-	1" to 2"	25



5SAR1G



5SAR2G



### ACCESSIBLE ADJUSTABILITY

Corner screws are easily accessible for adjustment before and after the device has been installed

## STUD MOUNTING ADJUSTABLE RINGS


### PRODUCT FEATURES

- ▶ Accepts 4" or 4-11/16" square boxes in line voltage applications
- ▶ Mount to any stud, shear wall, 6" X 6" NEMA 1 enclosure, Simple Support Bracket (pg. P1) or Ultimate Support Bracket (pg. P11)
- ▶ Can be used standalone for low voltage communications applications


### U.S. PATENT NO.:

7,468,486

Cat. No.	Description	Standard	With One Extension Installed		Std. Pkg.
			+ 1GX75	+ 2GX75	
WBAR1G	1-Gang Universal Box Bracket	1/4" to 1-1/4"	1" to 2"	-	25
WBAR2G	2-Gang Universal Box Bracket	1/4" to 1-1/4"	-	1" to 2"	25



WBAR1G



WBAR2G



WBAR on the 6" x 6" NEMA Enclosure

## EXTENSIONS AND ACCESSORIES

### PRODUCT FEATURES

- ▶ Extensions ensure flush finish regardless of wall thickness
- ▶ Attach to adjustable ring for additional 3/4" of depth
- ▶ Mount easily to ring with two 8-32 screws
- ▶ Multiple extensions can be installed on one ring
- ▶ UPC-12MA features domed cover for protecting Toggle & Decora™ -style switches
- ▶ UPC-12MA fits 1 Gang, 2 Gang, Multigang, & Adj. Rings

### U.S. PATENT NO.:

7,468,486

Cat. No.	Description	For Use With	Std. Pkg.
1GX75	1-Gang 3/4" Extension	4SAR1G, 5SAR1G, or WBAR1G Only	50
2GX75	2-Gang 3/4" Extension	4SAR2G, 5SAR2G, or WBAR2G Only	50
UPC	Gangable, Steel Universal Protective Cover protects any device during drywall, painting, routing, mudding & plastering		25
UPCTS	Optional Plastic Insert for UPC to protect Toggle Switch		25
UPC-12MA <b>NEW</b>	Gangable, Steel Universal Protective Cover, fits 1G, 2G, Multigang & Adj. Rings		50



1GX75



2GX75



UPC



UPCTS



UPC-12MA



Exploded View



Complete UPC Assembly Shown Installed with Toggle Switch



Multiple UPC-12MA shown installed on SSB-MB3 - Domed cover ideal for protecting Toggle Switch and other devices



# A22 | True 5" Boxes & Accessories

Boxes & Covers

## TRUE 5" SQUARE BOXES

**WELDED**

**3-1/4" DEEP**

71.8 Cu. In.

**WITH RAISED GROUND EMBOSS**

### PRODUCT FEATURES


- ▶ More than double capacity compared to 4" square boxes
- ▶ Extra space easily meets minimum bend radius for easier installations
- ▶ Increased space reduces short circuits and ground faults due to space and cable stress
- ▶ Supports all current copper CAT and fiber optic cables as well as predicted increases
- ▶ Use T5R or any Orbit 5" Sq. Box Mounting brackets to use 4" rings on 5" boxes

### NOTE

- ▶ \*Available in Durable Blue Powder Coat Finish, see pg. A23

Cat. No.	Description	Knockouts		Std. Pkg.
		Sides	Bottom	
*T5B-200	True 5" Square Box	2 - 1" to 2" CKO 4 - 1/2" to 1-1/4" CKO	1 - 1/2" & 3/4" MKO 1 - 3/4" & 1" MKO 1 - 1/2" KO & Two Ground Screws On Bottom	10
T5B-50/200	True 5" Square Box, 1/2" KO & 2" MKO	8 - 1/2" 2 - 1" to 2" CKO 4 - 1/2" & 3/4" CKO	1 - 1/2" 1 - 1/2" & 3/4" MKO 1 - 3/4" & 1" MKO	10

**Video Available On Our Website!**



\*T5B-200

T5B-200  
5" x 5" x 3-1/4"

T5B-50/200

T5B-50/200  
5" x 5" x 3-1/4"

## INSTALLATION

**Brackets allow for 4" ring compatibility!**



### Stud Mount with UMA-LVBS

Mount 4" Rings on 5" Boxes with UMA-LVBS

### Adjustable between Stud with SSB-T5

Snap UMA-LVBS onto SSB-T5 (pg. P1) to position the box exactly where you want

### Fixed between Stud with FB-4

Compatible with Orbit's Flat Bracket Family (pg. P13) and Fixed Mounting Brackets (pg.P15)

## 5" SQUARE BOXES ACCESSORIES


### PRODUCT FEATURES

- ▶ Steel Partitions allows for multi-system installations inside junction box
- ▶ T5R eliminates need for 5" sq. rings
- ▶ Partitions not compatible with Adj. Rings

### NOTE

- ▶ \*Available in Durable Blue Powder Coat Finish, see pg. A23

Cat. No.	Description	For Use with 2-Gang Rings:	Std. Pkg.
*T5C	True 5" Blank Cover	-	50
T5R	True 5" Reducer Cover, 4" Sq Opening, screws to mount 4" Sq. Ring included	-	50
T5P-100	True 5" Square Box Partition For 3-1/4" Deep Boxes	Flat to 1"	25
T5P-200	True 5" Square Box Partition For 3-1/4" Deep Boxes	5/8", 1-1/4" to 2"	25



T5C

T5R

T5R has the pre-Installed screws which are prepared to take any 4" Ring

T5P-100

T5P-200

## LARGE CAPACITY DATA BOXES AND COVERS

**WELDED**

**WITH RAISED GROUND EMBOSS**

### PRODUCT FEATURES

- ▶ Provides easy identification of products containing cabling of Data Systems
- ▶ Prevents need for repainting
- ▶ Increased space reduces short circuits and ground faults due to space and cable stress
- ▶ Durable Blue Powder Coat Finish

Cat. No.	Description	Knockouts		Std. Pkg.
		Sides	Bottom	
<b>B-5BC</b>	Blue 4-11/16" Square Blank Cover	-	-	50
<b>B-5SLB</b>	Blue 4-11/16" Sq., 2-1/2" Deep, 49.4 Cu. In.	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24
<b>5SLB-2MKO</b>	4-11/16" Square, 2-1/2" Deep, 49.4 Cu. In. Large Capacity Box	4 - 3/4" & 1" MKO 4 - 1" & 1-1/4" MKO	2 - 1/2", 2 - 3/4"	24
<b>B-T5C</b>	Blue True 5" Sq. Blank Cover	-	-	50
<b>B-T5B</b>	Blue True 5" Sq., 3-1/4" Deep Box, 71.8 Cu. In.	2 - 1" to 2" CKO 2 - 1" & 1-1/4" MKO 2 - 1/2" & 3/4" MKO	1 - 1/2" 1 - 1/2" & 3/4" MKO 1 - 3/4" & 1" MKO	12



B-5BC



B-5SLB



5SLB-2MKO




B-T5C



B-T5B

**Compatible Mounting Brackets in P Section**

## INSTALLATION



### FB-4 SHOWN INSTALLED

The Flat Bracket can be positioned to accommodate irregular stud spacings. See page P13-14 for more details



## FIRE ALARM BOXES & COVERS

### PRODUCT FEATURES

- ▶ Provide easy identification of products containing cabling of Fire Alarm Systems
- ▶ Prevent need for repainting
- ▶ Industrial, Commercial or Residential Use
- ▶ Durable Red Powder Coat Finish

### NOTE

- ▶ Additional specs located with corresponding models without red finish in catalog
- ▶ All 4S Boxes are certified for Fixture/Luminaire Support of 50 lbs or less (except for UMAB & UMIAB)
- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls (4S Box only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

Cat. No.	Description	Knockouts		Std. Pkg.
		Sides	Bottom	
*FA-4RBC	Red 4" Octagon Blank Cover	-	-	50
FA-4BC	Red 4" Square Blank Cover	-	-	50
FA-4SB-MKO	Red 4" Square, 1-1/2" Deep Box	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	50
FA-4SB-MKO-EXT	Red 4" Square, 1-1/2" Deep Extension	8 - 1/2", 4 - MKO	-	50
FA-4SDB-75	Red 4" Square, 2-1/8" Deep Box	8 - 3/4"	2 - 1/2", 2 - MKO	24
FA-4SDB-MKO	Red 4" Square, 2-1/8" Deep Box	8 - 1/2", 4 - MKO	2 - 1/2", 2 - MKO	24
FA-4SDB-MKO-FB	Red 4" Square, 2-1/8" Deep Box w/ FB Bracket	6 - 1/2", 3 - MKO	3 - 1/2", 2 - MKO	24
FA-4SEDB-CKO	Red 4" Square, 3-1/2" Deep Box	12 - CKO	4 - CKO	24
*FA-4SEDB-CKO-FB	Red 4" Square, 3-1/2" Deep Box w/ FB Bracket	10 - CKO	4 - CKO	10
FA-UMAB	External Adjustment Red 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 0" to 1-1/2"	12 - CKO	4 - CKO	10
FA-UMIAB-35 <b>NEW</b>	Internal Adjustment Red 4" Square, 3-1/2" Deep Box, 46 Cu. In., Adj. range: 1/2" to 1-1/2"	12 - CKO	4 - CKO	10
FA-UMAB-4R	External Adjustment Red 4" (4O), 2-1/8" Deep Box, 21.1 Cu. In., Adj. range: 0" to 1-1/2"	2 - 1/2", 2 - MKO	3 - 1/2", 2 - 3/4"	20
FA-5BC	Red 4-11/16" Square Blank Cover	-	-	50
FA-5SDB-MKO	Red 4-11/16" Square, 2-1/8" Deep Box	2 - 1/2", 10 - MKO	2 - 1/2", 2 - 3/4"	24



\*FA-4RBC



FA-4BC



FA-4SB-MKO



FA-4SB-MKO-EXT



FA-4SDB-75



FA-4SDB-MKO



FA-4SDB-MKO-FB



FA-4SEDB-CKO



\*FA-4SEDB-CKO-FB



FA-UMAB



FA-UMIAB-35



FA-UMAB-4R



FA-5BC



FA-5SDB-MKO

## UNIVERSAL CUT-IN BOX ADAPTER

### PRODUCT FEATURES

- ▶ Quickly mount any 4" square steel junction box into old work applications
- ▶ Works with 4" square boxes of any depth
- ▶ Two integrated old work steel clips with screws
- ▶ For drywall or other wall materials
- ▶ Small footprint easily concealed by life safety devices greater than 4-7/8" W X 4-3/4" H
- ▶ Available in Red powder coat finish for FA circuits

Visit our website to download a wall mounting template

Cat. No.	Description	Std. Pkg.
UCIA-4S <b>NEW</b>	Cut-in adapter for 4" Square Boxes	20
FA-UCIA-4S <b>NEW</b>	Red Cut-in adapter for 4" Square Boxes	20

### Turn any 4" square box into an "Old Work" box!



UCIA-4S



FA-UCIA-4S



**FIRE ALARM**



**PREFABRICATION**

Small footprint easily concealed by life safety devices Prepare 4" boxes with UCIA-4S in the shop


## MULTIGANG SWITCH BOXES

**DRAWN**


**2-1/8" DEEP**

**WITH RAISED GROUND EMBOSS & DEVICE EARS**


Cat. No.	No. of Gangs	Bracket & Setback	Knockouts		Dimension W x H	Cu. Inch	Std. Pkg.
			Sides	Bottom			
DHB-2	2	-	4 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	4" x 4"	30.3	25
DHB-3	3	-	4 - 1/2", 6 - CKO	2 - 1/2", 2 - 3/4"	5-3/4" x 4"	44.0	25
DHB-4	4	-	4 - 1/2", 8 - CKO	5 - 1/2", 4 - 3/4"	7-1/2" x 4"	57.8	20
DHB-3-B	3	B, 9/16"	2 - 1/2", 6 - CKO	2 - 1/2", 2 - 3/4"	5-3/4" x 4"	44.0	20
DHB-4-B	4	B, 9/16"	2 - 1/2", 8 - CKO	5 - 1/2", 4 - 3/4"	7-1/2" x 4"	57.8	20
DHB-2-FB	2	FB, 9/16"	2 - 1/2", 4 - CKO	2 - 1/2", 2 - 3/4"	4" x 4"	30.3	25
DHB-3-FB	3	FB, 9/16"	2 - 1/2", 6 - CKO	2 - 1/2", 2 - 3/4"	5-3/4" x 4"	44.0	20
DHB-4-FB	4	FB, 9/16"	2 - 1/2", 8 - CKO	5 - 1/2", 4 - 3/4"	7-1/2" x 4"	57.8	20




DHB-2




DHB-3




DHB-4




DHB-3-B




DHB-4-B



DHB-2-FB



DHB-3-FB



DHB-4-FB

## MULTIGANG SWITCH BOXES


**WELDED**

**1-5/8" DEEP**


**& LOW VOLTAGE PARTITION**

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls (2-Gang only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information


Cat. No.	No. of Gangs	Knockouts		Dimension W x H	Cu. Inch	Std. Pkg.	
		Sides	Bottom				
SB-2	2	6 - 1/2", 6 - MKO	3 - 1/2", 2 - 3/4"	6-13/16" x 4-9/16"	56.3	5	
SB-3	3	8 - 1/2", 6 - MKO	6 - 1/2", 4 - 3/4"	8-5/8" x 4-9/16"	65.0	5	
SB-4	4	8 - 1/2", 8 - MKO	6 - 1/2", 4 - 3/4"	10-7/16" x 4-9/16"	80.0	5	
SB-5	5	10 - 1/2", 8 - MKO	6 - 1/2", 4 - 3/4"	12-1/4" x 4-9/16"	94.8	5	
SB-6	6	10 - 1/2", 10 - MKO	6 - 1/2", 4 - 3/4"	14-1/16" x 4-9/16"	111.1	1	
SB-7	7	12 - 1/2", 10 - MKO	9 - 1/2", 6 - 3/4"	15-7/8" x 4-9/16"	127.0	1	
SB-8	8	12 - 1/2", 12 - MKO	9 - 1/2", 6 - 3/4"	17-11/16" x 4-9/16"	142.1	1	
SB-9	9	14 - 1/2", 12 - MKO	9 - 1/2", 6 - 3/4"	19-1/2" x 4-9/16"	157.9	1	
SB-10	10	14 - 1/2", 14 - MKO	9 - 1/2", 6 - 3/4"	21-3/8" x 4-9/16"	172.1	1	
SB-D	Partition for 1-5/8" SB Boxes, flat or raised cover						25



SB-2



SB-3



SB-6



SB-D



Mount Multigang boxes between studs on Orbit's SSB System. See pg. P1 for more info









**MULTIGANG  
DEEP SWITCH BOXES  
WELDED  
2-1/2" DEEP  
& LOW VOLTAGE  
PARTITION**

Cat. No.	No. of Gangs	Knockouts		Dimension W x H	Cu. Inch	Std. Pkg.
		Sides	Bottom			
<b>SDB-2</b>	2	4 - 3/4", 8 - 1/2" & 3/4" MKO	3 - 1/2", 2 - 3/4"	6-13/16" x 4-9/16"	70.0	5
<b>SDB-3</b>	3	8 - 3/4", 6 - 1/2" & 3/4" MKO	6 - 1/2", 4 - 3/4"	8-5/8" x 4-9/16"	90.0	5
<b>SDB-4</b>	4	4 - 3/4", 8 - 1/2" & 3/4" MKO	6 - 1/2", 4 - 3/4"	10-7/16" x 4-9/16"	110.0	5
<b>SDB-5</b>	5	6 - 3/4", 8 - 1/2" & 3/4" MKO	6 - 1/2", 4 - 3/4"	12-1/4" x 4-9/16"	130.0	5
<b>SDB-6</b>	6	6 - 3/4", 8 - 1/2" & 3/4" MKO	6 - 1/2", 4 - 3/4"	14-1/16" x 4-9/16"	150.0	1
<b>SDBL-2</b>	2	4 - 3/4", 8 - 3/4" & 1" MKO	3 - 1/2", 2 - 3/4"	6-13/16" x 4-9/16"	70.0	5
<b>SDBL-3</b>	3	8 - 3/4", 6 - 3/4" & 1" MKO	6 - 1/2", 4 - 3/4"	8-5/8" x 4-9/16"	90.0	5
<b>SDBL-4</b>	4	4 - 3/4", 8 - 3/4" & 1" MKO	6 - 1/2", 4 - 3/4"	10-7/16" x 4-9/16"	110.0	5
<b>SDBL-5</b>	5	6 - 3/4", 8 - 3/4" & 1" MKO	6 - 1/2", 4 - 3/4"	12-1/4" x 4-9/16"	130.0	5
<b>SDBL-6</b>	6	6 - 3/4", 8 - 3/4" & 1" MKO	6 - 1/2", 4 - 3/4"	14-1/16" x 4-9/16"	150.0	1
<b>SDB-D</b>	Partition for 1-5/8" Deep SB Boxes, flat, and & 2-1/2" SDB Boxes, flat or raised cover					25

3/4" & 1" Knockouts  
1/2" & 3/4" Knockouts







**BLANK AND DEVICE COVERS  
FOR MULTIGANG BOXES  
2 TO 10 GANGS  
FLAT**

**NOTE**

▶ Same W & H dimensions as SB & SR Series

Blank Cat. No.	Duplex Receptacle Cat. No.	Decorative or GFCI Cat. No.	Toggle Switch Cat. No.	No. of Gangs	Std. Pkg.
<b>4M2-B</b>	<b>4M2-DR</b>	<b>4M2-GFI</b>	<b>4M2-TS</b>	2	5
<b>4M3-B</b>	<b>4M3-DR</b>	<b>4M3-GFI</b>	<b>4M3-TS</b>	3	5
<b>4M4-B</b>	<b>4M4-DR</b>	<b>4M4-GFI</b>	<b>4M4-TS</b>	4	5
<b>4M5-B</b>	<b>4M5-DR</b>	<b>4M5-GFI</b>	<b>4M5-TS</b>	5	5
<b>4M6-B</b>	<b>4M6-DR</b>	<b>4M6-GFI</b>	<b>4M6-TS</b>	6	1
<b>4M7-B</b>	<b>4M7-DR</b>	<b>4M7-GFI</b>	<b>4M7-TS</b>	7	1
<b>4M8-B</b>	<b>4M8-DR</b>	<b>4M8-GFI</b>	<b>4M8-TS</b>	8	1
<b>4M9-B</b>	<b>4M9-DR</b>	<b>4M9-GFI</b>	<b>4M9-TS</b>	9	1
<b>4M10-B</b>	<b>4M10-DR</b>	<b>4M10-GFI</b>	<b>4M10-TS</b>	10	1



- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls (2-Gang only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## 4" SQUARE RING ADAPTER FOR 3-GANG BOX FLAT

### PRODUCT FEATURES

- ▶ Ideal where 2-1/2" stud depths are common
- ▶ Compatible with any style of 4" square device rings, including adjustable depth models
- ▶ Increase box fill volume by 55% (up to 65 Cu. In.) versus deep 4-11/16" Sq. junction boxes (42 Cu. In.)
- ▶ Designed for use with Welded 3-Gang Outlet Boxes

Cat. No.	Description	No. of Gangs	Std. Pkg.
<b>4M3-4S</b> <span style="color: red;">NEW</span>	4" Sq. Ring Adapter for 3-Gang Welded Boxes	3-Gang to 4" Sq.	25




4M3-4S




4M3-4S Shown Installed on BHA-16, SB-3 & 4AR1G-58

## DEVICE RINGS FOR MULTIGANG BOXES 2 TO 10 GANGS RAISED 3/4"


Cat. No.	No. of Gangs	Dimension W x H	Cu. Inch	Std. Pkg.
<b>SR-2</b>	2	6-13/16" x 4-9/16"	9.1	5
<b>SR-3</b>	3	8-5/8" x 4-9/16"	14.9	5
<b>SR-4</b>	4	10-7/16" x 4-9/16"	21.0	5
<b>SR-5</b>	5	12-1/4" x 4-9/16"	25.5	5
<b>SR-6</b>	6	14-1/16" x 4-9/16"	30.8	1
<b>SR-7</b>	7	15-7/8" x 4-9/16"	36.1	1
<b>SR-8</b>	8	17-11/16" x 4-9/16"	41.1	1
<b>SR-9</b>	9	19-1/2" x 4-9/16"	46.4	1
<b>SR-10</b>	10	21-3/8" x 4-9/16"	51.3	1



SR-2



SR-3



SR-5

## UL-APPROVED ADJUSTABLE RINGS

### PRODUCT FEATURES

- ▶ Can be adjusted on the jobsite for a quick installation
- ▶ Adjusts to achieve a flush finish every time
- ▶ Patented design provides strong electrical and mechanical connections to meet UL requirements

Cat. No.	Description	Adjustability Range	Std. Pkg.
<b>3GAR-34</b>	3-Gang Adjustable Ring	3/4" to 1-1/2"	25



3GAR-34




**SSB-SDB SERIES**

Contact us for Custom Assemblies of Standard & Multigang Boxes  
Email [info@orbitprofab.com](mailto:info@orbitprofab.com)

# A28 | Masonry Boxes


## MASONRY BOXES WITH CONCENTRIC KNOCKOUTS (CKO) 2-1/2" DEEP

Cat. No.	No. of Gangs	Bracket & Setback	Knockouts			Dimension W x H	Cu. Inch	Std. Pkg.
			Ends	Bottom	Sides			
<b>MSBG-1</b>	1, Gangable	-	2	1	4	1-7/8" x 3-3/4"	16.1	25
<b>MSB-1</b>	1	-	2	1	4	1-7/8" x 3-3/4"	16.1	25
<b>MSB-2</b>	2	-	4	2	4	3-3/4" x 3-3/4"	31.9	10
<b>MSB-3</b>	3	-	6	3	4	5-1/2" x 3-3/4"	47.9	10
<b>MSB-4</b>	4	-	8	4	4	7-3/8" x 3-3/4"	63.6	10
<b>MSB-5</b>	5	-	10	5	4	9-1/8" x 3-3/4"	79.6	10
<b>MSB-6</b>	6	-	12	6	4	11" x 3-3/4"	95.3	1
<b>MSB-3-FB</b>	3	FB, 9/16"	6	3	2	5-1/2" x 3-3/4"	47.9	20
<b>MSB-4-FB</b>	4	FB, 9/16"	8	4	2	7-3/8" x 3-3/4"	63.6	20
<b>MSB-5-FB</b>	5	FB, 9/16"	10	5	2	9-1/8" x 3-3/4"	79.6	20



## MASONRY BOXES WITH CONCENTRIC KNOCKOUTS (CKO) 3-1/2" DEEP

Cat. No.	No. of Gangs	Knockouts			Dimension W x H	Cu. Inch	Std. Pkg.
		Ends	Bottom	Sides			
<b>MBG-1</b>	1, Gangable	4	1	4	1-7/8" x 3-3/4"	23.5	25
<b>MB-1</b>	1	4	1	4	1-7/8" x 3-3/4"	23.5	25
<b>MB-2</b>	2	8	2	4	3-3/4" x 3-3/4"	46.9	10
<b>MB-3</b>	3	12	3	4	5-1/2" x 3-3/4"	69.3	10
<b>MB-4</b>	4	16	4	4	7-3/8" x 3-3/4"	92.1	10
<b>MB-5</b>	5	20	5	4	9-1/8" x 3-3/4"	116.1	10
<b>MB-6</b>	6	24	6	4	11" x 3-3/4"	139.0	1



## SSB WITH PREASSEMBLED ADJUSTABLE MASON BOX 3-1/2" DEEP

### PRODUCT FEATURES

- ▶ Bracket adjusts from 15" to 25"
- ▶ Rigidity eliminates need for far-side back support
- ▶ Ships preassembled with box depth set at 5/8", and adjustable up to 1-1/2"
- ▶ Guided-slots on each side allow the box depth to be easily adjusted by simply loosening the screws
- ▶ Built-In Adapter allows Masonry Box to be moved along SSB Bracket until set in final position with a Tek screw
- ▶ All Knockouts are Concentric 1/2" & 3/4"

Cat. No.	No. of Gangs	KO Ends	KO Bottom	KO Sides	Cu. Inches	Std. Pkg.
<b>SSB-MB3</b>	3	(6) - CKO	(3) - CKO	(4) - CKO	69.3	10
<b>SSB-MB4</b>	4	(8) - CKO	(4) - CKO	(4) - CKO	92.1	10
<b>SSB-MB5</b>	5	(10) - CKO	(5) - CKO	(4) - CKO	116.1	10
<b>SSB-MB6</b>	6	(12) - CKO	(6) - CKO	(4) - CKO	139	10



SSB-MB3



6-way Adjustability

**PATENTED**



An ideal solution in Nurse Call systems and Headwall assemblies for healthcare projects



SSB-MB3 SIDE VIEW


Adjustment Screws & Guided Slots  
Adjustable 5/8" to 1-1/2"

## MASONRY BOX PARTITION

### PRODUCT FEATURES

- ▶ Fits 2-1/2" & 3-1/2" Masonry Boxes


Cat. No.	Description	Dimension W x H	Std. Pkg.
<b>MB-D</b>	2-1/2" / 3-1/2" Partition for MSB and MB Boxes	3-1/4" x 3-1/2"	25




MB-D

## MASONRY THRU BOXES WITH CONCENTRIC KNOCKOUTS (CKO)


Cat. No.	Dimension W x H	Depth	Knockouts		Cu. Inch	Std. Pkg.
			Ends	Sides		
<b>*MTB-350</b>	2" x 3-3/4"	3-1/2"	2	4	24.0	25
<b>*MTB-550</b>	2" x 3-3/4"	5-1/2"	4	8	38.0	25
<b>*MTB-750</b>	2" x 3-3/4"	7-1/2"	6	12	52.3	25



\*MTB-350



\*MTB-550



\*MTB-750

- ▶ **600V** CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information



\*While Supplies Last




## 4" OCTAGONAL CONCRETE BOXES

### NOTE


- ▶ For Fixture/Luminaire Support of 50 lbs or less
- ▶ \*For Fixture/Luminaire Support of 90 lbs or less, Fan Support of 70 lbs or less

See Page A5 for Covers & Rings


Cat. No.	Depth	Knockouts		Cu. Inch	Std. Pkg.
		Sides 1, 3, 5, 7	Sides 2, 4, 6, 8		
2CB	2"	1 - 1/2"	1 - 3/4"	24.4	25
25CB	2-1/2"	1 - 1/2"	1 - 3/4"	30.5	25
3CB	3"	1 - 1/2"	1 - 3/4"	37.0	25
3CB-75/100	3"	1 - 3/4"	1 - 1"	37.0	25
35CB	3-1/2"	2 - 1/2"	2 - 3/4"	43.0	25
35CB-75/100	3-1/2"	1 - 3/4"	1 - 1"	43.0	25
4CB	4"	2 - 1/2"	2 - 3/4"	49.2	25
4CB-75/100	4"	2 - 3/4"	2 - 1"	49.2	25
*4CB-F	4"	Side 1, 5; 1 - 1/2" Side 3, 7; 2 - 1/2"	Side 2, 6; 1 - 3/4" Side 4, 8; 2 - 3/4"	49.2	25
5CB	5"	2 - 1/2"	2 - 3/4"	61.7	10
6CB	6"	2 - 1/2"	2 - 3/4"	73.5	10




2CB  
25CB  
3CB




35CB  
4CB  
5CB  
6CB



3CB-75/100  
35CB-75/100



4CB-75/100



\*4CB-F




### FAN-RATED CONCRETE BOX


Inside tabs for fans up to 70 lbs (dynamic)

## 4" OCTAGONAL CONCRETE BOX COVERS


Cat. No.	Description	Std. Pkg.
CB-B	Flat, Blank	25
CB-B-PT	Flat, Blank - With 12" #12AWG Solid Pigtail	25
CB-BK	Flat With 3 - 1/2" KO's & 2 - 3/4" KO's	25
CB-BK-STUD	2 - 1/2" KO's & 2 - 3/4" KO's - With #3/8-18 Threaded Fixture Stud	25



CB-B



CB-B-PT



CB-BK




CB-BK-STUD



**SUPER SHALLOW HANDY BOX**  
**DRAWN**  
**1-1/4" DEEP**

2" W x 4" H  
8.5 Cu. In.

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
DHSSB-1-50	8 - 1/2"	3 - 1/2"	50




DHSSB-1-50


**SHALLOW HANDY BOXES AND EXTENSION RING**  
**WELDED**  
**1-1/2" DEEP**

2" W x 4" H  
11.5 Cu. In.


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
HSB-1-50	-	8 - 1/2"	3 - 1/2"	50
HSB-1-50-B	B, 1/4"	5 - 1/2"	3 - 1/2"	50
HSB-1-50-EXT	-	8 - 1/2"	-	50



HSB-1-50



HSB-1-50-B




HSB-1-50-EXT

**HANDY BOX**  
**DRAWN**  
**1-7/8" DEEP**


2" W x 4" H  
13.0 Cu. In.

WITH RAISED GROUND EMBOSS

Cat. No.	Knockouts		Std. Pkg.
	Sides	Bottom	
DHB-1-50	8 - 1/2"	2 - 1/2"	50
DHB-1-75	6 - 3/4"	2 - 1/2"	50



DHB-1-50




DHB-1-75


**HANDY BOXES AND EXTENSION RINGS**  
**WELDED**  
**1-7/8" DEEP**

2" W x 4" H  
13.0 Cu. In.


Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
HB-1-50	-	8 - 1/2"	2 - 1/2"	50
HB-1-MKO	-	4 - 1/2", 4 - MKO	1 - 1/2", 1 - MKO	50
HB-1-50-FB	FB, 9/16"	5 - 1/2"	3 - 1/2"	50
HB-1-MKO-FB	FB, 9/16"	2 - 1/2", 3 - MKO	2 - 1/2", 1 - MKO	50
HB-1-MKO-AB	AB, 9/16"	2 - 1/2", 3 - MKO	2 - 1/2", 1 - MKO	50
HB-1-50-EXT	-	8 - 1/2"	-	50
HB-1-MKO-EXT	-	4 - 1/2", 4 - MKO	-	50




HB-1-50




HB-1-MKO




HB-1-50-FB




HB-1-MKO-FB



HB-1-MKO-AB



HB-1-50-EXT



HB-1-MKO-EXT

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information



# A32 | Deep Handy Boxes & Covers



Boxes & Covers

## DEEP HANDY BOXES


**WELDED**

**2-1/8" DEEP**

2" W x 4" H

16.5 Cu. In.

Cat. No.	Bracket & Setback	Knockouts		Std. Pkg.
		Sides	Bottom	
<b>HDB-1-50</b>	-	8 - 1/2"	2 - 1/2"	50
<b>HDB-1-50-FB</b>	FB, 9/16"	5 - 1/2"	3 - 1/2"	50
<b>HDB-1-MKO</b>	-	4 - 1/2", 4 - MKO	1 - 1/2", 1 - MKO	50
<b>HDB-1-MKO-AB</b>	AB, 9/16"	2 - 1/2", 3 - MKO	2 - 1/2", 1 - MKO	50
<b>HDB-1-MKO-FB</b>	FB, 9/16"	2 - 1/2", 3 - MKO	2 - 1/2", 1 - MKO	50




## HANDY BOX COVERS

2-5/16" W x 4-3/16" H

▶ With Screw Pre-Installed

Cat. No.	Description	Std. Pkg.
<b>HBC-B</b>	Blank	25
<b>HBC-BK</b>	1/2" K.O.	25
<b>HBC-DR</b>	Duplex Receptacle	25
<b>HBC-GFI</b>	GFCI / Decorative Switch	25
<b>HBC-SR</b>	Single Receptacle, 15A, 1.406" diameter	25
<b>HBC-PO</b>	Power Outlet, 20A, 1.60" diameter	25
<b>HBC-TS</b>	Toggle Switch	25




## SPECIAL APPLICATION UTILITY BOX AND COVERS

2-1/2" W x 4-1/8" H

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ Acceptable for use in 2-hour rated walls
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

**ORBIT INDUSTRIES EXCLUSIVE**

Cat. No.	Description	Std. Pkg.
<b>WDHB-1-50</b>	1-7/8" Raised Deep Drawn Box w/ Ground Emboss, 17.0 Cu. In., 10 - 1/2" K.O.s	25
<b>WHBC-B</b>	3/16" Raised Cover, Blank	25
<b>WHBC-BK</b>	3/16" Raised Cover, 1/2" K.O.	25
<b>WHBC-DR</b>	3/16" Raised Cover, Duplex Receptacle	25
<b>WHBC-GFI</b>	3/16" Raised Cover, GFCI / Decorative Switch	25
<b>WHBC-SR</b>	3/16" Raised Cover, Single Receptacle, 15A, 1.406" diameter	25
<b>WHBC-TS</b>	3/16" Raised Cover, Toggle Switch	25



## UNIVERSAL CUT-IN BOX ADAPTER

### PRODUCT FEATURES

- ▶ Conveniently mount any 4" square steel junction box into old work applications
- ▶ Works with 4" square boxes of any depth
- ▶ Two integrated old work steel clips with screws
- ▶ For drywall or other wall materials
- ▶ Small footprint easily concealed by life safety devices greater than 4-7/8" W X 4-3/4" H
- ▶ Available in Red powder coat finish for FA circuits

Visit our website to download a wall mounting template


Cat. No.	Description	Std.Pkg.
<b>UCIA-4S</b> <span style="background-color: yellow;">NEW</span>	Cut-in adapter for 4" Square Boxes	20
<b>FA-UCIA-4S</b> <span style="background-color: yellow;">NEW</span>	Red Cut-in adapter for 4" Square Boxes	20

NEW



UCIA-4S

NEW



FA-UCIA-4S

Turn any 4" square box into an "Old Work" box!



### FIRE ALARM

Small footprint easily concealed by life safety devices



### PREFABRICATION

Prepare 4" boxes with UCIA-4S in the shop


## EXTRA SHALLOW GANGABLE SWITCH BOXES 1-1/2" DEEP

2" W x 3" H  
7.5 Cu. In.


### BX/MC CLAMP FEATURES

- ▶ All MC series boxes are suitable for use with MCI-A Type


Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
<b>GESB-1</b>	Ears only	-	2 - 1/2"	2 - 1/2"	50
<b>GESB-1-NM</b>	With NM Cable Clamps	-	4 - Loom	1 - 1/2"	50
<b>*GESB-1-MC</b>	With BX/MC Cable Clamps	-	4 - Loom	1 - 1/2"	50



GESB-1



GESB-1-NM




\*GESB-1-MC

## SHALLOW GANGABLE SWITCH BOXES 2" DEEP


2" W x 3" H  
10.0 Cu. In.

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ \*Acceptable for use in 2-hour rated walls (2-Gang only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information


Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
<b>GSB-1</b>	Ears only	4 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>GSB-1-NM</b>	With NM Cable Clamps	4 - 1/2"	4 - Loom	1 - 1/2"	50
<b>GSB-1-MC</b>	With BX/MC Cable Clamps	4 - 1/2"	4 - Loom	1 - 1/2"	50



GSB-1



GSB-1-NM



GSB-1-MC



\*While Supplies Last

# A34 | Gangable Switch Boxes



Boxes & Covers

## GANGABLE SWITCH BOXES 2-1/2" DEEP


12.5 Cu. In.  
2" W x 3" H  
(Except for TGW 2-1/4" W x 3" H, 15.0 Cu.In.)

### BX/MC FEATURES

▶ All MC series boxes are suitable for use with MCI-A Type

- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ \*Acceptable for use in 2-hour rated walls (2-Gang only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
<b>GB-1-NE</b>	No Ears, with Leveling Bumps	2 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>GB-1</b>	Ears only	4 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>GB-1-MKO</b>	Ears only, M.K.O.	2 - 1/2"	2 - MKO	1 - 1/2"	50
* <b>GB-1-B</b>	With B Bracket (9/16" Setback)	2 - 1/2"	2 - 1/2"	2 - 1/2"	50
* <b>GB-1-FB</b>	With FB Bracket (9/16" Setback)	2 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>GB-1-OW</b>	For Old Work, with Locking Grips	-	2 - 1/2"	2 - 1/2"	50
<b>GB-1-NM</b>	With NM Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
* <b>GB-1-NM-B</b>	With NM Cable Clamps & B Bracket	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
* <b>GB-1-NM-FB</b>	With NM Cable Clamps & FB Bracket	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>GB-1-NM-OW</b>	With NM Cable Clamps For Old Work, with Locking Grips	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>GB-1-MC</b>	With BX/MC Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
* <b>GB-1-MC-B</b>	With BX/MC Cable Clamps & B Bracket	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
* <b>GB-1-MC-FB</b>	With BX/MC Cable Clamps & FB Bracket	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>GB-1-MC-OW</b>	With BX/MC Cable Clamps For Old Work, with Locking Grips	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>TG-1</b>	Old Work Tigergrip	4 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>TG-1-NM</b>	Old Work Tigergrip, NM Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>TG-1-MC</b>	Old Work Tigergrip, BX/MC Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>TGW</b>	<b>Extra Wide</b> Old Work Tigergrip for easier installation of oversized devices (Non-Gangable) Must be used with Mid-Size or Jumbo Wall Plate	4 - 1/2"	2 - 1/2"	2 - 1/2"	50



**Extra Wide for Easier Installation of Oversized Devices**



## GANGABLE SWITCH BOXES 2-3/4" DEEP (Intermediate Depth)

2" W x 3" H - 4" W x 3" H  
14.0 Cu. In. - 28.0 Cu. In.  
( Except for TGMW and  
WMB-PT 2-1/4" W x 3" H,  
18.5 Cu. In.)

### PRODUCT FEATURES

- ▶ 7" Solid Cu. #12AWG Pigtail Preassembled with 10-32 Ground Screw (Except TGMW)
- ▶ 2-Gang Gangable Switch Boxes can be expanded to multi-gang to non-bracket side (Except TGMW and WMB-PT)


### BX/MC CLAMP FEATURES

- ▶ All MC series boxes are suitable for use with MCI-A Type


- ▶ **600V** MKO's and CKO's suitable for bonding without any additional bonding means up to 600V
- ▶ \*Acceptable for use in 2-hour rated walls (2-Gang only)
- ▶ Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information




Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
<b>GMB-1</b>	Ears only	4 - 1/2"	2 - MKO	2 - 1/2"	50
<b>**GMB-2-B</b>	With B Bracket	2 - 1/2"	4 - MKO	4 - 1/2"	25
<b>*GMB-1-FB</b>	With FB Bracket (9/16" Setback)	2 - 1/2"	2 - MKO	2 - 1/2"	50
<b>**GMB-2-FB</b>	With FB Bracket (9/16" Setback)	2 - 1/2"	4 - MKO	4 - 1/2"	25
<b>GMB-1-NM</b>	With NM Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>**GMB-1-NM-B</b>	NM Clamps & B Bracket (9/16" Setback)	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>**GMB-2-NM-FB</b>	NM Clamps & FB Bracket (9/16" Setback)	2 - 1/2"	4 - 1/2", 8 - Loom	2 - 1/2"	25
<b>*GMB-1-NM-OW</b>	With NM Cable Clamps, Old Work Grips	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>GMB-1-MC</b>	With BX/MC Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>**GMB-1-MC-B</b>	BX/MC Clamps & B Bracket (9/16" Setback)	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>**GMB-1-MC-FB</b>	BX/MC Clamps & FB Bracket (9/16" Setback)	2 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>*GMB-1-MC-OW</b>	With MC Cable Clamps, Old Work Grips	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>SGM-1</b>	Gangable Old Work Switch Box	4 - 1/2"	2 - MKO	2 - 1/2"	50
<b>SGM-1-NM</b>	Gangable Old Work NM Switch Box	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>SGM-1-MC</b>	Gangable Old Work BX/MC Switch Box	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
<b>TGMW</b>	<b>Extra Wide &amp; Deep</b> Old Work Tigergrip for easier installation of oversized devices (Non-Gangable) Must be used with Mid-Size or Jumbo Wall Plate	4 - 1/2"	2 - 1/2"	2 - 1/2"	50
<b>WMB-PT</b>	<b>Extra Wide &amp; Deep</b> Old Work Tigergrip for easier installation of oversized devices (Non-Gangable) Must be used with Mid-Size or Jumbo Wall Plate	4 - 1/2"	2 - MKO	2 - 1/2"	50




GMB-1




\*\*GMB-2-B




\*GMB-1-FB




\*\*GMB-2-FB




GMB-1-NM




\*\*GMB-1-NM-B




\*\*GMB-2-NM-FB




\*GMB-1-NM-OW




GMB-1-MC




\*\*GMB-1-MC-B




\*GMB-1-MC-FB




\*GMB-1-MC-OW




SGM-1




SGM-1-NM



SGM-1-MC



TGMW



WMB-PT

**Extra Wide & Deep for Easier Installation of Oversized Devices**



\*While Supplies Last

# A36 | Switch Boxes

## NON-GANGABLE NAIL-ON SWITCH BOXES 2-3/4" DEEP (Intermediate Depth)


2-1/8" W x 3" H  
15.9 Cu. In.

### WITH TWO MOUNTING NAILS


#### BX/MC CLAMP FEATURES

- All MC series boxes are suitable for use with MCI-A Type

Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
*GMB-NM-NO	Nail-On Non-Gangable, with NM Clamps	-	2 - 1/2", 4 - Loom	1 - 1/2"	50
**GMB-MC-NO	Nail-On Non-Gangable, with BX/MC Clamps	-	2 - 1/2", 4 - Loom	1 - 1/2"	50



\*GMB-NM-NO




\*\*GMB-MC-NO

## GANGABLE SWITCH BOXES 3-1/2" DEEP


2" W x 3" H  
18.0 Cu. In.

### WITH PRE-ASSEMBLED 10-32 GROUND SCREW & 7" SOLID CU. #12AWG PIGTAIL (EXCEPT FOR GDB-1-NE)


Cat. No.	Description	Knockouts			Std. Pkg.
		Sides	Ends	Bottom	
*GDB-1-NE	No Ears, with Leveling Bumps	4 - 1/2"	2 - 1/2", 2 - MKO	2 - 1/2"	50
GDB-1	Ears only	4 - 1/2"	2 - 1/2", 2 - MKO	2 - 1/2"	50
GDB-1-NM	With NM Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
**GDB-1-NM-B	With NM Cable Clamps & B Bracket	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
*GDB-1-NM-FB	With NM Cable Clamps & FB Bracket	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
GDB-1-MC	With BX/MC Cable Clamps	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
*GDB-1-MC-FB	With BX/MC Cable Clamps & FB Bracket	4 - 1/2"	2 - 1/2", 4 - Loom	1 - 1/2"	50
TGD-1	Gangable Old Work Tigerrip	4 - 1/2"	2 - 1/2", 2 - MKO	2 - 1/2"	50




\*GDB-1-NE




GDB-1




GDB-1-NM




\*\*GDB-1-NM-B




\*GDB-1-NM-FB



GDB-1-MC



\*GDB-1-MC-FB



TGD-1

- **600V** MKO's suitable for bonding without any additional bonding means up to 600V
- \*Acceptable for use in 2-hour rated walls (Up to 2-Gang)
- Visit [www.ul.com](http://www.ul.com) or QCIT Guide on page W1 for more information

## STEEL HEAVY DUTY T-GRID BOX HANGERS

### PRODUCT FEATURES

- ▶ Pre-galvanized steel hanger
- ▶ Includes spring steel box mounting clip
- ▶ No tools required to install
- ▶ Accommodates multiple junction boxes
- ▶ Mounts flush with face of tile
- ▶ 50 lbs. static load rating

Cat. No.	Include Components	Length	Box Depth	Std. Pkg.
<b>BHT-1HD</b> <small>NEW</small>	Mounting Clip	24"	1-1/2" 2-1/8"	25
<b>BHT-1HDEEP</b> <small>NEW</small>	Mounting Clip, 1 1/2" Extension Bracket	24"	1-1/2" 2-1/8" 3-5/8"	25



## STEEL T-BAR BOX HANGERS

### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ For T-Bar

Cat. No.	Description	Std. Pkg.
<b>BHT-1</b>	24" T-Bar bracket for use with boxes 1-1/2" or 2-1/8" Deep, Box Clip included	50
<b>BHT-1A</b>	24" T-Bar bracket - 8" height adjustable, Box Clip included	50
<b>BHT-C</b>	Additional Box Clip & Screw set for use with BHT-1 & BHT-1A	100




**BHT-1 INSTALLATION VIEW**

## STEEL T-BAR BRACKET


### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ For T-Bar

Cat. No.	Description	Std. Pkg.
<b>BH-3</b>	Straight Bracket for architectural recessed lights 25-1/4" long with notches 24" apart for use on T-Bar	50



Secure to T-bar using bending tabs to comply with NEC 315.23(d)



**BH-3 INSTALLATION VIEW**



# A38 | Bar Hangers



Accessories

## STEEL

### ADJUSTABLE BOX HANGERS FOR CEILING JOISTS

#### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ For Fixture/Luminaire Support of 50 lbs or less at 16" Span

Cat. No.	Description	Master Ctn.
BHA-1	Adjustable Bar Hanger with Stud for joist spacing 16" to 24" with #3/8-18 NPS Threaded Stud	50
BHA-1C	Adjustable Bar Hanger with Stud for joist spacing 16" to 24" with Box Clip	50



BHA-1



BHA-1C

## STEEL

### FIXED BAR HANGERS FOR CEILING JOISTS

#### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ For stud

Cat. No.	Description	Master Ctn.
BH-1	24" Straight Bar Hanger for mounting ceiling boxes, Slotted, Includes 2 Stove Bolt / Unit	50



BH-1

### ADJUSTABLE BAR HANGERS

#### PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Ends bend and wrap around studs
- ▶ Can be used with boxes 1-1/2", 2-1/8" or 2-1/2" deep
- ▶ For stud and hard lid ceiling joists

**SHIPS PREASSEMBLED**

Cat. No.	Description	Std. Pkg.
BHA-16	11" to 18" Adjustable Box Bracket – Mount box with self-tapping screws	50
BHA-24	15-3/4" to 26" Adjustable Box Bracket – Mount box with self-tapping screws	50




BHA-16

Adjust from 11" to 18"



BHA-24

Adjust from 15-3/4" to 26"



**Fits 3 different box depths**

- 1-1/2" Deep
- 2-1/8" Deep
- 2-1/2" Deep

**BOX AND CONDUIT SUPPORT BETWEEN STUDS USING BHA**

## DROP-ON-BAR SLIDER BRACKETS

### PRODUCT FEATURES


- ▶ Quickly attach to any 4" or 4-11/16" square box
- ▶ Easily drops onto Orbit's BHA-16 and BHA-24
- ▶ A BARB and box assembly can easily be repositioned along the hanger
- ▶ Multiple BARB assemblies can be added before and after the BHA is installed
- ▶ Can be fully prefabricated and locked onto the BHA without setting final box position
- ▶ BARB-CS includes cable support pin holes

**PATENTED**


**ORBIT INDUSTRIES  
EXCLUSIVE**

**Video Available  
On Our Website!**

Cat. No.	Description	Std. Pkg.
<b>BARB</b>	Drop-On-Bar Slider Bracket	50
<b>BARB-CS</b>	Drop-On-Bar Slider Bracket with conduit & cable support pin holes	50



BARB-CS includes cable support pinholes



### BENDABLE LOCKING TABS

A BARB and box assembly can be locked onto a BHA before arriving on the job site for quick adjustment in the field

PREASSEMBLED

-OR-

IN-FIELD

**1**

**Box Holder Tip!**

Attach to a 4" or 4-11/16" box with a single wafer head screw, forming a versatile box assembly

**2A**

Box assemblies can be prefabricated onto a BHA before arriving to the job site, locking onto the hanger via its bendable tabs

**2B**

For in-field installations, simply drop the box assembly onto a BHA before or after the hanger has been installed

**3**

Once the BHA is installed on studs, the box assembly can be adjusted along the hanger

**4**

Secure the assembly to the BHA with Tek screws, setting the box in place

**5**

Multiple box assemblies can be easily added!  
**Up to 3 between 16" & 4 between 24" studs**



# A40 | Pigtails & Wiretails



Accessories

## GROUND SCREWS & CLIP

Cat. No.	Description	Std. Master Pkg. Carton	
GS-1032	Ground Screw 10-32 x 3/8", Green, Slotted/Philips/Square/Hex Washer Head	100	1000
GS-1032-PT	GS-1032 with 7" Solid Cu. #12AWG Pigtail	50	250
GS-1032-PT-10	GS-1032 with 10" Solid Cu. #12AWG Pigtail	50	250
GS-1032-PT-12	GS-1032 with 12" Solid Cu. #12AWG Pigtail	50	250
PTST-8 <b>NEW</b>	GS-1032 with 8" Stranded Cu. #12AWG Pigtail and Flanged Spade Terminal	50	250
GC	Grounding Clip, for #14 - #10 AWG Copper	100	1000



## POWER WIRE TAILS SOLID

### PRODUCT FEATURES

- ▶ Both ends pre-stripped 5/8"

Cat. No.	Description	Std. Pkg.	Master Carton
WTSO-8-BLK <b>NEW</b>	8" Solid Cu. #12AWG, Black	50	250
WTSO-8-RED <b>NEW</b>	8" Solid Cu. #12AWG, Red	50	250
WTSO-8-BL <b>NEW</b>	8" Solid Cu. #12AWG, Blue	50	250
WTSO-8-GR <b>NEW</b>	8" Solid Cu. #12AWG, Green	50	250
WTSO-8-WH <b>NEW</b>	8" Solid Cu. #12AWG, White	50	250



## POWER WIRE TAILS STRANDED

### PRODUCT FEATURES


- ▶ One flanged spade terminal
- ▶ One end pre-stripped 5/8"

Cat. No.	Description	Std. Pkg.	Master Carton
WTST-8-BLK <b>NEW</b>	8" Stranded Cu. #12AWG and Flanged Spade, Black	50	250
WTST-8-RED <b>NEW</b>	8" Stranded Cu. #12AWG and Flanged Spade, Red	50	250
WTST-8-BL <b>NEW</b>	8" Stranded Cu. #12AWG and Flanged Spade, Blue	50	250
WTST-8-GR <b>NEW</b>	8" Stranded Cu. #12AWG and Flanged Spade, Green	50	250
WTST-8-WH <b>NEW</b>	8" Stranded Cu. #12AWG and Flanged Spade, White	50	250



## ACCESSORIES


Cat. No.	Description	Std. Pkg.
<b>SB-EXT</b>	Switch Box Extension fits any 1-Gang Box, adjustable from 1/4" to 1" to shield combustible wall surfaces from wiring system, 3.5 Cu. In.	25
<b>SBS</b>	Switch Box Support with bendable tabs, 20GA	100
<b>DLR-1G</b>	Device Leveler and Retainer, 1-Gang	50
<b>OWG</b>	Clips and locks old-work steel boxes tightly to wall. 2 required per box	100
<b>EOWB</b>	Ear for old work boxes with screws	100



SB-EXT




Installation View



SBS



Installation View



DLR-1G




Installation View



OWG



Installation View



EOWB



Installation View

## NAIL SAFETY PLATES


### PRODUCT FEATURES

- Provides protection from nail and screw penetration

Cat. No.	Features	Dimensions (W x L)	Thickness	Std. Pkg.
<b>SP-1</b>	With 2 Mounting Prongs & 1 Nail Hole each end	1.5" x 2.75"	16 GA	100
<b>SP-1-500</b>	With 2 Mounting Prongs & 1 Nail Hole each end	1.5" x 2.75"	16 GA	500
<b>SP-35</b>	With 2 Mounting Prongs & 1 Nail Hole each end	3" x 5"	16 GA	100
<b>SP-6</b>	With 2 Mounting Prongs & 1 Nail Hole each end	1.5" x 6"	16 GA	100
<b>SP-9</b>	With 4 Nail Holes each end	1.5" x 9"	16 GA	50
<b>SP-12</b>	With 4 Nail Holes each end	1.5" x 12"	16 GA	50
<b>SP-18</b>	With 6 Nail Holes each end	1.5" x 18"	16 GA	50
<b>SP-24</b>	With 6 Nail Holes each end	1.5" x 24"	16 GA	50
<b>*SPH-9</b>	Heavy-Duty, With 4 Nail Holes each end	1.5" x 9"	12 GA	50
<b>SPH-12</b>	Heavy-Duty, With 4 Nail Holes each end	1.5" x 12"	12 GA	50
<b>SPH-18</b>	Heavy-Duty, With 6 Nail Holes each end	1.5" x 18"	12 GA	50
<b>*SPH-24</b>	Heavy-Duty, With 6 Nail Holes each end	1.5" x 24"	12 GA	50



INSTALLATION VIEW




\*While Supplies Last



## FLEX/RIGID/EMT NAIL STRAPS

Cat. No.	FLEX/RIGID Size	EMT Size	Description	Std. Pkg.	Master Carton
NS-50	-	1/2"	EMT Nail Strap	100	1000
NS-50/75	1/2"	3/4"	Flex/Rigid/EMT Nail Strap	100	1000
NS-100	3/4"	1"	Flex/Rigid/EMT Nail Strap	100	1000



NS-50  
NS-50/75  
NS-100

## LOW VOLTAGE PRODUCTS

### LVSB PRODUCT FEATURES

- ▶ 1/2" raise
- ▶ Mounts vertically or horizontally
- ▶ Attaches to wooden or metal studs with the use of self-tapping screws or nails
- ▶ Can install onto the front or side of wood or metal studs
- ▶ Compatible with Simple Support Bracket (SSB-T5, pg. P1) and Ultimate Support Bracket (USB, pg. P11) for between stud applications

### LVWP PRODUCT FEATURES

- ▶ For Old Work applications
- ▶ Fits 1/2" to 1-1/4" drywall thickness
- ▶ Can also be used in plaster or tile openings
- ▶ Eliminates need to use electrical box for low voltage Class 2 wiring
- ▶ Requires only a drywall saw and screwdriver to install

Cat. No.	Description	Std. Pkg.
LVSB1	1-Gang Low Voltage Stud Mounting Bracket	50
LVSB2	2-Gang Low Voltage Stud Mounting Bracket	25
LVWP1	1-Gang Low Voltage Wall Mounting Plate	50
LVWP2	2-Gang Low Voltage Wall Mounting Plate	25




## STEEL BACK SUPPORTS

### PRODUCT FEATURES

- ▶ Electroplated Zinc

Cat. No.	Description	Std. Pkg.
ABS	Far-Side Box Support for 1-1/2" & 2-1/8" deep boxes, for use with 4" metal studs	50
ABS-6	Far-Side Box Support for 1-1/2" & 2-1/8" deep boxes, for use with 6" metal studs	50



## JACK CHAIN

### PRODUCT FEATURES

- ▶ Steel
- ▶ Electroplated Zinc
- ▶ 25 lbs. Max. Load
- ▶ In Steel Reel



Cat. No.	Trade Size	Std. Pkg.
JC-12	12GA	100

## "S" HOOK

### PRODUCT FEATURES

- ▶ Steel
- ▶ Electroplated Zinc
- ▶ 25 lbs. Max. Load



Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
SH-2	12GA, 1-1/4"	100	1000

## HANGER SCREW WITH SINGLE HOLE

### PRODUCT FEATURES

- ▶ Steel
- ▶ Wood Screw Thread




Cat. No.	Description	Dimension	Std. Pkg.	Master Ctn.
H-SCREW	Flat Hanger Screw	1/4" x 3"	100	500

## FIXTURE HANGER

### PRODUCT FEATURES

- ▶ Steel



Cat. No.	For Use With	Mount Position	Std. Pkg.	Master Ctn.
FH-E	2, 3, or 4 Light Fixtures	End Mount	100	500
FH-S	2, 3, or 4 Light Fixtures	Side Mount	100	500

## PORCELAIN WIRE HOLDERS

### PRODUCT FEATURES

- ▶ Porcelain & Galvanized Steel
- ▶ Varies According to Sizes



Cat. No.	Description	Trade Size	Std. Pkg.	Master Ctn.
PWH-L	With 2-1/4" Lag Bolt	2-3/4"	5	20
PWH-M	With Steel Clip for 1-1/4" to 3" Mast	1-1/4" to 3"	5	20

## TIE WIRE

### PRODUCT FEATURES

- ▶ Black Annealed Steel
- ▶ 16GA



Cat. No.	Description	Trade Size	Std. Pkg.
TW	Tie Wire	16GA, 400'	20