



# SUBMITTAL SHEETS

## WEATHERPROOF PRODUCTS - C

## SPECIFICATION & FEATURES

## UNIVERSAL WHILE-IN-USE COVERS EXTRA DUTY

### FEATURES:

- Horizontally and Vertically Mountable
- Impact-resistant thermoplastic construction
- Lockable to prevent accidental disconnects
- Pre-installed Adhesive Gasket
- **EXTRA DUTY** rated and conforms to NEMA 3R
- Conforms to UL standard 514D
- Meets 2014 NEC article 406.9(B)(1) Extra Duty specifications

### CERTIFICATION:



File E327021



Wet Location



WIU-1U-ED




WIU-1UD-ED



WIU-2UD-ED

**14 in 1**

**31 in 1**










Easy-to-Assemble Building-Block  
Style Adapters Accommodate  
a Wide Range of Wiring Devices










### CONFIGURATION DATA:

Part No.	Depth	Description	Std.Pkg.
WIU-1U-ED	2-3/4"	1-Gang Vert./Horiz.	8
WIU-1UD-ED	3-1/2"	1-Gang Vert./Horiz	8
WIU-2UD-ED	3-1/2"	2-Gang	6

#### One-Gang Cover Base Configuration:

Duplex	GFCI	Toggle	1-3/8" Round	1-9/16"~1-5/8" Round	1-11/16" Round	2-1/8" Round
						
Duplex Adapter	GFCI Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring Toggle Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring 1-3/8" Ring	2-1/8" Adapter 1-9/16"~1-5/8" Ring	2-1/8" Adapter 1-11/16" Ring	2-1/8" Adapter

#### Two-Gang Cover Base Configuration:

(2) Duplex	(2) GFCI	(2) Toggle	(2) 1-9/16"~1-5/8" Round	(2) 1-3/8" Round	(1) 1-9/16"~1-5/8" Round	(1) 1-11/16" Round	(1) 2-1/8" Round	(1) 2-5/8" Round
								
Duplex Adapter	GFCI Adapter	1-9/16"~1-5/8" Adapter Toggle Switch	1-9/16"~1-5/8" Adapter	1-9/16"~1-5/8" Adapter 1-3/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-9/16"~1-5/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-11/16" Ring	2-5/8" Adapter 2-1/8" Ring	2-5/8" Adapter



## SPECIFICATION & FEATURES

## EXTRA DUTY WHILE-IN-USE COVERS

### DESCRIPTION:

Orbit's Extra Duty Weatherproof Covers meet strict extra duty requirements set by the NEC while still offering easy installation and versatility. A variety of configurations are available for both 1 and 2 gang boxes

### FEATURES:

- Heavy-Duty Die-Cast Metal
- Patented Device Inserts
- Pre-installed Adhesive Gasket
- Clean installation with no break-off parts
- Extra-large cord opening
- Pad lockable design
- **EXTRA DUTY** rated



WIUM-1DH

**7 in 1**



WIUM-1DV

**7 in 1**



WIUM-2U

**31 in 1**

### CERTIFICATION:



File E227970










Wet Location










### CONFIGURATION DATA:

Part No.	Color	Multi-Height	Description	Std.Pkg.
WIUM-1DV	Gray	2-3/4" & 4"	1G Vertical "Extra Duty" While-In-Use Cover	10
WIUM-1DH	Gray	2-3/4" & 3-1/2"	1G Horizontal "Extra Duty" While-In-Use Cover	10
WIUM-2U	Gray	3-1/4" & 4-1/2"	2G Universal "Extra Duty" While-In-Use Cover	10

#### One-Gang Cover Base Configuration:

Duplex	GFCI	Toggle	1-3/8" Round	1-9/16"~1-5/8" Round	1-11/16" Round	2-1/8" Round
						
Duplex Adapter	GFCI Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring Toggle Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring 1-3/8" Ring	2-1/8" Adapter 1-9/16"~1-5/8" Ring	2-1/8" Adapter 1-11/16" Ring	2-1/8" Adapter

#### Two-Gang Cover Base Configuration:

(2) Duplex	(2) GFCI	(2) Toggle	(2) 1-9/16"~1-5/8" Round	(2) 1-3/8" Round	(1) 1-9/16"~1-5/8" Round	(1) 1-11/16" Round	(1) 2-1/8" Round	(1) 2-5/8" Round
								
Duplex Adapter	GFCI Adapter	1-9/16"~1-5/8" Adapter Toggle Switch	1-9/16"~1-5/8" Adapter	1-9/16"~1-5/8" Adapter 1-3/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-9/16"~1-5/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-11/16" Ring	2-5/8" Adapter 2-1/8" Ring	2-5/8" Adapter



## SPECIFICATION & FEATURES

## UNIVERSAL WHILE-IN-USE COVERS

### FEATURES:


- Device Inserts
- Clean installation with no break-off parts
- Heavy-Duty Die-Cast Metal (AL) Construction
- Pad lockable design
- Pre-installed Adhesive Gasket
- Extra large cord opening with rubber flaps that minimize debris
- Meets NEC Article 406.9 (A)(B)(1)(2) for damp and wet locations
- One-Gang cover is Horizontally and Vertically Mountable



Vert./Horiz

WIUM-1UD  
(Metal)

**14 in 1**



Easy-to-Assemble Building-Block  
Style Adapters Accommodate  
a Wide Range of Wiring Devices



WIUM-2UD  
(Metal)

**31 in 1**

### CERTIFICATION:



Wet Location

### CONFIGURATION DATA:

Part No.	Depth	Description	Std.Pkg.
White			
WIUM-1UD-W	3-1/2"	Metal, 1-Gang Vert./Horiz	8
WIUM-2UD-W	3-1/2"	Metal, 2-Gang	6





## SPECIFICATION & FEATURES

## UNIVERSAL FLAT DEVICE COVERS

### FEATURES:

- Device Inserts
- Clean installation with no break-off parts
- Heavy-Duty Die-Cast Metal with polycarbonate Inserts
- Pad lockable design
- Pre-installed Adhesive Gasket
- Meets NEC Article 406.9 (A) for damp and wet locations

### CERTIFICATION:



Wet Location



1C-U

**5 in 1**



2C-U

**16 in 1**




3C-U

**64 in 1**

### CONFIGURATION DATA:

Part No.			Description	Std.Pkg.
Gray	Bronze	White		
1C-U	1C-U-BR	1C-U-W	1-Gang	25
2C-U	2C-U-BR	2C-U-W	2-Gang	12
3C-U	-	-	3-Gang	10



#### 1C-U Includes:

- 1 x Toggle Switch
- 1 x Duplex Receptacle
- 1 x GFCI/Decorative
- 1 x 1-3/8"
- 1 x 1-9/16"~1-5/8"

#### 2C-U Includes:

- 2 x Toggle Switch
- 2 x Duplex Receptacle
- 2 x GFCI/Decorative
- 2 x 1-3/8"

#### 3C-U Includes:

- 3 x Toggle Switch
- 3 x Duplex Receptacle
- 3 x GFCI/Decorative
- 3 x 1-3/8"

Easy-to-Assemble Building-Block  
Style Adapters Accommodate  
a Wide Range of Wiring Devices



## SPECIFICATION & FEATURES

## 1-GANG BLANK AND DEVICE COVERS

### FEATURES & DIMENSION:

- 1-Gang Blank and Device Covers
- Zinc Die Cast (Except 1-BC, 1-BC-G, & 1CA-SW, 1CA-SW15, 1CA-SW20)
- Gasket included
- Device mounted
- Meets NEC Article 406.9 (A) for damp and wet locations
- Width: 2-3/4"
- Height: 4-1/2"

### CERTIFICATION:




File E227970



Listed



Wet Location



### CONFIGURATION DATA:

Part No.			Description	Std.Pkg.
Gray	Bronze	White		
1-BC	-	-	Aluminum Blank (Unpainted)	50
1-BC-G	1-BC-BR	1-BC-W	Heavy-Duty Galvanized Steel Blank	50
1C-TS	1C-TS-BR	1C-TS-W	Toggle Switch	25
1C-DH	1C-DH-BR	1C-DH-W	Duplex/Combo. Device - Horizontal	25
1C-DV	1C-DV-BR	1C-DV-W	Duplex/Combo. Device - Vertical	25
1C-GH	1C-GH-BR	1C-GH-W	GFCI - Horizontal	25
1C-GV	1C-GV-BR	1C-GV-W	GFCI - Vertical	25
1C-SV	1C-SV-BR	1C-SV-W	Single recept.or Switch Vertical - 1.406" Diameter	25
1C-PO20	-	-	20A Power Outlet - 1.594" Diameter	25
1C-PO30	-	-	30A Power Outlet - 1.750" Diameter	25
1C-PO40	-	-	40-50A Power Outlet - 2.281" Diameter	25
1CA-SW15	1CA-SW15-BR	1CA-SW15-W	Aluminum Lever + 15A Single-Pole Switch	25
1CA-SW20	1CA-SW20-BR	1CA-SW20-W	Aluminum Lever + 20A Single-Pole Switch	25
1CA-SW	1CA-SW-BR	1CA-SW-W	Aluminum Lever, compatible with Standard Toggle Switches	25
-	G-1 (Black only)	-	Universal 1-Gang Foam Gasket	50




## SPECIFICATION & FEATURES


## 1-GANG DEVICE COVERS WITH PADLOCK HASP

### FEATURES & DIMENSION:


- 1-Gang Device Covers
- Zinc Die Cast
- Gasket included
- Device mounted
- With Padlock Hasp
- Width: 2-3/4"
- Height: 4-1/2"
- Device Mounted: 1CL-DV, 1CL-SV
- Box Mounted: 1CL-GV



1CL-DV



1CL-GV



1CL-SV

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:


Part No.	Description	Std.Pkg.
1CL-DV	Duplex/Combo. Device - Vertical	25
1CL-GV	GFCI - Vertical	25
1CL-SV	Single recept. or Switch Vertical - 1.406" Diameter	25




## SPECIFICATION & FEATURES 1-GANG RAISED COVERS

### FEATURES & DIMENSION:


- 1-Gang Raised Covers
- Die Cast Copper-Free Aluminum
- Closure Plugs included(except RE-1)
- Gasket included
- Width: 2-7/8"
- Height: 4-5/8"



RE-1



RE-2



RE-3

### CERTIFICATION:



File E303572, E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.			Outlet Holes	Hole Size	Closure Plug QTY	Std.Pkg.
Gray	Bronze	White				
RE-1	RE-1-BR	RE-1-W	1	1/2"	-	25
RE-2	RE-2-BR	RE-2-W	2	1/2"	1	25
RE-3	RE-3-BR	RE-3-W	3	1/2"	2	25




## SPECIFICATION & FEATURES


## PLASTIC 1-GANG DEVICE COVERS

### FEATURES & DIMENSION:


- 1-Gang Device Covers
- Polycarbonate Composite
- Gasket included
- Device mounted
- Meets NEC Article 406.9 (A) for damp and wet locations
- Width: 2-3/4"
- Height: 4-1/2"



1CP-DH



1CP-DV



1CP-GV

### CERTIFICATION:



File E323779



Wet Location

### CONFIGURATION DATA:

Part No.		Description	Std.Pkg.
Gray	White		
1CP-DH	1CP-DH-W	Duplex/Combo. Device - Horizontal	20
1CP-DV	1CP-DV-W	Duplex/Combo. Device - Vertical	20
1CP-GV	1CP-GV-W	GFCI - Vertical	20



## SPECIFICATION & FEATURES

## 2-GANG BLANK AND DEVICE COVERS

### FEATURES & DIMENSION:

- 2-Gang Blank and Device Covers
- Zinc Die Cast (Except 2-BC, 2-BC-G, & 2CA-2SW, 2CA-SW15)
- Powder Coat Finish
- Gasket included
- Device mounted
- Meets NEC Article 406.9 (A) for damp and wet locations
- Width: 4-9/16"
- Height: 4-1/2"

### CERTIFICATION:




File E227970



Listed



Wet Location



### CONFIGURATION DATA:

Part No.			Description	Std.Pkg.
Gray	Bronze	White		
2-BC	-	-	Aluminum Blank (unpainted)	25
2-BC-G	2-BC-BR	2-BC-W	Heavy-Duty Galvanized Steel Blank	25
2C-2D	2C-2D-BR	2C-2D-W	Two duplex receptacles	12
2C-2G	2C-2G-BR	2C-2G-W	Two GFCI	12
2C-2S	2C-2S-BR	2C-2S-WH	Single recept. or Two switches- 1.406" diameter	12
2CA-SW15	2CA-SW15-BR	2CA-SW15-W	Aluminum Two levers + Two 15A Single-Pole Switches	12
2C-GD	-	-	One GFCI, One Duplex	12
2C-SD	-	-	One Duplex, One Single recept. - 1.406" diameter	12
2C-GS	-	-	One GFCI, one switch or Single recept. - 1.406" diameter	12
2C-DH	-	-	Oversized One Duplex - Horizontal device mount unit has K.O.'s for box mounting	12
2CL-PO60	-	-	One 30, 50, 60 Amp 3 & 4 Wire 12 With Built-In Padlock Hasp - 2.641" diameter	12
2CA-2SW	2CA-2SW-BR	2CA-2SW-W	Two Aluminum Levers, compatible with Standard Toggle Switches	12
-	G-2 (Black Only)	-	Universal 2-Gang Foam Gasket	50




## SPECIFICATION & FEATURES


## 3-GANG BLANK AND DEVICE COVERS

### FEATURES & DIMENSION:


- 3-Gang Blank and Device Covers
- Zinc Die Cast
- Gray Powder Coat Finish
- Gasket included
- Device mounted
- Width: 6-3/8"
- Height: 4-1/2"




3-BC



3C-3D



3C-3G



3C-3S

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.	Description	Std.Pkg.
3-BC	Aluminum Blank	10
3C-3D*	Three Duplex receptacles	20
3C-3G*	Three GFCI	20
3C-3S*	Three Single recept. or Switches - 1.406" Diameter	20

\*While Supplies Last







## SPECIFICATION & FEATURES 1-GANG BOXES 2" DEEP

### FEATURES & DIMENSION:


- Die Cast Copper-Free Aluminum
- Premium Powder Coat Finish
- Closure Plugs included
- Ground Screw installed
- Lugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 2-3/4"
- Height: 4-1/2"
- Depth: 2"




1B50-3  
1B75-3  
1B100-3



1B50-4  
1B75-4



1B50-5  
1B75-5



1B50-5X  
1B75-5X

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:


Part No.			Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray	Bronze	White					
1B50-3	1B50-3-BR	1B50-3-W	3	1/2"	2	18.3	20
1B50-4	1B50-4-BR	1B50-4-W	4	1/2"	2	18.3	20
1B50-5	1B50-5-BR	1B50-5-W	5	1/2"	3	18.3	20
1B50-5X	-	-	5	1/2"	3	18.3	20
1B75-3	1B75-3-BR	1B75-3-W	3	3/4"	2	18.3	20
1B75-4	1B75-4-BR	1B75-4-W	4	3/4"	2	18.3	20
1B75-5	1B75-5-BR	1B75-5-W	5	3/4"	3	18.3	20
1B75-5X	-	-	5	3/4"	3	18.3	20
1B100-3	-	-	3	1"	2	18.3	20




## SPECIFICATION & FEATURES 1-GANG DEEP BOXES 2-5/8" DEEP

### FEATURES & DIMENSION:


- Die Cast Copper-Free Aluminum
- Gray Finish
- Closure Plugs included
- Ground Screw installed
- Lugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 2-3/4"
- Height: 4-1/2"
- Depth: 2-5/8"



1DB50-3  
1DB75-3  
1DB100-3



1DB50-4  
1DB75-4



1DB50-5X  
1DB75-5X  
1DB100-5X

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
1DB50-3	3	1/2"	2	23.8	12
1DB50-4	4	1/2"	2	23.8	12
1DB50-5X	5	1/2"	3	23.8	12
1DB75-3	3	3/4"	2	23.8	12
1DB75-4	4	3/4"	2	23.8	12
1DB75-5X	5	3/4"	3	23.8	12
1DB100-3	3	1"	2	23.8	12
1DB100-5X	5	1"	3	23.8	12



## SPECIFICATION & FEATURES 2-GANG BOXES 2" DEEP

### FEATURES & DIMENSION:

- Die Cast Copper-Free Aluminum
- Premium Powder Coat Finish
- Closure Plugs included
- Ground Screw installed
- Lugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 4-9/16"
- Height: 4-1/2"
- Depth: 2"

### CERTIFICATION:




File E227970




Listed




Wet Location




2B50-3  
2B75-3  
2B100-3




2B50-4  
2B75-4  
2B100-4




2B50-5  
2B75-5




2B50-5X  
2B75-5X  
2B100-5X




2B50-6X  
2B75-6X



2B50-7  
2B75-7



2B50-7X  
2B75-7X



2B50-9  
2B75-9

### CONFIGURATION DATA:

Part No.			Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray	Bronze	White					
2B50-3	2B50-3-BR	2B50-3-W	3	1/2"	2	30.5	12
2B50-4	-	-	4	1/2"	2	30.5	12
2B50-5	2B50-5-BR	2B50-5-W	5	1/2"	3	30.5	12
2B50-5X	-	-	5	1/2"	3	30.5	12
2B50-6X	-	-	6	1/2"	3	30.5	12
2B50-7	-	-	7	1/2"	4	30.5	12
2B50-7X	-	-	7	1/2"	4	30.5	12
2B50-9	-	-	9	1/2"	4	30.5	12
2B75-3	2B75-3-BR	2B75-3-W	3	3/4"	2	30.5	12
2B75-4	-	-	4	3/4"	2	30.5	12
2B75-5	2B75-5-BR	2B75-5-W	5	3/4"	3	30.5	12
2B75-5X	-	-	5	3/4"	3	30.5	12
2B75-6X	-	-	6	3/4"	3	30.5	12
2B75-7	-	-	7	3/4"	4	30.5	12
2B75-7X	-	-	7	3/4"	4	30.5	12
2B75-9	-	-	9	3/4"	4	30.5	12
2B100-3	2B100-3-BR	2B100-3-W	3	1"	2	30.5	12
2B100-4	-	-	4	1"	2	30.5	12
2B100-5X	-	-	5	1"	3	30.5	12



[www.orbitelectric.com](http://www.orbitelectric.com)

Application and Performance Specification Information is Subject to Change Without Notification

LOS ANGELES, CA 1-800-90-ORBIT



# **SPECIFICATION & FEATURES      2-GANG DEEP BOXES 2-5/8" DEEP**

## **FEATURES & DIMENSION:**

- Die Cast Copper-Free Aluminum
- Gray Finish
- Closure Plugs included
- Ground Screw installed
- Lugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 4-9/16"
- Height: 4-1/2"
- Depth: 2-5/8"

## **CERTIFICATION:**




File E227970




Listed



Wet Location



2DB50-5  
2DB75-5  
2DB100-5



2DB75-7X  
2DB100-7X

## **CONFIGURATION DATA:**


Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
2DB50-5	5	1/2"	3	39.1	9
2DB75-5	5	3/4"	3	39.1	9
2DB100-5	5	1"	3	39.1	9
2DB75-7X	7	3/4"	4	39.1	9
2DB100-7X	7	1"	4	39.1	9



## SPECIFICATION & FEATURES 3-GANG DEEP BOXES 2-5/8" DEEP

### FEATURES & DIMENSION:

- Die Cast Copper-Free Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included
- Ground Screw installed
- Lugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 6-3/8"
- Height: 4-1/2"
- Depth: 2-5/8"



3DB50-7  
3DB75-7  
3DB100-7

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
3DB50-7	7	1/2"	4	54	10
3DB75-7	7	3/4"	4	54	10
3DB100-7	7	1"	4	54	10




## SPECIFICATION & FEATURES


## PLASTIC BLANK COVER WITH GASKET

### FEATURES:

- Patented design
- Use with 1PB or 2PB
- With Gasket
- Made In USA



1PC



2PC

### CERTIFICATION:



Listed

Patented design



Wet Location

### CONFIGURATION DATA:

Part No.		Dimension		No. of Gangs	Std.Pkg.
Gray	White	Width (in)	Height (in)		
1PC-G	1PC-W	3"	4-3/4"	1	25
2PC-G	2PC-W	4-3/4"	4-3/4"	2	25




## SPECIFICATION & FEATURES


## PLASTIC MODIFIABLE WEATHERPROOF BOXES

### FEATURES:

- Patented design
- Field-Modifiable Box
- Embossed Guidelines for hole positioning
- Make hole anywhere
- Use with any device cover
- (2) 1/2" and (2) 3/4" Locknuts included
- Lugs Included
- Made In USA



1PB



2PB

### CERTIFICATION:



Listed

Patented design



Wet Location

### CONFIGURATION DATA:

Part No.		Dimension			No. of Gangs	Cu.Inch	Std.Pkg.
Gray	White	Width (in)	Height (in)	Depth (in)			
1PB-G	1PB-W	2-13/16"	4-5/8"	2-5/16"	1	22.5	25
2PB-G	2PB-W	4-9/16"	4-9/16"	2-9/16"	2	42.5	25






# **SPECIFICATION & FEATURES**

## **1-GANG EXTENSION RINGS**


### **1" DEEP**

#### **FEATURES & DIMENSION:**


- Die Cast Copper-Free Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included (except EXR-1)
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 2-3/4"
- Height: 4-1/2"
- Depth: 1"



EXB50-4  
EXB75-4



EXB50-6  
EXB75-6



EXR-1

#### **CERTIFICATION:**



File E227970



Listed



Wet Location

#### **CONFIGURATION DATA:**

Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
EXB50-4	4	1/2"	4	9.5	12
EXB50-6	6	1/2"	6	9.5	12
EXB75-4	4	3/4"	4	9.5	12
EXB75-6	6	3/4"	6	9.5	12
EXR-1	-	-	-	10	24




## SPECIFICATION & FEATURES


## 1-GANG FLANGED EXTENSION BOXES 1-1/2" DEEP

### FEATURES & DIMENSION:


- Die Cast Copper-Free Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 3-1/2"
- Height: 5-1/4"
- Depth: 1-1/2"



EXF50-2  
EXF75-2



EXF50-4  
EXF75-4



EXF50-6  
EXF75-6

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:


Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
EXF50-2	2	1/2"	2	13.5	10
EXF50-4	4	1/2"	4	13.5	10
EXF50-6	6	1/2"	6	13.5	10
EXF75-2	2	3/4"	2	13.5	10
EXF75-4	4	3/4"	4	13.5	10
EXF75-6	6	3/4"	6	13.5	10




## SPECIFICATION & FEATURES 2-GANG EXTENSION RINGS 1" DEEP

### FEATURES & DIMENSION:


- Die Cast Copper-Free Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included (except EXR-2)
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Width: 4-9/16"
- Height: 4-1/2"
- Depth: 1"



2EXB50-6  
2EXB75-6



2EXB50-8  
2EXB75-8



EXR-2

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.	Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray					
2EXB50-6	6	1/2"	6	15	9
2EXB75-6	6	3/4"	6	15	9
2EXB50-8	8	1/2"	6	15	9
2EXB75-8	8	3/4"	6	15	9
EXR-2	-	-	-	16.3	12




## SPECIFICATION & FEATURES


## 4" ROUND BOXES & EXTENSION RINGS

### FEATURES & DIMENSION:


- Die Cast Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included(except EXR-R)
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Diameter: 4"
- Depth: 1-1/2"
- RB50-5 and RB75-5 are UL listed for Fixture/Luminaire Support of 50lbs or less



RB50-5  
RB75-5



EXR50-4  
EXR75-4



EXR-R

### CERTIFICATION:



File E227970



Listed



Wet Location

### CONFIGURATION DATA:

Part No.			Outlet Holes	Hole Size	Closure Plug QTY	Cu.Inch	Std.Pkg.
Gray	Bronze	White					
RB50-5	RB50-5-BR	RB50-5-W	5	1/2"	4	15.8	16
RB75-5	-	-	5	3/4"	4	15.8	16
EXR50-4	-	-	4	1/2"	4	19	16
EXR75-4	-	-	4	3/4"	4	19	16
EXR-R	-	-	-	-	-	19	50



## SPECIFICATION & FEATURES 4" ROUND COVERS

### FEATURES & DIMENSION:

- Die Cast Aluminum
- Premium Gray Powder Coat Finish
- Closure Plugs included(except RBC-4&RC-1)
- Individually shrink-wrapped with barcode
- Retail shelf packaging
- Diameter: 4"

### CERTIFICATION:




File E316426




Listed




Wet Location




RBC-4



RC-1




RC-2




RC-3D

Can be mounted  
on a 3" Plaster Ring



RC-3



G-R

### CONFIGURATION DATA:

Part No.					Outlet Holes	Hole Size	Closure Plug QTY	Std.Pkg.
Natural	Gray	Bronze	Black	White				
RBC-4*	-	-	-	-	-	-	-	25
-	RC-1	RC-1-BR	-	RC-1-W	1	1/2"	-	25
-	RC-2	RC-2-BR	-	RC-2-W	2	1/2"	1	25
-	RC-3D	-	-	-	3	1/2"	2	25
-	RC-3	RC-3-BR	-	RC-3-W	3	1/2"	2	25
G-R					Foam Gasket		-	25

\*Stamped Aluminum



## SPECIFICATION & FEATURES

### DESCRIPTION:

Orbit Industries' 2" Deep 1-Gang Cast Device Boxes with Dead End are pull boxes for wiring devices and provide room to splice and tap conductors. They are for use with Rigid/IMC conduits in both outdoor and indoor area.

The standard opening accommodates switches and receptacles, and can be used in areas of rough usage.

Trade Size from 1/2" To 1"

### CERTIFICATION:

UL file E227970, conforms to UL 514A


### 1-GANG CAST DEVICE BOXES DEAD END 2" DEEP 1/2" TO 1"



### FEATURES:

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc electroplated for added corrosion protection
- Dead-end configurations
- For both outdoor and indoor use

### LINE DRAWINGS:



### CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.	Master Ctn.
1MFS-50	1/2"	2.19	6.07	2.93	1	5
1MFS-75	3/4"	2.19	6.07	2.93	1	5
1MFS-100	1"	2.19	6.07	2.93	1	5



## SPECIFICATION & FEATURES

### DESCRIPTION:

Orbit Industries' 2-7/10" Deep 1-Gang Cast Device Boxes with Dead End are pull boxes for wiring devices and provide room to splice and tap conductors.

They are for use with Rigid/IMC conduits in both outdoor and indoor area.


The standard opening accommodates switches and receptacles, and can be used in areas of rough usage.

Trade Size from 1/2" To 1"

### CERTIFICATION:

UL file E227970, conforms to UL 514A


## 1-GANG DEEP CAST DEVICE BOXES DEAD END 2-7/10" DEEP 1/2" TO 1"



### FEATURES:

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc electroplated for added corrosion protection
- Dead-end configurations
- For both outdoor and indoor use

### LINE DRAWINGS:



### CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.	Master Ctn.
1MFD-50	1/2"	2.9	6.09	2.97	1	5
1MFD-75	3/4"	2.9	6.09	2.97	1	5
1MFD-100	1"	2.9	6.09	2.97	1	5





## SPECIFICATION & FEATURES


### DESCRIPTION:

Orbit Industries' 2" Deep 1-Gang Cast Device Boxes Feed Through are pull boxes for wiring devices and provide room to splice and tap conductors. They are for use with Rigid/IMC conduits in both outdoor and indoor area. The standard opening accommodates switches and receptacles, and can be used in areas of rough usage. Trade Size from 1/2" To 1"

### CERTIFICATION:

UL file E227970, conforms to UL 514A


## 1-GANG CAST DEVICE BOXES FEED THROUGH 2" DEEP 1/2" TO 1"



### FEATURES:

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc electroplated for added corrosion protection
- Feed Through configurations
- For both outdoor and indoor use

### LINE DRAWINGS:



### CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.	Master Ctn.
1MFSC-50	1/2"	2.19	6.08	2.94	1	5
1MFSC-75	3/4"	2.19	6.08	2.94	1	5
1MFSC-100	1"	2.19	6.08	2.94	1	5



## SPECIFICATION & FEATURES


### DESCRIPTION:

Orbit Industries' 2-7/10" Deep 1-Gang Cast Device Boxes Feed Through are pull boxes for wiring devices and provide room to splice and tap conductors.

They are for use with Rigid/IMC conduits in both outdoor and indoor area. The standard opening accommodates switches and receptacles, and can be used in areas of rough usage.

Trade Size from 1/2" To 1"

**1-GANG DEEP CAST DEVICE  
BOXES FEED THROUGH  
2-7/10" DEEP  
1/2" TO 1"**




### CERTIFICATION:

UL file E227970, conforms to UL 514A

### FEATURES:

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc electroplated for added corrosion protection
- Feed Through configurations
- For both outdoor and indoor use

### LINE DRAWINGS:



### CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.	Master Ctn.
1MFDC-50	1/2"	2.9	6.11	2.97	1	5
1MFDC-75	3/4"	2.9	6.11	2.97	1	5
1MFDC-100	1"	2.9	6.11	2.97	1	5



## SPECIFICATION & FEATURES

### 1-GANG CAST DEVICE BOX COVERS AND GASKET

#### DESCRIPTION:

Orbit Industries' 1-Gang Cast Device Box Covers and Gasket are for use with FS and FD cast device box. There are two different materials: Malleable Iron and Steel with 4 types of device configurations: Blank, Duplex, Toggle Switch, GFI.

#### CERTIFICATION:

Meet UL 514B Standard

#### FEATURES:

- Zinc Electroplated
- For use with FS&FD cast device box



1MFC-B



1MFC-D



1MFC-TS



1SFC-B



1SFC-D



1SFC-G



1SFC-TS



FG-1

#### CONFIGURATION DATA:

Part No.	Material	Description	Std. Pkg.
1MFC-B	Malleable Iron	Blank	20
1MFC-D	Malleable Iron	Duplex	20
1MFC-TS	Malleable Iron	Guarded Toggle Switch	20
1SFC-B	Steel	Blank	25
1SFC-D	Steel	Duplex	25
1SFC-TS	Steel	Unguarded Toggle Switch	25
1SFC-G	Steel	GFI	25
FG-1	Neoprene	Neoprene Gasket	50



## SPECIFICATION & FEATURES SWIMMING POOL JUNCTION BOXES

### FEATURES:

- Metal/Plastic
- For use with installation of underwater pool lights
- For connection to 120V or low voltage below normal water level of the pool
- Meets NEC Article 680.52 (A)(B)
- Solid Brass Wiring Platform with grounding post and 3 ground terminals for use with metallic or PVC conduit



SJB-50/100



SJB100-3




SJB100-3-W



SJB100-5



SJB100-5-W



SJB-ROD

### CERTIFICATION:

### CONFIGURATION DATA:

Part No.	Description	Size & Remarks	Std.Pkg.
SJB-50/100	Two 1/2", One 1" outlets With 1" to 1/2" port adapter Black Lexan Cover with built-in gasket Brass bottom	3.5"W x 5.38"H x 2"D 22.0 Cu. In.	1
SJB100-3	Two 3/4", One 1" outlets <b>Black</b> Lexan Material with built-in gasket Brass Terminal Block, Brass Ground Lug	4"Dia. X1.75"D 14.0 Cu. In. (Use with PVC Pipe)	1
SJB100-3-W	Two 3/4", One 1" outlets <b>White</b> Lexan Material with built-in gasket Brass Terminal Block, Brass Ground Lug	4"Dia. X1.75"D 14.0 Cu. In. (Use with PVC Pipe)	1
SJB100-5	One 1/2", Two 3/4", Two 1" outlets <b>Black</b> Lexan Material with built-in gasket Brass Terminal Block, Brass Ground Lug	5"Dia. X 2"D 23.0 Cu. In. (Use with PVC Pipe)	1
SJB100-5-W	One 1/2", Two 3/4", Two 1" outlets <b>White</b> Lexan Material with built-in gasket Brass Terminal Block, Brass Ground Lug	5"Dia. X 2"D 23.0 Cu. In. (Use with PVC Pipe)	1
*SJB-ROD	4-Ft. Solid PVC Support Rod for Lexan Boxes	1/2" Dia X 4'	2

\* While Supplies Last



## SPECIFICATION & FEATURES LAMP HOLDER ACCESSORIES



BASE



BASE-R



BASE-SB



TB-LV

### CONFIGURATION DATA:

Part No.	Description	Colors Available	Std.Pkg.
BASE	Surface-Mount Bracket 1/2" Female, Cast Aluminum	*VG	10
BASE-R	Round Surface-Mount Bracket 1/2" Female, Cast Aluminum	BK, BR, GN, VG, WH	10
BASE-SB	Round Surface-Mount Bracket 1/2" Female, Solid Brass	Antique Brass, Ant. Brz, Acid Grn	10
TB-LV	Tree-Hugger Canopy, Low-Voltage	BR, GN, VG, WH	1

\*While Supplies Last



## SPECIFICATION & FEATURES LAMP HOLDERS

### FEATURES:

- Cast Aluminum
- 120V
- 90W Max

### CERTIFICATION:




File E303572



Listed



Wet Location



LH150-SG


Includes Premium Silicon Gasket

### CONFIGURATION DATA:

Part No.					Description	Std.Pkg.
Gray	Bronze	Black	White	Green		
LH150-SG-GY	LH150-SG-BR	LH150-SG-BK	LH150-SG-W	-	Lampholder with Premium Silicon Outer Gasket	25



## SPECIFICATION & FEATURES WEATHERPROOF ACCESSORIES



LUG




SW-SP



G



SG



WG-38



BH-50

### CONFIGURATION DATA:

Part No.	Description	Colors	Std.Pkg.
LUG	Mounting Lugs, Each unit is a poly bag containing 2 lugs and 2 screws	Natural	100
SW-SP	1/2" Brass Spacer for mounting a Toggle Switch in a Lever Switch Cover	Natural	100
G	Inner Fiber Gasket for LH150 Weatherproof Lamp Holder	-	250
SG	Premium Silicon Outer Sealing Gasket for LH150 Weatherproof Lamp Holder	-	25
WG-38	PAR38 Wire Guard for Weatherproof Lamp Holders, Zinc-Plated Steel	-	5
BH-50	1/2" Zinc-Die Cast Weatherproof Box Holder	-	25







## SPECIFICATION & FEATURES WEATHERPROOF CLOSURE PLUGS

### FEATURES & DIMENSION:


- Zinc Die Cast in 1/2" and 3/4" sizes
- Aluminum Die Cast in 1"



PL-50



PL-75



PL-100

### CERTIFICATION:

Meet UL Standard

### CONFIGURATION DATA:


Part No.			Description	Std.Pkg.	Master Ctn.
Gray	Bronze	White			
PL-50	PL-50-BR	PL-50-W	1/2" Closure Plug, 100 bags of 5	5	500
PL-75	PL-75-BR	PL-75-WH	3/4" Closure Plug, 100 bags of 5	5	500
PL-100	-	-	1" Closure Plug, 100 bags of 2	2	200



## SPECIFICATION & FEATURES PHOTOELECTRIC CONTROLS

### FEATURES:

- 1.5VA Power Consumption
- 6-20 Lx On Level
- 30-60 Lx Off Level
- 2-Year Warranty



### CERTIFICATION:



File E224007 / E348511



Wet Location



### CONFIGURATION DATA:

Part No.	Description	Rating		Std.Pkg.
		Tungsten	Ballast	
PC-1	120V 50/60Hz, Standard Contractor Grade	2000 W	1900VA	12
PC-1-277	208/277V 50/60Hz, Standard Contractor Grade	2000 W	1900VA	12
PC-1S	120V 50/60Hz, Swivel-Type	1200 W	1000VA	12
PC-1SH	120V 50/60Hz, High-Wattage Swivel-Type	2000 W	1900VA	12
PC-1F	120V 50/60Hz, Wire-In Flush Model	500 W	850VA	12
PC-1F-277	208/277V 50/60Hz, Wire-In Flush Model	500 W	850VA	12
PC-1P	120V 50/60Hz, with Weatherproof Plate & Gasket	500 W	850VA	12
PC-1T	120~277V 50/60Hz, Twist Lock E-Ballast: 8A @120VAC, 5A @208-277VAC	1000 W	1800VA	12

