



**Catalog#: REDUCING BUSHINGS**  
**REDUCING BUSHINGS**

**Description:**

Orbit Industries' reducing bushings are used with threaded rigid or IMC conduits to reduce the size of female hubs in order to accommodate smaller sized conduits or male threaded hubs. Orbit Industries' reducing bushings have rugged steel construction and they are durable. The rugged steel construction ensures mechanical protection to the conduit and designated electrical junction box or enclosure. In damp locations, reducing bushings are also of excellent corrosion protection with zinc electroplated.

**Features:**

- Machined Steel
- Electroplated Zinc
- Meets Federal Spec. A-A-50553

**Certifications:****UL File Number:**

[E310658](#)

CAT NO	UPC	TRADE SIZE	STD PKG	MASTER CTN
RB-50/38	8-35243-03234-7	1/2 to 3/8	100	500
RB-75/50	8-35243-03221-7	3/4 to 1/2	100	500
RB-100/50	8-35243-03222-4	1 to 1/2	50	250
RB-100/75	8-35243-03223-1	1 to 3/4	50	250
RB-125/50	8-35243-03732-8	1-1/4 to 1/2	20	100
RB-125/75	8-35243-03733-5	1-1/4 to 3/4	20	100
RB-125/100	8-35243-03734-2	1-1/4 to 1	20	100
RB-150/50	8-35243-03735-9	1-1/2 to 1/2	10	50
RB-150/75	8-35243-03736-6	1-1/2 to 3/4	10	50
RB-150/100	8-35243-03737-3	1-1/2 to 1	10	50
RB-150/125	8-35243-03738-0	1-1/2 to 1-1/4	10	50
RB-200/50	8-35243-03739-7	2 to 1/2	10	50
RB-200/75	8-35243-03740-3	2 to 3/4	10	50
RB-200/100	8-35243-03741-0	2 to 1	10	50
RB-200/125	8-35243-03742-7	2 to 1-1/4	10	50
RB-200/150	8-35243-03743-4	2 to 1-1/2	10	50
*RB-250/200	8-35243-00685-0	2-1/2 to 2	10	50
*RB-300/200	8-35243-05342-7	3 to 2	10	50
*RB-300/250	8-35243-05343-4	3 to 2-1/2	10	50
*RB-350/250	8-35243-00430-6	3-1/2 to 2-1/2	5	20

\*Malleable iron

