



Catalog#: OEU580H
50-80 CFM ECONOMY SERIES, DC MOTOR & HUMIDITY SENSOR

Category FANS
Page [J3](#)
Barcode 8-35243-02380-2

Features:

Housing:

- Dimensions: 9" L x 9" W x 5-3/4" H
- Corrosion-Resistant 26 GA Galvanized Steel Housing
- Adjustable double bar hanger system that extends up to 24"
- Includes detachable 4" round duct with built-in draft damper

Motor and Blower:

- Power rating of 120V/60Hz
- Permanently lubricated, quick installation motor
- Energy efficient, brushless two speed DC motor for low speed continuous ventilation at 50 CFM
- Built-in dip switch to adjust high fan speed setting to 80 CFM
- Built-in overload disconnect for safety and longer motor life
- Low RPM for quiet performance
- ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille:

- Modern and elegant design
- Torsion spring clips included for easy mounting
- Grille Dimension: 10-3/10" x 10-1/4"

Humidity Sensor:

- Adjustable from 50 to 100% relative humidity
- Fan will elevate to high speed when Humidity exceeds desired setting

Warranty 2 year limited warranty
Document [Installation Instruction](#)
Certifications



Catalog Number	Duct Diameter	Air Volume	Static Pressure	Noise	Power Consumption	Power Rating	Energy Efficiency
OEU580H	4"	50 CFM	0.25 w.g.	N/A	11 W	120V / 60Hz	4.54 CFM / W
		80* CFM	0.1 w.g.	1.5 sone	11 W		7.27 CFM / W

