

H1 | LED Flood & Area Lights

*AWC-LFL7 SERIES

PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 7H x 6V NEMA Type
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage & CCT
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES




Adjustable Color Temperature (CCT) Knob
(cover included)



AWC-LFL7-KN



AWC-LFL7-T



DIP Switch with Cover Weatherproof with cover on

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
AWC-LFL7-50W-KN	120~277V	15W/ 20W/ 30W/ 50W	3000K/ 4000K/ 5000K/ 5700K	1,920 lm/ 2,560 lm/ 3,840 lm/ 6,403 lm	70W/ 100W/ 175W MH
AWC-LFL7-50W-T					

LFL7 SERIES

PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ 7H x 6V NEMA Type
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES



LFL7-15W-KN



LFL7-15W-T



LFL7-30W-KN



LFL7-30W-T



LFL7-50W-KN



LFL7-50W-T

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LFL7-15W-WW-KN	120~277V	15W	3000K	1,870 lm	50W MH
LFL7-15W-WW-T		15W	3000K	1,870 lm	50W MH
LFL7-15W-CW-KN		15W	5000K	1,937 lm	50W MH
LFL7-15W-CW-T		15W	5000K	1,937 lm	50W MH
LFL7-30W-WW-KN		30W	3000K	3,936 lm	100W MH
LFL7-30W-WW-T		30W	3000K	3,936 lm	100W MH
LFL7-30W-CW-KN		30W	5000K	4,040 lm	100W MH
LFL7-30W-CW-T		30W	5000K	4,040 lm	100W MH
LFL7-50W-CW-KN		50W	5000K	6,218 lm	175W MH
LFL7-50W-CW-T		50W	5000K	6,218 lm	175W MH

SCAN FOR MORE INFO

