

LCM7 SERIES

PRODUCT FEATURES

- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Prismatic Polycarbonate Lens with Weatherproof Gasket
- ▶ TYPE VS Distribution
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES



Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LCM7-40W-CW	120~277V	40W	5000K	4,814 lm	150W MH
LCM7-60W-CW		60W		7,074 lm	175W MH
LCM7-75W-CW		75W		9,900 lm	250W MH

ACCESSORIES Sold Separately



LCM7-M

Microwave Motion Sensor

LTL SERIES

PRODUCT FEATURES

- ▶ UL Listed for Damp Location
- ▶ Stainless Steel Lamp Cage
- ▶ 3 Prong, Male Plug with 10FT 18AWG Cord
- ▶ 3 Prong, hidden built-in Socket
- ▶ Stainless Steel Portable Hook with flexible spring
- ▶ Ambient Operating Temp: -40°C / -40°F to 60°C / 140°F
- ▶ 50,000 Life Hours
- ▶ 5 Year Limited Warranty

CERTIFICATES




LTL Series can connect up to 14pcs of 60W fixtures, 8pcs of 100W fixtures, 5pcs of 150W fixtures, or a combination of the three, not exceeding 900W at the same time

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LTL-60W-CW	120~277V	60W	5000K	7,200 lm	250W MH
LTL-100W-CW		100W		12,000 lm	400W MH
LTL-150W-CW		150W		18,000 lm	600W MH

ACCESSORIES Sold Separately

SCAN FOR MORE INFO



LTL-FS

Floor Stand Bracket



Shown Installed



LTL-TS

Tripod Stand Bracket



Shown Installed