

H3 | LED Flood & Area Lights

LFL10 SERIES

PRODUCT FEATURES


- ▶ UL Listed for Wet Location
- ▶ Die Cast Aluminum Housing
- ▶ UV Resistant Bronze Powder Coat Finish
- ▶ Polycarbonate Lens with Weatherproof Gasket
- ▶ TYPE III Distribution
- ▶ Ambient Operating Temp: -40°C / -40°F to 40°C / 104°F
- ▶ 50,000 Life Hours
- ▶ Adjustable Wattage Models (120~277V 150W/300W/400W)
- ▶ Pre-installed Photocell With Cover
- ▶ 0-10V/PWM/VR Dimmable
- ▶ 5 Year Limited Warranty

CERTIFICATES



DIMMABLE

SCAN FOR MORE INFO



Note: Keep power switch cover on to maintain waterproof integrity

Catalog No.	Voltage	System Wattage	Color Temp.	Lumens	Wattage Equiv.
LFL10-80W-P	120~277V	80W	5000K	11,000 lm	250W MH
LFL10-100W-P		100W		13,125 lm	400W MH
LFL10-150W-P		50W/ 80W/ 100W/ 150W		6,650 lm/ 10,640 lm/ 13,300 lm/ 20,137 lm	175W/ 250W/ 400W/ 750W MH
LFL10-230W-P		230W		33,457 lm	1,000W MH
LFL10-300W-P		150W/ 200W/ 240W/ 300W		21,600 lm/ 28,800 lm/ 34,560 lm/ 41,466 lm	750W/ 1,000W MH
LFL10-400W-P		230W/ 300W/ 350W/ 400W		32,430 lm/ 42,300 lm/ 49,350 lm/ 56,047 lm	1,000W/ 1,200W MH
LFL10-150W-P-480V	277~480V	150W		18,933 lm	750W
LFL10-230W-P-480V		230W		31,735 lm	1,000W MH
LFL10-300W-P-480V		300W		37,025 lm	1,000W MH
LFL10-400W-P-480V		400W		57,435 lm	1,200W MH

ACCESSORIES Sold Separately

