

STEEL EMT SLIP COUPLING SET-SCREW TYPE

PRODUCT FEATURES

- ▶ Electroplated Zinc
- ▶ Used to join two ends of EMT together
- ▶ Diamond shape inspection window to ensure both ends of conduits are visible
- ▶ Back out center screw stop as necessary to slip coupling over conduit
- ▶ Fully install center screw stop between conduits



Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
SESCS-50 <small>NEW</small>	1/2"	50	500
SESCS-75 <small>NEW</small>	3/4"	25	250
SESCS-100 <small>NEW</small>	1"	10	100
SESCS-125 <small>NEW</small>	1-1/4"	-	25
SESCS-150 <small>NEW</small>	1-1/2"	-	25
SESCS-200 <small>NEW</small>	2"	-	20
SESCS-250 <small>NEW</small>	2-1/2"	-	12
SESCS-300 <small>NEW</small>	3"	-	12
SESCS-350 <small>NEW</small>	3-1/2"	-	6
SESCS-400 <small>NEW</small>	4"	-	6



1/2" to 1"



1-1/4" to 4"

ZINC DIE CAST DOUBLE-SNAP CABLE CONNECTOR

PRODUCT FEATURES

- ▶ Zinc Die Cast
- ▶ 105°C rated throat insulator
- ▶ Fast and Tool-free installation
- ▶ Removable and Reusable
- ▶ For FMC, AC, MCI, MCI-A, HCF, RWFC
- ▶ Dry location



Cat. No.	Description	Trade Sides	Std. Pkg.	Master Ctn.
DSC-38	DOUBLE-SNAP CABLE CONNECTOR WITH INSULATOR Steel/AL AC: 14/2 (0.40") - 10/3 (0.618") Steel MCI: 0.395" - 0.638" AL MCI: 0.40" - 0.618" Steel/AL MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL HCF MCI-A: 14/2 (0.395") - 10/3 (0.638") AL RWFC: 3/8"	3/8"	50	500
DSC-38C	CUT-IN DOUBLE-SNAP CABLE CONNECTOR WITH INSULATOR, FOR OLD WORK Steel/AL AC: 14/2 (0.40") - 10/3 (0.618") Steel/AL MCI: 14/2 (0.395") - 10/3 (0.638") Steel/AL MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL HCF MCI-A: 14/2 (0.395") - 10/3 (0.638") Steel/AL FMC: 3/8"	3/8"	50	500



DSC-38



DSC-38C



Full Selection of Flex/AC/MC Fittings on pages D11-19