CLCSL SERIES

CONDUIT LOCKING CONNECTOR WITH SEISMIC WIRING HOLES

PRODUCT FEATURES

- Fits 4", 4-11/16", and 4O junction boxes as well as Orbit's patented EALB/S
- Available for 1/2" and 3/4" threaded conduits.
- Hooks prevent rotation of fixtures such as security cameras and emergency lighting
- Holes allow for use of seismic wiring for added protection against seismic disturbances
- Includes set-screw and locknut for secure fixture installations

PATENT PENDING

ORBIT INDUSTRIES EXCLUSIVE

Cat. No.	Trade Size	Std. Pkg.	Master Ctn.
CLCSL-50	1/2"	10	100
CLCSL-75	3/4"	10	100

PREVENT FIXTURE ROTATION

Before Installation

After Installation Prevents Rotation

SOLUTION TO SECURE FIXTURES FROM ROTATING

SET SCREW
Secure Installation of Conduit

LOCKNUT
Included

WIRING
Added Stability Against Seismic Disturbances

HOOKS
Prevents Rotation

(1) Fasten CLCSL to threaded conduit

(2) Tighten set-screw to secure conduit

(3) Secure conduit to box using locknut

(4) Mount seismic wires to surroundings and tie to holes of CLCSL

Intertek