


*LMR16-3W

PRODUCT FEATURES

- ▶ Wattage: 3W
- ▶ Voltage: 12V
- ▶ Base: GU5.3
- ▶ Housing: Aluminum Alloy, Silver
- ▶ Min Operating Temp: -30°C / -22°F
- ▶ Life Hours: 50,000
- ▶ Beam Angle: 30°
- ▶ Lens: Frosted Acrylic
- ▶ 3 Year Warranty




Catalog No.	Efficacy	Color Temp.	Emission Color	Lumens	CRI	Wattage Equiv.
LMR16-3W-CW	46 lm/W	4700K	Cool White	128 lm	70	20W MH

*LMR16-4W

PRODUCT FEATURES

- ▶ Wattage: 3W
- ▶ Voltage: 12V
- ▶ Base: GU5.3
- ▶ Housing: Aluminum Alloy, Silver
- ▶ Min Operating Temp: -30°C / -22°F
- ▶ Life Hours: 50,000
- ▶ Beam Angle: 30°
- ▶ Lens: Frosted Acrylic
- ▶ 3 Year Warranty




Catalog No.	Efficacy	Color Temp.	Emission Color	Lumens	CRI	Wattage Equiv.
LMR16-4W-CW	42 lm/W	4700K	Cool White	170 lm	70	20W MH

*LMR16-3W-EB

PRODUCT FEATURES

- ▶ Wattage: 3W
- ▶ Voltage: 120V
- ▶ Base: E26/E27
- ▶ Housing: Die Cast Aluminum
- ▶ Min Operating Temp: -20°C / -4°F
- ▶ Life Hours: 50,000
- ▶ Beam Angle: 30°
- ▶ Lens: Frosted Acrylic
- ▶ 3 Year Warranty



Catalog No.	Efficacy	Color Temp.	Emission Color	Lumens	CRI	Wattage Equiv.
LMR16-3W-EB-WW	63 lm/W	3000K	Warm White	190 lm	70	20W MH

LED Lighting