



Ventilation Fans | J



INNOVATIVE VENTILATION SOLUTIONS

EASY INSTALLATION

Adjustable double-hanger bar system expands up to 24" for between-joist installation. Mounting tabs on the fan housing allow for direct attachment to joist or truss. Snap-in wiring connections allow for easy addition of light / night light accessories, as well as quick motor change-outs.

CODE COMPLIANT

Orbit vent fans are HVI certified for airflow and sound performance. Most of our fixtures are ENERGY STAR® listed, helping owners meet LEED, NAHB Green Building, and Title 24 efficiency standards. All fans are either UL or ETL Listed.

SELECTION

Orbit offers a wide selection of IAQ solutions for meeting code and saving energy. Choose complete fan units with LED lights, DC motors, and motion / humidity sensors. Or, select housing, motors, and grille designs à la carte with **Orbit Contractor Packs**.

QUIET AND LONG-LASTING

Permanently lubricated motors sustain continuous operation up to 30,000 hours for AC motors, and upwards of 60,000 hours for DC motors. Fully enclosed DC motors and AC condenser motors ensure quiet operation as low as 0.5 to 0.3 sone.

Orbit Industries' Ventilation Fans and Fanlights meet energy efficiency and IAQ standards set by most U.S. cities.

Designed with the contractor in mind, our fans are quick and easy to install. Orbit fixtures are long-lasting, and prove a valuable investment for the homeowner.





Universal Vent Fans and Fanlights | Pg. J1~3



Orbit's Universal Series feature adjustable, long-lasting DC Motors that adapt to any whole-house system. The Universal Economy Series (OEU) is a cost-effective solution for continuous (low speed) operation. The OEU series features a dip-switch for selecting 50CFM or 80CFM settings. The Universal Deluxe Series (ODU) doubles as whole house fan and spot ventilator. For continuous ventilation, dial Universal Deluxe models between 30 to 80 CFM. For intermittent (high speed) settings, a dip-switch lets the user preset from 80 to 140 CFM. High speeds settings are triggered by a built-in Motion Sensor (ODU Only) or Humidity Sensor. Available with LED fanlight.

Recessed Fanlight | Pg. J5



Deluxe Recessed Architectural Fanlights (OE80RL Series) incorporate a powerful yet quiet 80 CFM fan behind a recessed downlight aperture. At just 1.0 sone, the only way occupants will know the OE80RL is working will be the fresh air it produces. The OE80 Series is ETL Listed for use over bathtubs or showers when connected to GFCI protected branch circuits.

Deluxe Series | Pg. J4, 6~7



Deluxe Series Fans and Fanlights (OD Series) are the most powerful - yet surprisingly quiet - single-speed bathroom fans in Orbit's catalog. The OD Series is ideal for spot ventilation, with motors that produce air volume from 80CFM to 120CFM. The OD Series' very quiet operation ranges from 0.5 to 2.0 sones. The OD Series is also easy to install, with simple on-off switch control.

Contractor Packs | Pg. J11~12



Orbit Contractor Packs give professionals the option to customize vent fan components for new construction or room side retrofits. Professionals can install the Fan Housing of their choice prior to ceiling installation. Once ceilings are finished, the professional can install a variety of Grilles, Motors and even Fanlight Kits to match room aesthetics. Contractor Packs help reduce instances of damaged grills and motors, as well as lost parts, on busy construction sites leading to jobs being completed faster.

**SERIES**

Model

CFM

Sones

Fanlight

Housing
Depth

Pg.

Universal Deluxe Fan With DC Motor & Motion Sensor	ODU814M	90 - 140	0.5 - 1.5	—	7-5/8"	J1
Universal Deluxe Fan With DC Motor & Humidity Sensor	ODU814H	90 - 140	<0.3 - 0.5	—	7-5/8"	J2
Universal Deluxe Fanlight With DC Motor & Humidity Sensor	ODU814LLH	90 - 140	<0.3 - 0.5	LED	7-5/8"	J2
Universal Economy Fan With DC Motor & Humidity Sensor	OEU580H	80	1.5	—	5-3/4"	J3
Universal Economy Fanlight With DC Motor & Humidity Sensor	OEU580LLH	80	1.5	LED	5-3/4"	J3
Deluxe Fans With Humidity Sensor	OD80H	80	0.5	—	7-5/8"	J4
	OD110H	110	0.9	—	7-5/8"	J4
Deluxe Fanlights With Humidity Sensor	OD80LLH	80	0.5	LED	7-5/8"	J4
	OD110LLH	110	0.9	LED	7-5/8"	J4
Deluxe Recessed Fanlight	OE80RL	80	1.2	CFL	7-1/4"	J5
Deluxe Fans	OD80	80	0.8	—	7-5/8"	J6
	OD90	90	1.0	—	7-5/8"	J6
	OD110	110	1.5	—	7-5/8"	J6
	OD120	120	2.0	—	7-5/8"	J6
Deluxe Fanlights	OD80L	80	0.5	CFL	7-5/8"	J6
	OD90L	90	0.7	CFL	7-5/8"	J6
	OD110L	110	1.2	CFL	7-5/8"	J6
	OD120L	120	1.5	CFL	7-5/8"	J6
Deluxe Heat Fanlight	ODHFL110	110	0.5	CFL	7-5/8"	J7
Economy Plus Fans	OEP80	80	1.3	CFL	7-5/8"	J8
	OEP90	90	1.5	CFL	7-5/8"	J8
	OEP110	110	2.0	CFL	7-5/8"	J8
Standard Plus Fans	OSP50	50	2.5	—	3-11/16"	J9
	OSP70	70	4.0	—	3-11/16"	J9
Standard Plus Fanlight	OSP70L	70	4.0	CFL	5-1/8"	J9
	OSP70LL	70	4.0	LED	5-1/8"	J9
Standard Heat Fanlight	OEHFL70	70	4.0	CFL	5-3/4"	J10
Contractor Packs						J11
Wiring Devices						J13
Fan Accessories						J14



DC Motor & Motion Sensor

Housing Dimensions

- 11-3/8" L x 10-1/2" W x 7-5/8" H

Housing

- Corrosion-Resistant Galvanized Steel
- Adjustable double bar hanger system that extends up to 24"
- Sloped ceiling mounting capability up to 45 degrees
- Includes **detachable 4" and 6"** polymeric collar with lightweight built-in back draft damper
- IC Rated up to R40 insulation

Motor

- Power rating of 120V/60Hz
- Permanently lubricated motor
- Energy efficient, brushless **two speed DC motor** for low speed continuous ventilation from 30-80 CFM
- Quick installation of motor and impeller assembly
- Built-in dip switch to adjust high fan speed setting from 80 to 140 CFM
- Built-in overload disconnect for safety and longer motor life
- Low RPM for quiet operation
- ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit
- Life Hours: 60,000

Grille

- Modern and elegant design
- Durable Polymeric Resin
- Torsion spring clips included for easy mounting

Motion Sensor

- Activates higher motor speed and delayed timer
- Adjustable timer from 5 to 60 minutes


Warranty

- 2 year limited warranty



**Refer to Pg. J15
for Fan Curve (1)**

Grille



Cat. No.		ODU814M			
Static pressure	Inches w.g.	0.1"			
Duct diameter	Inches	6"			
Air volume	CFM	90	110	120	140
Noise	Sone	0.5	0.9	1.2	1.5
Power consumption	Watts	8.1	10.3	12.2	15.6
Energy efficiency	CFM/Watts	12.23	11.49	10.80	9.41
Power rating	V/Hz.	120/60			
Weight	lbs	10.5			
Standard Qty.		1			

DC Motor & Humidity Sensor

Housing Dimensions

- 11-3/8" L x 10-1/2" W x 7-5/8" H

Housing

- Corrosion-Resistant Galvanized Steel
- Adjustable double bar hanger system that extends up to 24"
- Includes **detachable 4" and 6"** round duct with built-in draft damper
- IC Rated up to R40 insulation

Motor and Blower

- Power rating of 120V/60Hz
- Permanently lubricated, quick installation motor
- Energy efficient, brushless **two speed DC motor** for low speed continuous ventilation from 30-80 CFM
- Built-in dip switch to adjust high fan speed setting from 80 to 140 CFM
- Built-in overload disconnect for safety and longer motor life
- Low RPM for quiet operation
- ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit
- Life Hours: 60,000

Grille

- Modern and elegant design
- Durable Polymeric Resin
- Torsion spring clips included for easy mounting

Humidity Sensor

- Adjustable from 50 to 100% relative humidity
- Adjustable timer from 5 to 60 minutes

Warranty

- 2 year limited warranty

Lighting

LED FANLIGHTS

Included:
10 Watt LED Lamp



ODU814H



ODU814LLH

*Refer to Pg. J15
for Fan Curve (1)*

Model		FANS		LED FANLIGHTS	
Cat. No.		ODU814H*		ODU814LLH	
Static pressure	Inches w.g.	0.1"			
Duct diameter	Inches	6"			
Air volume	CFM	90	110	120	140
Noise	Sone	<0.3	<0.3	<0.3	0.5
Power consumption	Watts	8.1	10.3	12.2	15.6
Energy efficiency	CFM/Watts	12.23	11.49	10.80	9.41
Power rating	V/Hz.	120/60			
Weight	lbs	10.5		11.8	
Standard Qty.		1		1	



TITLE 24 COMPLIANT



DC Motor & Humidity Sensor

Housing Dimensions

- › 9" L x 9" W x 5-3/4" H

Housing

- › Corrosion-Resistant 26 GA Galvanized Steel Housing
- › Adjustable double bar hanger system that extends up to 24"
- › Includes detachable 4" round duct with built-in draft damper

Motor and Blower

- › Power rating of 120V/60Hz
- › Permanently lubricated, quick installation motor
Quick installation of motor and impeller assembly
- › Energy efficient, brushless **two speed DC motor** for low speed continuous ventilation at 50 CFM
- › Built-in dip switch to adjust high fan speed setting to 80 CFM
- › Built-in overload disconnect for safety and longer motor life
- › Low RPM for quiet performance
- › ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille

- › Modern and elegant design
- › Torsion spring clips included for easy mounting
- › Grille Dimension: 10-1/2" x 10-1/4"

Humidity Sensor

- › Adjustable from 50 to 100% relative humidity
- › Fan will elevate to high speed when Humidity exceeds desired setting

Warranty

- › 2 year limited warranty

Lighting

LED FANLIGHTS

Included:
11 Watt LED Lamp



OEU580H



OEU580LLH

*Refer to Pg. J15
for Fan Curve (2)*

Model		FANS	LED FANLIGHTS
Cat. No.		NEW OEU580H	NEW OEU580LLH
Static pressure	Inches w.g.	0.1"	0.1"
Duct diameter	Inches	4"	4"
Air volume	CFM	80	80
Noise	Sone	1.5	1.5
Power consumption	Watts	11.0	11.0
Energy efficiency	CFM/Watts	7.27	7.27
Power rating	V/Hz.	120/60	120/60
Weight	lbs	3.2	3.2
Standard Qty.		1	1
Master Qty.		8	8



Humidity Sensor

Housing Dimensions

- 11-3/8" L x 10-1/2" W x 7-5/8" H

Housing

- Corrosion-Resistant Galvanized Steel
- Adjustable double bar hanger system that extends up to 24"
- Sloped ceiling mounting capability up to 45 degrees
- Includes **detachable 4" and 6"** round duct with built-in draft damper
- IC Rated up to R40 insulation

Motor and Blower

- Power rating of 120V/60Hz
- Permanently lubricated, energy efficient motor
- Low RPM for quiet operation
- Built-in overload disconnect for safety and longer motor life
- ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille

- Modern and elegant design
- Durable Polymeric Resin
- Torsion spring clips included for easy mounting

Humidity Sensor

- Adjustable from 50 to 100% relative humidity
- Adjustable timer from 5 to 60 minutes

Warranty

- 2 year limited warranty

Lighting

LED FANLIGHTS

Included:
10 Watt LED Lamp



OD80H & OD110H



OD80LLH & OD110LLH

**Refer to Pg. J15
for Fan Curve (3)**

Model		FANS		LED FANLIGHTS	
Cat. No.		OD80H*	OD110H*	OD80LLH	OD110LLH
Static pressure	Inches w.g.	0.1"	0.1"	0.1"	0.1"
Duct diameter	Inches	4" & 6"	4" & 6"	4" & 6"	4" & 6"
Air volume	CFM	80	110	80	110
Noise	Sone	0.5	0.9	0.5	0.9
Power consumption	Watts	24.4	27.6	24.4	27.6
Energy efficiency	CFM/Watts	3.79	4.77	3.79	4.77
Power rating	V/Hz.	120/60	120/60	120/60	120/60
Weight	lbs	9.9	9.9	11.2	11.2
Standard Qty.		1	1	1	1



Recessed Fanlight

Housing Dimensions

- 12-5/8" L x 8" W x 7-1/4" H

Housing

- Corrosion-Resistant Galvanized Steel
- Adjustable double bar hanger system that extends up to 24"
- Sloped ceiling mounting capability up to 45 degrees
- Includes **4" and 5"** metal duct adapter with built-in back draft damper
- Adjustable lamp base holder for flushed lighting mounts
- IC rated up to R40 insulation

Motor and Blower

- Power rating of 120V/60Hz
- Permanently lubricated, energy efficient motor
- Quick installation of motor and impeller assembly
- Quiet operation and minimal vibration transfer
- Built-in overload disconnect for safety and longer motor life
- ETL and cETL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille & Trim

- Modern and elegant design
- Durable Polymeric Resin
- Torsion spring clips included for easy mounting

Warranty

- 2 year limited warranty

Lighting

FANLIGHTS

Not Included:
23W CFL
Base Compact
Fluorescent Lamp



OE80RL

**Refer to Pg. J15
for Fan Curve (4)**



Model		FANLIGHTS
Cat. No.		OE80RL
Static pressure	Inches w.g.	0.1"
Duct diameter	Inches	4"
Air volume	CFM	80
Noise	Sone	1.2
Power consumption	Watts	19.3
Energy efficiency	CFM/Watts	4.98
Power rating	V/Hz.	120/60
Weight	lbs	9.2
Standard Qty.		1



Housing Dimensions

- 9-1/8" L x 9-1/8" W x 7-5/8" H

Housing

- Heavy-duty steel housing coated with rust proof paint
- Adjustable double bar hanger system that extends up to 24"
- 4" exhaust pipe connection
- Wired for both fan or fanlight
- Effortless side electrical connection
- Termination damper to prevent cold air infiltration
- Light, durable, and sturdy

Motor and Blower

- Power rating of 120V/60Hz
- Permanently lubricated, energy efficient motor with ball bearings designed for continuous use
- Quick installation of motor and impeller assembly
- Effortless snap in wiring connection
- UL and cUL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille

- Contemporary design - with or without light kit
- Durable white ABS for easy cleaning
- Torsion spring clips included for easy installation
- Electronic ballast

Warranty

- 2 year limited warranty

Lighting

FANLIGHTS

Included:
 2 - 18 Watt Flicker-Free,
 Electronic Ballast
 Compact Fluorescent Lamps



FANLIGHTS MODEL

*Refer to Pg. J16
 for Fan Curve (5)*

Model	FANS				FANLIGHTS			
Cat. No.	OD80	*OD90	OD110	*OD120	*OD80L	*OD90L	*OD110L	*OD120L
Static pressure Inches w.g.	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"	0.1"
Duct diameter Inches	4"	4"	4"	4"	4"	4"	4"	4"
Air volume CFM	80	90	110	120	80	90	110	120
Noise Sone	0.8	1.0	1.5	2.0	0.5	0.7	1.2	1.5
Power consumption Watts	27.9	28.4	30.6	32.1	31.6	32.1	33.7	37.0
Energy efficiency CFM/Watts	2.87	3.17	3.59	3.74	2.53	2.80	3.26	3.24
Power rating V/Hz.	120/60	120/60	120/60	120/60	120/60	120/60	120/60	120/60
Weight lbs	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Standard Qty.	1	1	1	1	1	1	1	1
Master Qty.	4	4	4	4	4	4	4	4





Heat Fanlight

Housing Dimensions

- › 10-1/2" L x 11-3/8" W x 7-5/8" H

Housing

- › Corrosion-Resistant Galvanized Steel
- › Double hanger bar mounting brackets that are adjustable up to 24"
- › Sloped ceiling mounting capability up to 45 degrees
- › Effortless side electrical connection
- › Includes detachable 4" polymeric collar with lightweight built-in back draft damper

Motor

- › Power rating of 120V/60Hz
- › Permanently lubricated, energy efficient motor
- › Built-in overload disconnect for safety and longer motor life
- › Low RPM for quiet operation
- › ETL and cETL listed for tub/shower enclosure when used with a GFCI branch circuit

Heater

- › 1000W PTC ceramic heater with metal blower
- › Thermal auto-self protection
- › Electric shock protection

Grille

- › Thermal paint 22 gauge sheet metal
- › Torsion spring clips included for easy installation

Warranty

- › 2 year limited warranty on parts


Lighting

FANLIGHTS

Not Included:
2 - 23 Watt GU24
Compact Fluorescent
Lamps



*Refer to Pg. J16
for Fan Curve (6)*



Cat. No.		ODHFL110
Static pressure	Inches w.g.	0.1"
Duct diameter	Inches	4"
Air volume	CFM	110
Noise	Sone	0.5
Power consumption	Watts	24.4
Energy efficiency	CFM/Watts	3.79
Power rating	V/Hz.	120/60
Weight	lbs	12.8
Standard Qty		1

*6" polymeric collar available upon request

Housing Dimensions

- 9-1/8" L x 9-1/8" W x 7-5/8" H

Housing

- Heavy-duty steel housing coated with rust proof paint
- Adjustable double bar hanger system that extends up to 24"
- Includes 4" exhaust pipe connection
- Wired for both fan only or fanlight
- Effortless side electrical connection
- Termination damper to prevent cold air infiltration
- Light, durable and sturdy

Motor and Blower


- Power rating of 120V/60Hz
- Permanently lubricated, energy efficient motor designed to continuously active
- Quick installation of motor and impeller assembly
- Effortless snap in wiring connection
- UL and cUL listed for tub/shower enclosure when connected to a GFCI protected branch circuit



**Refer to Pg. J16
for Fan Curve (7)**

Grille

- Contemporary design - with or without light kit
- Durable white ABS for easy cleaning
- Torsion spring clips included for easy mounting
- Electronic ballast



Warranty

- 2 year limited warranty



Model		FANS		
Cat. No.		OEP80	*OEP90	OEP110
Static pressure	Inches w.g.	0.1"	0.1"	0.1"
Duct diameter	Inches	4"	4"	4"
Air volume	CFM	80	90	110
Noise	Sone	1.3	1.5	2.0
Power consumption	Watts	31.2	24.5	27.0
Energy efficiency	CFM/Watts	2.56	3.67	4.07
Power rating	V/Hz.	120/60	120/60	120/60
Weight	lbs	9.2	9.9	9.9
Standard Qty.		1	1	1
Master Qty.		4	4	4



Housing Dimensions

- ▶ **OSP50 & OSP70:** 7-1/2" L x 7-5/16" W x 3-11/16" H
- ▶ **OSP70L:** 7-1/2" L x 7-1/8" W x 5-1/8" H "

Housing

- ▶ Corrosion-Resistant Galvanized Steel
- ▶ Built-in mounting ears for ceiling or wall installation
- ▶ Torsion mounting
- ▶ Wired for both fan or fanlight
- ▶ Includes **detachable 3" or 4"** polymeric collar

Motor and Blower

- ▶ Power rating of 120V/60Hz
- ▶ Permanently lubricated motor with plug for continuous run and easy removal
- ▶ Built-in overload disconnect for safety and longer motor life
- ▶ Low RPM for quiet performance
- ▶ Removable Centrifugal-type Blower Wheel
- ▶ UL and cUL listed for tub/shower enclosure when connected to a GFCI protected branch circuit

Grille

- ▶ Modern and elegant design
- ▶ Durable Polymeric Resin

Warranty

- ▶ 2 year limited warranty

Lighting

FANLIGHTS

Included:
1 - 13 Watt GU24
Compact Fluorescent
Lamp



LED FANLIGHTS

Included:
8.5 Watt LED Lamp



OSP50 & OSP70



OSP70L & OSP70LL

**Refer to Pg. J16
for Fan Curve (8)**

Model		FANS		FANLIGHTS	LED FANLIGHTS
Cat. No.		OSP50*	OSP70	OSP70L*	OSP70LL*
Statistic Pressure	Inches w.g.	0.1"	0.1"	0.1"	0.1"
Duct diameter	Inches	3"	4"	4"	4"
Air volume	CFM	50	70	70	70
Noise	Sone	2.5	4.0	4.0	4.0
Power consumption	Watts	45	45	45	45
Energy efficiency	CFM/Watts	1.10	1.55	1.55	1.55
Power rating	V/Hz.	120/60	120/60	120/60	120/60
Weight	lbs	5.1	5.1	6.4	6.4
Standard Qty.		1	1	1	1
Master Qty.		12	12	-	-



Housing Dimensions

- 14" L x 7-3/4" W x 5-3/4" H

Housing

- Galvanized housing resists humid conditions & changing attic temperatures, unlike plain steel housing used in many vents
- Ceiling/wall thickness indicator markings & built-in mounting tabs for quick installation
- Built-in junction box for easy wiring
- Precision balanced, molded fan blade for quiet operation
- Molded Duct Adaptor with built-in damper
- Combination Lamp Compartment & Aluminum Reflector
- Built-in medium base lampholder included



Motor and Heating

- 950 W fan-forced heating element
- Easy removal and installation of motor assembly with keyhole mounting bracket
- Permanently lubricated motor with plug for quick activations
- Units and service parts are CSA listed

Grille

- Attractive molded grille with spring clips for smooth fit against ceiling or wall
- Dishwasher-safe grille with Polycarbonate Light Lens for easy homeowner cleaning



Warranty


- 2 year limited warranty

Housing & Motor

5 3/4"



7 3/4"



Cat. No.		OEHFL70
Duct diameter	Inches	4"
Air volume	CFM	70
Noise	Sone	4.0
Finish Color		White
Master Qty.		4





Orbit's highly certified and energy efficient ventilation fan and fanlights are available in contractor packs for large projects and quick installations.


- *Easy and secure installation for reduced labor and costs*
- *Universal housing for reduced inventory and greater flexibility*
- *Fitted with the best fan motors in the ventilation market lasting up to 30,000 hours*
- *Optimal energy efficiency-reduces utility costs by up to 50%*
- *No sharp edges to reduce injury in the field*

ORDERING GUIDE



STEP 1

Select Housing



STEP 2

Select
Grille + Motor



ACCESSORIES 1

Fanlight
Conversion Kits



ACCESSORIES 2

Grille
Replacement



CONTRACTOR PACKS

STEP 1

Select Housing

STEP 2




Select
Grille + Motor




ACCESSORIES 1


Fanlight
Conversion Kits

ACCESSORIES 2

Grille
Replacement

Cat.No.		Description	Compatible Models
OSPH		Standard Housing 7-1/2" L x 7-5/16" W x 3-11/16" H 6 Per Carton	OSP50
OSPL-H		Standard Plus Housing 7-1/2" L x 7-1/8" W x 5-1/8" H 6 Per Carton	OSP70L
OEPH		Economy Plus Housing 9-1/8" L x 9-1/8" W x 7-5/8" H 4 Per Carton	OEP80

Cat.No.		Air Volume (CFM)	Description	Compatible Models
OSP50F		50CFM	Standard Plus 6 Per Carton 1 Grille + 1 Fan Motor	OSP50
OSP70L-F		70CFM	Standard Plus 6 Per Carton 1 Grille + 1 Fan Motor	OSP70L
OEP80F		80CFM	Economy Plus 4 Per Carton 1 Grille + 1 Fan Motor	OEP80

Cat.No.	Grille + light	Description	Compatible Models
*OVFM		4 Per Carton 2 - 18W Lamps + Fanlight Grille + Ballast	*OD80L *OD90L *OD110L *OD120L

Cat.No.		Description	Compatible Models
OEP-G		Economy Plus Grille	OEP80 *OEP90 OEP110
OD-G		Deluxe Grille	OD80 *OD90 OD110 *OD120
OEP-G		Deluxe & Economy Plus Grille for Fanlights	*OD80L *OD90L *OD110L *OD120L
OEP-L		Deluxe & Economy Plus Lens	*OD80L *OD90L *OD110L *OD120L



HUMIDITY SENSORS

PRODUCT FEATURES

CONDENSATION SENSORS (adjustable)

- ▶ Turns ON the fan when condensation is present and OFF when dry
- ▶ Adjust sensors to solve moisture problem
- ▶ Helps fight mold

QUE™ TECHNOLOGY

- ▶ Ultra moisture-sensing adaptive technology (patent pending)

COUNTDOWN TIMER (adjustable)

- ▶ You choose how long your fan will run
- ▶ Great for tenant and family use
- ▶ **MANUAL ON/OFF CONTROL**
- ▶ Manual light control allows you to control bathroom lighting
- ▶ Manual fan control for immediate ventilation

LED FAN INDICATOR LIGHT


- ▶ Lets you know the fan is ON
- ▶ **CONCEALED ADJUSTMENT SETTINGS**

- ▶ Tamper-proof settings cover

TITLE 24
COMPLIANT

Cat. No.	Description	Inner	Master
FS-3300-W NEW	Fan Switch Electrical Input: 120 volts @ 60Hz Max. Fan Load: 6 Amps	1	72
FS-3325-W NEW	Fan & Light Switch Electrical Input: 120 volts @ 60Hz Max. Fan Load: 6 Amps Max. Light Load: Fluorescent: 400 Watt Incandescent: 600 Watt LED/CFL: 150 Watt	1	72

NEW



blue LED light
Condensation Sentry
fan ON
fan OFF

FS-3300-W

NEW



blue LED light
Condensation Sentry
light ON/OFF
fan ON/OFF

FS-3325-W

RESIDENTIAL GRADE DECORATIVE SWITCHES

PRODUCT FEATURES

- ▶ 120~277 VAC
- ▶ Rocker-type
- ▶ Impact-Resistant Thermoplastic Body
- ▶ With Combination Head Screws

Cat. No.	Description	Color (Cat. No. - Color Code)				Std. Pkg.	Master Carton
		White	Ivory	Black	Almond		
2DS15	Double Rocker Switch, 15A, 120~277V Single-Pole Side Wire only	2DS15-W	2DS15-I	2DS15-BK	2DS15-A	10	200
3DS15	Triple Rocker Switch, 15A, 120~277V Single-Pole Push-In Back Wire only, with Ground Pigtail	3DS15-W	3DS15-I	3DS15-BK	3DS15-A	10	200



2DS15



3DS15

Ventilation Fans



FAN ACCESSORIES

45LT-D Compatible Models

OD80 OEP80
 *OD90 *OEP90
 OD110 OEP110
 *OD120

45LT-D-1212 Compatible Models

ODU814M OD80H
 ODU814H OD110H

Cat. No.	Description	Std. Pkg.
45LT-D	Ceiling Radiation Fire Damper 10" X 10"	1
45LT-D-1212 NEW	Ceiling Radiation Fire Damper 12" X 12"	1
GUEBA	GU24 to Edison Base adapter	10



45LT-D
 45LT-D-1212 **NEW**



GUEBA

REPLACEMENT BULBS

Cat. No.	Description	Std. Pkg.
PL23-GU-41K	23W GU24 Base Compact Fluorescent, 4100K	1



PL23-GU-41K

REPLACEMENT GRILLES


OFLGML Compatible Models

ODU814H
 OD80H
 OD110H


Cat. No.	Description	Std. Pkg.
OFLGML	Fan Light Grille Module with 10W LED Lamp	1




OFLGML




See Pg.J1 or Pg.J2 for Fan Info




See Pg.J3 for Fan Info




See Pg.J4 for Fan Info




See Pg.J5 for Fan Info




See Pg.J6 for Fan Info



See Pg.7 for Fan Info



See Pg.8 for Fan Info



See Pg.J9 for Fan Info