

Catalog No.:
Job/Title:
Notes:

# **SPECIFICATION & FEATURES**

### **DESCRIPTION:**

Orbit Industries' 4" Octagonal Concrete Boxes are used for concrete constructions. The 1/2", 3/4", 1" side knockouts and mounting tabs allow for easy installation. They are constructed from 16 gauge galvanized steel. Orbit Industries' selection includes concrete rings with depths ranging from 2" to 6".

## **CERTIFICATION:**

UL file E227970, conforms to UL514A. For Fixture/Luminaire Support of 50 lbs or less


# **FEATURES**

Knockout:

**50:** 1/2" K.O. **75:** 3/4" K.O. **100:** 1" K.O.

**4CB-F** is UL Rated for Fan Support of 35 LBS or Less; For Fixture/Luminaire Support of 90 LBS or Less **Other Concrete boxes** are UL Rated for Fixture/Luminaire Support of 50 LBS or Less

# 4" OCTAGONAL CONCRETE BOXES



#### **DIMENSIONS**

Diameter: 4"

Other Dimensions see below

#### **CONFIGURATION DATA**

Catalog No.	Depth	Knockouts		Curlo	Std.
		Sides 1,3,5,7	Sides 2,4,6,8	Cu.In.	Pkg.
2CB	2"	(1)-1/2"	(1)-3/4"	24.4	25
25CB	2-1/2"	(1)-1/2"	(1)-3/4"	30.5	25
3CB	3"	(1)-1/2"	(1)-3/4"	37.0	25
3CB-75/100	3"	(1)-3/4"	(1)-1"	37.0	25
35CB	3-1/2"	(2)-1/2"	(2)-3/4"	43.0	25
35CB-75/100	3-1/2"	(1)-3/4"	(1)-1"	43.0	25
4CB	4"	(2)-1/2"	(2)-3/4"	49.2	25
4CB-75/100	4"	(2)-3/4"	(2)-1"	49.2	25
4CB-F*	4"	Side 1, 5: (1)-1/2" Side 3, 7: (2)-1/2"	Side 2, 6: (1)-3/4" Side 4, 8: (2)-3/4"	49.2	25
5CB	5"	(2)-1/2"	(2)-3/4"	61.7	10
6CB	6"	(2)-1/2"	(2)-3/4"	73.5	10

\*Fan Rated



2CB 25CB 3CB 35CB 4CB 5CB 6CB 350

