

SPECIFICATION SHEET 2-Gang Floor Box Assembly Pop-up Type



FLBPU-DD-BR

FLBPU-DD-SS

FLBPU-LL-BR

FLBPU-LL-SS

FLBPU-DL-BR

FLBPU-DL-SS

DESCRIPTION:

Orbit's 2-Gang Floor Box Assembly Pop-up Type are used for either carpet, tile, or wood floors. Ears on the floor box are installed flush to finished floor using screws before installing the cover. Pop-up covers are accessible when needed and can be retracted when not in use. Covers have 20A tamper resistant duplex and low-voltage receptacles. In addition, Orbit's covers are available in Brass or Stainless Steel.

FEATURES:

- 125 VAC
- For use with carpet, tile or wood floor installation
- Rated for counter top applications following NEC Code
- Steel floor boxes must be installed flush with finished floor prior to final installation
- Includes cover, receptacle, screws and 2-Gang Floor Box
- Meets NEC Article 406.12 for tamper-resistant receptacles



SPECIFICATIONS:

Cat. No.	Box Type	Cover Style		
		Receptacle	Color	Std. Pkg.
FLBPU-DD-BR	2-Gang Box (4" x 7-7/8" x 3") 86.0 Cu. In.)	(2) 20A TR Duplex	Brass	10
FLBPU-DD-SS		(2) 20A TR Duplex	Stainless Steel	10
FLBPU-LL-BR		(2) Low-Voltage (CAT5E)	Brass	10
FLBPU-LL-SS		(2) Low-Voltage (CAT5E)	Stainless Steel	10
FLBPU-DL-BR		20A TR Duplex + Low-Voltage (CAT5E)	Brass	10
FLBPU-DL-SS		20A TR Duplex + Low-Voltage (CAT5E)	Stainless Steel	10

Floor Box Specifications:

Floor Box	Knockouts		Cu. In.
	Sides	Bottom	
2-Gang Pop-up	(6)-1/2" CKO & (6)-1" CKO	(6)-1/2" & (3)-3/4"	86.0

DIMENSIONS:

