

Catalog No.:
Job/Title:
Notes:

SPECIFICATION & FEATURES

DESCRIPTION:

Orbit Industries' 4" Octagon (40) Welded Boxes are used in the installation of light fixtures, and other electrical devices. They are constructed from 16 gauge galvanized steel. The 2-1/8" deep, welded boxes provide extra space for wires and devices, and non-metallic sheathed cable clamp is included for ease of installation. Selected models include an FB Bracket for direct mounts on studs or an LB bracket with spurs.

CERTIFICATION:

UL file E227970, conforms to UL514A. For Fixture/Luminaire Support of 50 lbs or less

FEATURES

Knockout:

50: 1/2" K.O.

Loom: Loom Pryouts

MKO: Moon K.O. (1/2" and 3/4" K.O.)

Bracket:

FB: (L: 7-1/4", W: 3/4") Offset (1/2") Mounts on flat side of

stud or joist

LB: (L: 2-3/8", W: 2-23/32") Offset (1/4") With spurs, slotted

holes for toe-nailing.

Clamp:


NM: Accommodates #14-2 to #10-3 Non-Metallic Cables with

ground

Mfg. Process:

WELDED

4" OCTAGON (40) WELDED DEEP BOXES 2-1/8" DEEP WITH NM



DIMENSIONS


Diameter: 4" **Depth:** 2-1/8" **Cu.In.:** 21.5


CONFIGURATION DATA

Catalog No.	Bracket &	Knockouts		Std.
	Setback	Sides	Bottom	Pkg.
4RDB-NM	-	(2)-MKO, (4)-Loom	(1)-1/2"	50
4RDB-NM-FB	FB, 1/2"	(1)-MKO, (4)-Loom	(1)-1/2"	25
4RDB-NM-LB	LB, 1/2"	(2)-MKO, (4)-Loom	(1)-1/2"	25



4RDB-NM





4RDB-NM-LB



