

Catal	00	No	
Cata	US.	INO.	

Job/Title:

Notes:

SPECIFICATION & FEATURES

DESCRIPTION:

Orbit Industries' 4" Square (4S) Drawn Boxes are used to install lighting fixtures, switches, and receptacles in ceilings and walls. They are constructed from 16 gauge galvanized steel. The 1-1/2" deep, drawn steel boxes include a preinstalled raised ground emboss at the bottom and 10-32 ground screw. Models have multiple 1/2" and 3/4" knockouts, and selected models include a side bracket to mount on stud walls or a 7" long solid #12AWG pigtail for secure grounding.

CERTIFICATION:

UL file E227970, conforms to UL514A. For Fixture/Luminaire Support of 50 lbs or less

FEATURES

Piqtail Features:

7" Solid Cu. #12AWG Pigtail Pre-assembled with Ground Emboss and 10-32 Ground Screw

Knockout:

50: 1/2" K.O.

75: 3/4" K.O.

CKO: Concentric K.O. (1/2" and 3/4" K.O.)

Bracket:

FB: (L: 7-3/8", W: 1-9/16") Offset (Flush) Mounts on flat side of stud Mfg. Process:

DRAWN


CONFIGURATION DATA

Catalog No.	Bracket &	Knockouts		Std.
Catalog No.	Setback	Sides	Bottom	Pkg.
D4SB-50	-	(12)-1/2"	(4)-1/2"	50
D4SB-50-PT	-	(12)-1/2"	(4)-1/2"	50
D4SB-50/75	-	(8)-1/2",(4)-3/4"	(2)-1/2",(2)-3/4"	50
D4SB-50/75-PT	-	(8)-1/2",(4)-3/4"	(2)-1/2",(2)-3/4"	50
D4SB-75	-	(8)-3/4"	(2)-1/2",(2)-3/4"	50
D4SB-75-PT	-	(8)-3/4"	(2)-1/2",(2)-3/4"	50
D4SB-CKO	-	(8)-1/2",(4)-CKO	(2)-1/2",(2)-3/4"	50
D4SB-50-FB	FB, Flush	(9)-1/2"	(4)-1/2"	24
D4SB-50/75-FB*	FB, Flush	(6)-1/2",(3)-3/4"	(2)-1/2",(2)-3/4"	24
D4SB-CKO-FB	FB, Flush	(6)-1/2",(3)-CKO	(2)-1/2",(2)-3/4"	24

* While Supplies Last



4" SQUARE (4S) DRAWN BOXES 1-1/2" DEEP



DIMENSIONS

Width:	4″
Height:	4"
Depth:	1-1/2"
Cu.In.:	21.0





D4SB-50



D4SB-75-PT



D4SB-50/75

D4SB-50/75-PT



D4SB-CKO



D4SB-75



D4SB-50/75-FB D4SB-CKO-FB



www.orbitelectric.com

Application and Performance Specification Information is Subject to Change Without Notification

LOS ANGELES, CA 1-800-90-ORBIT

D4SB-50-FB