

Catalog No.:
Job/Title:
Notes:

# **SPECIFICATION & FEATURES**

### **DESCRIPTION:**

Orbit Industries' 4" Square (4S) Boxes are used to install lighting fixtures, switches, and receptacles in ceilings and walls. They are constructed from 16 gauge galvanized steel. The 1-1/2" deep, welded boxes include non-metallic sheathed cable clamps for ease of installation. Selected models include metal stud brackets that engage on either side of a metal stud or a bracket to directly mount on a stud.

# **CERTIFICATION:**

UL file E227970, conforms to UL514A. For Fixture/Luminaire Support of 50 lbs or less (Except 4SB-NM-MS)

# **FEATURES**

#### Knockout:

**50:** 1/2" K.O.; **Loom**: Loom Pryouts; **MKO:** Moon K.O. (1/2" and 3/4" K.O.)

#### **Bracket:**

**FB**: (L: 7-3/8", W: 1-9/16") Offset (Flush) Mounts on flat side of stud **WB**: (L: 7-1/2", W: 1-9/16") Offset (Flush) With positioning spurs to

mount box on side of stud

**MS**: (L: 2-1/2", W: 1-3/8") Offset (Flush) Self-Gripping Metal Stud Bracket with Box Support Clip. Engages on either side of metal stud.

U.S. Patent No.: 8,262,043


# Clamp:


NM: Accommodates #14-2 to #10-3 Non-Metallic Cables with ground

Mfg. Process:

WELDED

# 4" SQUARE (4S) WELDED BOXES 1-1/2" DEEP WITH NM









#### **DIMENSIONS**

Width: 4" Height: 4" Depth: 1-1/2" Cu.ln.: 21.0

# **CONFIGURATION DATA**

Catalog No.	Bracket&	Knockouts		Std.
	Setback	Sides	Bottom	Pkg.
4SB-NM	-	(4)-1/2", (2)-MKO, (4)-Loom	(1)-1/2"	50
4SB-NM-FB	FB, Flush	(2)-1/2", (1)-MKO, (4)-Loom	(1)-1/2"	24
4SB-NM-MS*	MS, Self- Gripping+Box Support Clip	(2)-1/2", (1)-MKO, (4)-Loom	(1)-1/2"	24
4SB-NM-WB	WB, Flush	(2)-1/2", (1)-MKO, (4)-Loom	(1)-1/2"	24

<sup>\*</sup> While Supplies Last

