

SPECIFICATION & FEATURES

UNIVERSAL WHILE-IN-USE COVERS EXTRA DUTY

FEATURES:

- Horizontally and Vertically Mountable
- Impact-resistant thermoplastic construction
- Lockable to prevent accidental disconnects
- Pre-installed Adhesive Gasket
- **EXTRA DUTY** rated and conforms to NEMA 3R
- Conforms to UL standard 514D
- Meets 2014 NEC article 406.9(B)(1) Extra Duty specifications

CERTIFICATION:



File E327021



Wet Location




WIU-1U-ED

WIU-1UD-ED

14 in 1









WIU-2UD-ED

31 in 1

 Easy-to-Assemble Building-Block
Style Adapters Accommodate
a Wide Range of Wiring Devices










CONFIGURATION DATA:

Part No.	Depth	Description	Std.Pkg.
WIU-1U-ED	2-3/4"	1-Gang Vert./Horiz.	8
WIU-1UD-ED	3-1/2"	1-Gang Vert./Horiz	8
WIU-2UD-ED	3-1/2"	2-Gang	6

One-Gang Cover Base Configuration:

Duplex	GFCI	Toggle	1-3/8" Round	1-9/16"~1-5/8" Round	1-11/16" Round	2-1/8" Round
						
Duplex Adapter	GFCI Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring Toggle Adapter	2-1/8" Adapter 1-9/16"~1-5/8" Ring 1-3/8" Ring	2-1/8" Adapter 1-9/16"~1-5/8" Ring	2-1/8" Adapter 1-11/16" Ring	2-1/8" Adapter

Two-Gang Cover Base Configuration:

(2) Duplex	(2) GFCI	(2) Toggle	(2) 1-9/16"~1-5/8" Round	(2) 1-3/8" Round	(1) 1-9/16"~1-5/8" Round	(1) 1-11/16" Round	(1) 2-1/8" Round	(1) 2-5/8" Round
								
Duplex Adapter	GFCI Adapter	1-9/16"~1-5/8" Adapter Toggle Switch	1-9/16"~1-5/8" Adapter	1-9/16"~1-5/8" Adapter 1-3/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-9/16"~1-5/8" Ring	2-5/8" Adapter 2-1/8" Ring 1-11/16" Ring	2-5/8" Adapter 2-1/8" Ring	2-5/8" Adapter

