

SPECIFICATION & FEATURES

THREADED SERVICE ENTRANCE CONDUIT BODIES "SLB" SERIES

DESCRIPTION:

THREADED SERVICE ENTRANCE CONDUIT BODIES "SLB" SERIES



CERTIFICATION:



UL file E227970, Conforms to UL 514A



FEATURES:

- Die Cast Copper-Free Aluminum
- Gray color
- Suitable for wet location when used with Gasket and Cover
- NPT Thread Hubs
- With Die Cast Cover and Neoprene Gasket

LINE DRAWINGS:



CONFIGURATION DATA:

Part No.	Trade Size	A (in)	B (in)	C (in)	Std.Pkg.
SLB-50	1/2"	1-5/8"	1-3/8"	3-5/16"	20
SLB-75	3/4"	1-7/8"	1-9/16"	3-5/8"	20
SLB-100	1"	2-1/8"	2"	4-5/16"	10
SLB-125	1-1/4"	2-5/8"	2-7/16"	5-9/16"	10
SLB-150	1-1/2"	2-5/8"	2-5/8"	6-1/4"	6
SLB-200	2"	3-1/8"	3-1/8"	6-3/4"	3
SLBXL-200	2"	3-11/16"	3-7/16"	10-1/16"	1

