

SPECIFICATION & FEATURES

CONDUIT CLAMPS SNAP CLOSE 1/2" ~ 2" EMT

DESCRIPTION:

Orbit Industries' snap close conduit clamps can be installed vertically or horizontally to fit conduits in different directions. Conduits can be easily and fast snapped to the clamp. The clamps can be combined with other Orbit industries' fasteners to hang conduits to beams, purlins or rods.

CERTIFICATION:

UL file E328572, conforms to UL 2239.

FEATURES:

- Spring Steel
- Used for vertical or horizontal installations
- Snap-close
- When only one hole is provided use for EMT or Rigid; when two holes are provided use the first hole for Rigid, the second for EMT



CONFIGURATION DATA:

Part No.	FMC Size	MC/AC Size	EMT/Rigid Size	Hole Size	Hole Type	Load Capacity		Std. Pkg.
						Vertical	Horizontal	
F6M4I	3/8"	14-2 ~ 12-3	-	1/4"	Threaded	100 LB	25 LB	100
F812M4I	-	-	1/2", 3/4"	1/4"	Threaded	100 LB	25 LB	100
F16M4I	-	-	1"	1/4"	Threaded	100 LB	25 LB	100
F20M4I	-	-	1-1/4"	1/4"	Threaded	100 LB	25 LB	100
F24M4I	-	-	1-1/2"	1/4"	Threaded	100 LB	25 LB	100
F32M4I	-	-	2"	1/4"	Threaded	100 LB	25 LB	100
F6M	3/8"	14-2 ~ 12-3	-	9/32"	Plain	100 LB	25 LB	100
F812M	-	-	1/2", 3/4"	9/32"	Plain	100 LB	25 LB	100
F16M	-	-	1"	9/32"	Plain	100 LB	25 LB	100
F20M	-	-	1-1/4"	9/32"	Plain	100 LB	25 LB	100
F24M	-	-	1-1/2"	9/32"	Plain	100 LB	25 LB	100
F32M	-	-	2"	9/32"	Plain	100 LB	25 LB	100

