

SUBMITTAL SHEET

MALLEABLE GROUND BUSHINGS INSULATED WITH UNIVERSAL LAY-IN LUG

DESCRIPTION:

Malleable Ground Bushings Insulated with Universal Lay-In Lug
Trade size varies from 1/2" to 6".



FEATURES:

- 150°C rated Throat Insulator
- Malleable Iron
- Zinc Electroplated
- Aluminum Lay-In Lug for use with copper or aluminum grounding conductor
- Full Machine-Cut Internal Threads
- Meets Federal Spec. A-A-50553

CERTIFICATION:

UL file E310659, Conforms to UL 514B



CONFIGURATION DATA:

Part No.	UPC	Trade Size	Lug Range	Std.Pkg.	Master Ctn
MGBLL-50	835243053922	1/2"	#14 - #4	50	200
MGBLL-75	835243053939	3/4"	#14 - #4	25	100
MGBLL-100	835243053946	1"	#14 - #4	25	100
MGBLL-125	835243053953	1-1/4"	#14 - #4	10	50
MGBLL-125-10	835243021822	1-1/4"	#14 - #1/0	20	200
MGBLL-150	835243053960	1-1/2"	#14 - #4	10	50
MGBLL-150-10	835243021839	1-1/2"	#14 - #1/0	10	100
MGBLL-200	835243053977	2"	#14 - #4	10	50
MGBLL-200-10	835243021846	2"	#14 - #1/0	10	100
MGBLL-250	835243053984	2-1/2"	#6 - #250MCM	5	25
MGBLL-250-10	835243021853	2-1/2"	#14 - #1/0	-	50
MGBLL-300	835243053991	3"	#6 - #250MCM	5	25
MGBLL-300-10	835243021860	3"	#14 - #1/0	-	25
MGBLL-350	835243054004	3-1/2"	#6 - #250MCM	-	5
MGBLL-350-10	835243021877	3-1/2"	#14 - #1/0	-	10
MGBLL-400	835243054011	4"	#6 - #250MCM	-	5
MGBLL-400-10	835243021884	4"	#14 - #1/0	-	10
MGBLL-500	835243054028	DA	#6 - #250MCM	-	5
MGBLL-500-30*	835243021891	5"	#6 - #3/0	-	5
MGBLL-600	835243054035	6"	#6 - #250MCM	-	5
MGBLL-600-30*	835243021907	6"	#6 - #3/0	-	5

* No UL Listed

