

SUBMITTAL SHEET

MALLEABLE IRON INSULATED 45 DEG ANGLE LIQUIDTIGHT CONNECTORS

DESCRIPTION:

Orbit Industries' malleable iron insulated 45° angle liquid tight connectors are used on flexible metallic liquid tight conduits and Type B flexible non-metallic liquid tight conduits to positively bond conduits to boxes or enclosures in both wet and damp locations. In addition, when connectors are terminated in threadless openings, the included sealing washers provide liquid tight seals. The heavy duty locknuts included with every Orbit liquid tight connector ensures the continuity of the grounding. In damp locations, the connectors are also of excellent corrosion protection with zinc electroplated. The trade size varies from 3/8" to 4".



FEATURES:

- Malleable Iron
- Electroplated Zinc
- With Insulated Throat
- Insulated color may vary
- NPT Male Threads
- Suitable for use in hazardous locations: Class I, Division 2; Class II, Divisions 1 & 2; and Class III, Divisions 1 & 2 per NEC

CERTIFICATION:

UL file E310658, Conforms to UL 514B



CONFIGURATION DATA:

Part No.	UPC	Trade Size	Std.Pkg.	Master Ctn
MLT45-38	8-35243-03206-4	3/8"	25	150
MLT45-50	8-35243-03207-1	1/2"	25	150
MLT45-75	8-35243-03208-8	3/4"	10	100
MLT45-100	8-35243-03209-5	1"	5	50
MLT45-125	8-35243-03210-1	1-1/4"	5	40
MLT45-150	8-35243-03211-8	1-1/2"	4	20
MLT45-200	8-35243-03212-5	2"	1	15
MLT45-250	8-35243-05330-4	2-1/2"	-	1
MLT45-300	8-35243-05331-1	3"	-	1
MLT45-350	8-35243-05332-8	3-1/2"	-	1
MLT45-400	8-35243-05333-5	4"	-	1

